Form 3160-5 (September 2001)

UNITED STATES UNITED STATES UNITED STATES UNITED STATES ORM APPROVED DEPARTMENT OF THE INTERIOR 625 N. French Drive Expires: January

BUREAU OF LAND MANAGEMENT Hobbs, NM 88248

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

OMB No. 1004-013	ر 5
Expires: January 31, 2	200

5. Lease Serial No.	
LC 061873-B	
6. If Indian. Allottee or Tribe Name	

SUBMIT IN TRI	PUCATE - Other instruc	ctions on revers	e side	7. If Unit or CA	/Agreement, Name and/or No.	
l. Type of Well	<u> </u>					
Oil Well Gas Well	8. Well Name	8. Well Name and No.				
2. Name of Operator	Paduca 9 F	Paduca 9 Federal #1				
H.L. Brown Operating L.L.C. OGRID #213179					0.	
3a. Address		3b. Phone No. (include	le area code)	30 - 025 - 3		
300 W. Louisiana, Midland, Texas 79702 432 - 688 - 3726					ool, or Exploratory Area	
4. Location of Well (Footage, Sec., T, R., M., or Survey Description) 1980' FNL & 660' FWL					Paduca Delaware 11. County or Parish, State	
Unit E, Sec 9, T-25-S, R-32-E	Lea Count	y, NM				
12. CHECK APP	PROPRIATE BOX(ES) TO	INDICATE NATU	RE OF NOTICE, R	EPORT, OR O	THER DATA	
TYPE OF SUBMISSION		T	YPE OF ACTION			
	Acidize	Deepen	Production (Star	t/Resume)	Water Shut-Off	
Notice of Intent	Alter Casing	Fracture Treat	Reclamation		Well Integrity	
Subsequent Report	Casing Repair	New Construction	Recomplete		Other	
	Change Plans	Plug and Abandon	Temporarily Ab	andon		
Final Abandonment Notice	Convert to Injection	Plug Back	Water Disposal			
Notice of Spud and setting surface 07-03-04: MIRU Auger Air Drilli Drilled rat hole and mo 08-01-04: Finished rigging up, mi 08-02-04: Drilled 12-1/4" hole to 08-03-04: LD 8" collars and RU c guide shoe on bottom v 1 hour and rigged up B 200 sx "C" w/ 2% CaC up BOPs. BLM witness	e casing. Ing crew. Drilled 20" hole to 40' use hole to fit Key Rig #6. In the spud mud and spud well at 782'. TD surface hole at 3:30 A sasing crew. Ran 6 jts 8-5/8", 24 with a float insert at 737'. Ran ce J Services. Pumped 260 sx 35:61 at 14.8 PPG with a yield of 1.3 sed cementing. Total WOC times	and ran 16" pipe to 12:00 noon on 8-01- M and circulated for 14, J-55 followed by entralizers in the mid 15 Poz w/6% gel, 5% 34. Plug down at 11:0	oottom. Cemented pipe 04. 1 hour. POOH with pi 13 joints 8-5/8", 32#, J tle and top of the 1st ju 6 salt and ½# CF at 12	pe and BHA -55 and set at 78; t, and every 3rd ju	2'. Ran a Texas pattern of to the surface. Circulated	
14. 1 hereby certify that the foregoing Name (PrintedlTyped) Robert McNaughton	g is true and correct	Title Op	perations Manager/ Pet	roleum Engineer		
Signature Date 8-5-04						
	THIS SPACE FO	R FEDERAL OR S	TATE OFFICE USE			
Approved by (signature) TE	D FOR RECORD		Jame	Tit	le	
Conditions of approval Cap SGI certify that the applicant holds lega which would entitle the applican AG	attached Approval of this notice for equitable title to those rights anduct special des thereon.	does not warrant or	Printed/Typed) Office	TH.	Date	

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, first tious or fraudulent statements or representations as to any matter within its jurisdiction.

(Continued on next page)PETFOLEUM ENGINEER