

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
May 27, 2004

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-025-01270
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. E-1814
7. Lease Name or Unit Agreement Name New Mexico A
8. Well Number 3
9. OGRID Number 17213
10. Pool name or Wildcat Wildcat

Pit or Below-grade Tank Application ☐ or Closure ☐ **will utilize steel pits**

Pit type _____ Depth to Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water _____

Pit Liner Thickness: _____ mil Below-Grade Tank: Volume _____ bbls; Construction Material _____

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:
PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
OTHER: ☐

SUBSEQUENT REPORT OF:
REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☒
CASING/CEMENT JOB ☐
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

This well was plugged back by Basic to 4580' on 4/26/04. Penroc rigged up to perforate and test the Penrose & Grayburg. Was unable to get down 8 5/8" casing below 1827'. all attempts failed due to parted casing. Met w/ Mr. Chris Williams and received verbal approval to P&A. TTH w/ tbg to 1827'. Circ. hole w/ 9.3" galled brine. Spotted 35 sx. cement plug. Tag after WOC. Pull up to 400'. Spotted 35 sx. cement plug. Tag @ Pull up to 100' - 15 sx. cement plug to surface. Installed DH marker. Cut anchors. Clean up location. Used steel pit for fluid so NO SURFACE PIT.

Approved as to plugging of the Well Bore.
Liability under bond is retained until
surface restoration is completed.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOC guidelines ☒, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE M. Y. Merchant TITLE PRESIDENT DATE 8.17.04
Type or print name M. Y. Merchant E-mail address: mymerche@hotmail.com Telephone No. (505) 492-1236
For State Use Only
APPROVED BY: Gary W. Wink OC FIELD REPRESENTATIVE II / STAFF MANAGER
Conditions of Approval (if any): _____ TITLE _____ DATE AUG 30 2004