STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

> This form is not to be used for reporting packer leakage tests in Southeast New Mexico

600703

362

OIL CONSERVATION DIVISION

30-045-25389

API#

Well

Page 1 Revised 10/01/78

NORTHWEST NEW MEXICO PACKER-LEAKAGE TE

BURLINGTON RESOURCES OIL & GAS CO. **BOLACK TOMMY** Operator Lease 1M Location of Well: 01 030N 012W SAN JUAN Unit Sect Twp. Rge. County NAME OF RESERVOIR OR POOL TYPE OF PROD. METHOD OF PROD. PROD. MEDIUM (Oil or Gas) (Flow or Art. Lift) (Tbg. or Csg.) Upper **MESAVERDE** Gas Tubing Flow Completion Lower DAKOTA Gas Flow Tubing Completion PRE-FLOW SHUT-IN PRESSURE DATA Upper Hour, date shut-in Length of time shut-in SI press. psig Stabilized? (Yes or No) Completion 7/25/2004 120 Hours 441 Lower Completion 7/25/2004 72 Hours 138 FLOW TEST NO. 1 Commenced at (hour,date)* 7/28/2004 Zone producing (Upper or Lower) LOWER TIME LAPSED TIME **PRESSURE** PROD. ZONE SINCE* (hour,date) Upper Completion Lower Completion TEMP REMARKS 7/29/2004 96 Hours 167 138 Turned on DK 7/30/2004 120 Hours 179 138 Production rate during test Oil: BOPD based on Bbls. in Hours. Gas: MCFPD; Tested thru (Orifice or Meter): MID-TEST SHUT-IN PRESSURE DATA Upper Hour, date shut-in Length of time shut-in SI press. psig Stabilized? (Yes or No) Completion Lower Hour, date shut-in Length of time shut-in SI press. psig Stabilized? (Yes or No) Completion

(Continue on reverse side)

FLOW TEST NO. 2

Commenced at (hour, date)**			Zone producing (Upper or Lower):		
TIME (hour, date) / LAPSED TIME SINCE **	PRESSURE		PROD. ZONE	DEMARKS	
	Upper Completion	Lower Completion	on TEMP.	REMARKS	
					1
Night.	W. W.		1	·	
1.	.,,	,			
	25 is the				•
11.5 /	r* vc		1 1	i i i i i i i i i i i i i i i i i i i	. i .
ring test			, ,	, .	
ВО	PD based on	Bbls. in _	Hours	Grav	GOR
	MCFPI	D: Tested thru (Orif	fice or Meter):	· · · · · · · · · · · · · · · · · · ·	14.74
·		, e - 10 g.	4		
		and complete to th			
VUG 23 200	4	· . · · · · · · · · · · · · · · · · · ·	y	3.4	1,100 1,00
l Conservation Divis			$\mathcal{O}I$	Die	
17/	_			Associate	· , , &
				* *** A A *******	
i	t the information here UG 23 200	ring test BOPD based on MCFPI t the information herein contained is true	BOPD based onBbls. in	BOPD based onBbls. inHours MCFPD: Tested thru (Orifice or Meter): the information herein contained is true and complete to the best of my knowled 19Operator Burling li Conservation Division By	ring test BOPD based onBbis. inHoursGrav

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within
 seven days after actual completion of the well, and annually thereafter as prescribed by the
 order authorizing the multiple completion. Such tests shall also be commenced on all
 multiple completions within seven days following recompletion and/or chemical or fracture
 treatment, and whenever remedial work has been done on a well during which the packer or
 the tubing have been disturbed. Tests shall also be taken at any time that communication is
 suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at bourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).