Submit 3 Copies To Appropriate Distric	
District I	Energy, Minerals and Natural Resources May 27
1625 N. French Dr., Hobbs, NM 88240 District II	1 30-025-36689
1301 W. Grand Ave., Artesia, NM 8821	0 OIL CONSERVATION DIVISION 5. Indicate Type of Lease
District III 1000 Rio Brazos Rd., Aztec, NM 87410	1220 South St. Francis Dr. STATE FEE KXX
District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505	Santa Fe, NM 87505 6. State Oil & Gas Lease No.
SUNDRY NO	OTICES AND REPORTS ON WELLS POSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A 7. Lease Name or Unit Agreement Na
	PLICATION FOR PERMIT* (FORM C-101) FOR SUCH White Owl
1. Type of Well: Oil Well	X Gas Well Other 8. Well Number 1
2. Name of Operator	9. OGRID Number
3. Address of Operator Box	Inc         3659           10549         10. Pool name or Wildcat
4. Well Location	hd, TX 79702 House, Abo
Unit Letter D	: 582 feet from the North line and 330 feet from the West
Section 2	Township 28 E Range 38 S NMPM Lea County MM
and the second	11. Elevation (Show whether DR, RKB, RT, GR, etc.)
	3573 GR
Pit or Below-grade Tank Application	
Pit typeDepth to Grou	ndwaterDistance from nearest fresh water wellDistance from nearest surface water
Pit Liner Thickness:	mil Below-Grade Tank: Volume bbls; Construction Material
12. Chec	k Appropriate Box to Indicate Nature of Notice, Report or Other Data
PERFORM REMEDIAL WORK TEMPORARILY ABANDON	INTENTION TO:       SUBSEQUENT REPORT OF:         PLUG AND ABANDON       REMEDIAL WORK       ALTERING CASIN         CHANGE PLANS       COMMENCE DRILLING OPNS.       P AND A         MULTIPLE COMPL       CASING/CEMENT JOB       XX
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING	PLUG AND ABANDON       REMEDIAL WORK       ALTERING CASIN         CHANGE PLANS       COMMENCE DRILLING OPNS.       P AND A         MULTIPLE COMPL       CASING/CEMENT JOB       XX
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 13. Describe proposed or co	PLUG AND ABANDON       REMEDIAL WORK       ALTERING CASIN         CHANGE PLANS       COMMENCE DRILLING OPNS.       P AND A
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 13. Describe proposed or co of starting any proposed or recompletion.	PLUG AND ABANDON       REMEDIAL WORK       ALTERING CASIN         CHANGE PLANS       COMMENCE DRILLING OPNS       P AND A         MULTIPLE COMPL       CASING/CEMENT JOB       XX         OTHER:       OTHER:       OTHER:         ompleted operations. (Clearly state all pertinent details, and give pertinent dates, including estimated work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completions:
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 13. Describe proposed or co of starting any proposed or recompletion. Drilled 17-1/2 cemented w/ 20	PLUG AND ABANDON       REMEDIAL WORK       ALTERING CASIN         CHANGE PLANS       COMMENCE DRILLING OPNS.       PAND A         MULTIPLE COMPL       CASING/CEMENT JOB       XX         OTHER:       OTHER:       OTHER:         owork). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed com         2" hole to 127'. ran and Set 127' 13-3/8" J-55 csg at 00 sx Class "C" w/ 2% Cacl. Circulated cement to
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 13. Describe proposed or co of starting any proposed or recompletion. Drilled 17-1/2 cemented w/ 20 surface. Plug	PLUG AND ABANDON       REMEDIAL WORK       ALTERING CASIN         CHANGE PLANS       COMMENCE DRILLING OPNS.       PAND A         MULTIPLE COMPL       CASING/CEMENT JOB       XX         OTHER:       OTHER:         ompleted operations. (Clearly state all pertinent details, and give pertinent dates, including estimated work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completed operations: (Clearly state all pertinent details, and give pertinent dates, including estimated work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completed operations: (Clearly state all pertinent details, and set 127' 13-3/8" J-55 csg at 0.0 sx Class "C" w/ 2% Cacl. Circulated cement to 100 sx Class "C" w/ 2% Cacl. Circulated cement to 100 syn 6/18/04. Drilled 12-1/4" hole to 1636'. Ran
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 13. Describe proposed or co of starting any proposed or recompletion. Drilled 17-1/2 cemented w/ 20 surface. Plug and set 1636'	PLUG AND ABANDON       REMEDIAL WORK       ALTERING CASIN         CHANGE PLANS       COMMENCE DRILLING OPNS.       PAND A         MULTIPLE COMPL       CASING/CEMENT JOB       XX         OTHER:       OTHER:         ompleted operations. (Clearly state all pertinent details, and give pertinent dates, including estimal d work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed com         2" hole to 127'. ran and Set 127' 13-3/8" J-55 csg at 00 sx Class "C" w/ 2% Cacl. Circulated cement to Down 6/18/04. Drilled 12-1/4" hole to 1636'. Ran 8-5/8" 24# csg. Cemented to Surface w/ 400 sx 50/50
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 13. Describe proposed or co of starting any proposed or recompletion. Drilled 17-1/2 cemented w/ 20 surface. Plug and set 1636' POZ "C" w/ 2%	PLUG AND ABANDON       REMEDIAL WORK       ALTERING CASIN         CHANGE PLANS       COMMENCE DRILLING OPNS.       PAND A         MULTIPLE COMPL       CASING/CEMENT JOB       XX         OTHER:       OTHER:         ompleted operations. (Clearly state all pertinent details, and give pertinent dates, including estimated work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed com         2" hole to 127'. ran and Set 127' 13-3/8" J-55 csg at 00 sx Class "C" w/ 2% Cacl. Circulated cement to         Down 6/18/04. Drilled 12-1/4" hole to 1636'. Ran         8-5/8" 24# csg. Cemented to Surface w/ 400 sx 50/50         Cacl and 325 Sx Class "C" w/ 2% Cacl. Plug Down 6/2
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 13. Describe proposed or co of starting any proposed or recompletion. Drilled 17-1/2 cemented w/ 20 surface. Plug and set 1636' POZ "C" w/ 2% Drilled 7-7/8"	PLUG AND ABANDON       REMEDIAL WORK       ALTERING CASING         CHANGE PLANS       COMMENCE DRILLING OPNS.       . P AND A         MULTIPLE COMPL       CASING/CEMENT JOB       XX         OTHER:       OTHER:         ompleted operations. (Clearly state all pertinent details, and give pertinent dates, including estimated work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed com         2" hole to 127'. ran and Set 127' 13-3/8" J-55 csg at 00 sx Class "C" w/ 2% Cacl. Circulated cement to         Down 6/18/04. Drilled 12-1/4" hole to 1636'. Ran         8-5/8" 24# csg. Cemented to Surface w/ 400 sx 50/50         Cacl and 325 Sx Class "C" w/ 2% Cacl. Plug Down 6/2         " hole to 7741'. Ran 7768.65' 5-1/2" 17# N80 casing
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 13. Describe proposed or co of starting any proposed or recompletion. Drilled 17-1/2 cemented w/ 20 surface. Plug and set 1636' POZ "C" w/ 2% Drilled 7-7/8' cemented to su	PLUG AND ABANDON       REMEDIAL WORK       ALTERING CASIN         CHANGE PLANS       COMMENCE DRILLING OPNS.       PAND A         MULTIPLE COMPL       CASING/CEMENT JOB       XX         OTHER:       OTHER:       XX         ompleted operations. (Clearly state all pertinent details, and give pertinent dates, including estimated work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completed completed completed completions: Attach wellbore diagram of proposed completed complete
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 13. Describe proposed or co of starting any proposed or recompletion. Drilled 17-1/2 cemented w/ 20 surface. Plug and set 1636' POZ "C" w/ 2% Drilled 7-7/8' cemented to su 6% Gel, tailed	PLUG AND ABANDON       REMEDIAL WORK       ALTERING CASIN         CHANGE PLANS       COMMENCE DRILLING OPNS.       .PAND A         MULTIPLE COMPL       CASING/CEMENT JOB       XX         OTHER:       OTHER:         ompleted operations. (Clearly state all pertinent details, and give pertinent dates, including estimated work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completed completed completed completed l2-1/4"       J-55 csg at a state completed completed completed completed completed completed l2-1/4"         2"       hole to 127'. ran and Set 127' 13-3/8"       J-55 csg at a state completed complet
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 13. Describe proposed or co of starting any proposed or recompletion. Drilled 17-1/2 cemented w/ 20 surface. Plug and set 1636' POZ "C" w/ 2% Drilled 7-7/8' cemented to su	PLUG AND ABANDON       REMEDIAL WORK       ALTERING CASIN         CHANGE PLANS       COMMENCE DRILLING OPNS.       .PAND A         MULTIPLE COMPL       CASING/CEMENT JOB       XX         OTHER:       OTHER:         ompleted operations. (Clearly state all pertinent details, and give pertinent dates, including estimated work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completed comp
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 13. Describe proposed or co of starting any proposed or recompletion. Drilled 17-1/2 cemented w/ 20 surface. Plug and set 1636' POZ "C" w/ 2% Drilled 7-7/8' cemented to su 6% Gel, tailed	PLUG AND ABANDON       REMEDIAL WORK       ALTERING CASIN         CHANGE PLANS       COMMENCE DRILLING OPNS.       .PAND A         MULTIPLE COMPL       CASING/CEMENT JOB       XX         OTHER:       OTHER:         ompleted operations. (Clearly state all pertinent details, and give pertinent dates, including estimated work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completed completed completed completed l2-1/4"       J-55 csg at a state completed completed completed completed completed completed l2-1/4"         2"       hole to 127'. ran and Set 127' 13-3/8"       J-55 csg at a state completed complet
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 13. Describe proposed or co of starting any proposed or recompletion. Drilled 17-1/2 cemented w/ 20 surface. Plug and set 1636' POZ "C" w/ 2% Drilled 7-7/8' cemented to su 6% Gel, tailed	□       PLUG AND ABANDON       □         □       CHANGE PLANS       □         □       MULTIPLE COMPL       □         □       MULTIPLE COMPL       □         □       MULTIPLE COMPL       □         □       MULTIPLE COMPL       □         □       OTHER:         □       OTHER:         □       OTHER:         □       OTHER:         □       0xxx113.         □       OTHER:         □       0xx113.         □       0xx114.
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 13. Describe proposed or co of starting any proposed or recompletion. Drilled 17-1/2 cemented w/ 20 surface. Plug and set 1636' POZ "C" w/ 2% Drilled 7-7/8' cemented to su 6% Gel, tailed	□       PLUG AND ABANDON       □         □       CHANGE PLANS       □         □       MULTIPLE COMPL       □         □       MULTIPLE COMPL       □         □       MULTIPLE COMPL       □         □       MULTIPLE COMPL       □         □       OTHER:         □       OTHER:         □       OTHER:         □       OTHER:         □       0xxx113.         □       OTHER:         □       0xx113.         □       0xx114.
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 13. Describe proposed or co of starting any proposed or recompletion. Drilled 17-1/2 cemented w/ 20 surface. Plug and set 1636' POZ "C" w/ 2% Drilled 7-7/8' cemented to su 6% Gel, tailed	□       PLUG AND ABANDON       □         □       CHANGE PLANS       □         □       MULTIPLE COMPL       □         □       MULTIPLE COMPL       □         □       MULTIPLE COMPL       □         □       MULTIPLE COMPL       □         □       OTHER:         □       OTHER:         □       OTHER:         □       OTHER:         □       0xxx113.         □       OTHER:         □       0xx113.         □       0xx114.
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 13. Describe proposed or co of starting any proposed or recompletion. Drilled 17-1/2 cemented 17-1/2 cemented w/ 20 surface. Plug and set 1636' POZ "C" w/ 2% Drilled 7-7/8' cemented to su 6% Gel, tailed sodium metasi.	PLUG AND ABANDON       REMEDIAL WORK       ALTERING CASIN         CHANGE PLANS       COMMENCE DRILLING OPNS.       PAND A         MULTIPLE COMPL       CASING/CEMENT JOB       XX         OTHER:       OTHER:       OTHER:         ompleted operations. (Clearly state all pertinent details, and give pertinent dates, including estimate dwork). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed com         2" hole to 127'. ran and Set 127' 13-3/8" J-55 csg at 00 sx Class "C" w/ 2% Cacl. Circulated cement to         Down 6/18/04. Drilled 12-1/4" hole to 1636'. Ran         8-5/8" 24# csg. Cemented to Surface w/ 400 sx 50/50         Cacl and 325 Sx Class "C" w/ 2% Cacl. Plug Down 6/2         " hole to 7741'. Ran 7768.65' 5-1/2" 17# N80 casing         urface w/ 1220 sx 35/65 POZ "H" /w .2% BWOC FL-52         A in W/ 490 SX Class "H" w/ 1% BWOC FL25 & .1% BWOC         I in W/ 490 SX Class "H" w/ 1% BWOC FL25 & .1% BWOC
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 13. Describe proposed or co of starting any proposed or recompletion. Drilled 17-1/2 cemented 17-1/2 cemented w/ 20 surface. Plug and set 1636' POZ "C" w/ 2% Drilled 7-7/8' cemented to su 6% Gel, tailed sodium metasi.	□       PLUG AND ABANDON       □         □       CHANGE PLANS       □         □       MULTIPLE COMPL       □         □       MULTIPLE COMPL       □         □       MULTIPLE COMPL       □         □       MULTIPLE COMPL       □         □       OTHER:         □       OTHER:         □       OTHER:         □       OTHER:         □       0xxx113.         □       OTHER:         □       0xx113.         □       0xx114.
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 13. Describe proposed of co of starting any proposed or recompletion. Drilled 17-1/2 cemented w/ 20 surface. Plug and set 1636' POZ "C" w/ 2% Drilled 7-7/8' cemented to su 6% Gel, tailed sodium metasi.	PLUG AND ABANDON       REMEDIAL WORK       ALTERING CASIN         CHANGE PLANS       COMMENCE DRILLING OPNS       . P AND A         MULTIPLE COMPL       CASING/CEMENT JOB       XX         OTHER:       OTHER:       COMMENCE DRILLING OPNS       . P AND A         owork). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed com       OTHER:         2" hole to 127'. ran and Set 127' 13-3/8" J-55 csg at 0.0 sx Class "C" w/ 2% Cacl. Circulated cement to         Down 6/18/04. Drilled 12-1/4" hole to 1636'. Ran         8-5/8" 24# csg. Cemented to Surface w/ 400 sx 50/50         Cacl and 325 Sx Class "C" w/ 2% Cacl. Plug Down 6/2         " hole to 7741'. Ran 7768.65' 5-1/2" 17# N80 casing urface w/ 1220 sx 35/65 POZ "H" /w .2% BWOC FL-52         a in W/ 490 SX Class "H" w/ 1% BWOC FL25 & .1% BWOC         Hon above is true and complete to the best of my knowledge and belief. I marther cartify that any pit or or doed according to NMOCD guidelines ], a general permit or an (attached) alternative OCD -approved permits of the coded according to NMOCD guidelines ], a general permit or an (attached) alternative OCD -approved permits of the coded according to NMOCD guidelines [], a general permit or an (attached) alternative OCD -approved permits of the coded according to NMOCD guidelines [], a general permit or an (attached) alternative OCD -approved permits of the code according to NMOCD guidelines [], a general permit [] or an (attached) alternative OCD -approved permits of the code according to NMOCD guidelines [], a general permit [] or an (attached) alternative oCD -approved permits of the code accor
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 13. Describe proposed of co of starting any proposed or recompletion. Drilled 17-1/2 cemented w/ 20 surface. Plug and set 1636' POZ "C" w/ 2% Drilled 7-7/8' cemented to su 6% Gel, tailed sodium metasi.	□       PLUG AND ABANDON       □       REMEDIAL WORK       □       ALTERING CASIN         □       MULTIPLE COMPL       □       CASING/CEMENT JOB       DXX         □       OTHER:       □       OTHER:         □       more than the state of the state all pertinent details, and give pertinent dates, including estimated work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed complete to 127'. ran and Set 127' 13-3/8" J-55 csg at 00 sx Class "C" w/ 2% Cacl. Circulated cement to         2" hole to 127'. ran and Set 127' 13-3/8" J-55 csg at 00 sx Class "C" w/ 2% Cacl. Circulated cement to         Down 6/18/04. Drilled 12-1/4" hole to 1636'. Ran         8-5/8" 24# csg. Cemented to Surface w/ 400 sx 50/50         Cacl and 325 Sx Class "C" w/ 2% Cacl. Plug Down 6/2         " hole to 7741'. Ran 7768.65' 5-1/2" 17# N80 casing         urface w/ 1220 sx 35/65 POZ "H" /w .2%         BWOC FL-52         4 in W/ 490 SX Class "H" w/ 1% BWOC FL25 \$\$ .1% BWOC         Icate.
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 13. Describe proposed or co of starting any proposed or recompletion. Drilled 17-1/2 cemented w/ 20 surface. Plug and set 1636' POZ "C" w/ 2% Drilled 7-7/8' cemented to su 6% Gel, tailed sodium metasi.	□       PLUG AND ABANDON       □       REMEDIAL WORK       □       ALTERING CASIN         □       MULTIPLE COMPL       □       CASING/CEMENT JOB       DXX         □       OTHER:       □       OTHER:         □       more than the state of the state all pertinent details, and give pertinent dates, including estimated work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed complete to 127'. ran and Set 127' 13-3/8" J-55 csg at 00 sx Class "C" w/ 2% Cacl. Circulated cement to         2" hole to 127'. ran and Set 127' 13-3/8" J-55 csg at 00 sx Class "C" w/ 2% Cacl. Circulated cement to         Down 6/18/04. Drilled 12-1/4" hole to 1636'. Ran         8-5/8" 24# csg. Cemented to Surface w/ 400 sx 50/50         Cacl and 325 Sx Class "C" w/ 2% Cacl. Plug Down 6/2         " hole to 7741'. Ran 7768.65' 5-1/2" 17# N80 casing         urface w/ 1220 sx 35/65 POZ "H" /w .2%         BWOC FL-52         4 in W/ 490 SX Class "H" w/ 1% BWOC FL25 \$\$ .1% BWOC         Icate.
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 13. Describe proposed or co of starting any proposed or recompletion. Drilled 17-1/2 cemented w/ 20 surface. Plug and set 1636' POZ "C" w/ 2% Drilled 7-7/8' cemented to su 6% Gel, tailed sodium metasi.	PLUG AND ABANDON       REMEDIAL WORK       ALTERING CASIN         CHANGE PLANS       COMMENCE DRILLING OPNS       PAND A         MULTIPLE COMPL       CASING/CEMENT JOB       XX         OTHER:       OTHER:         ompleted operations. (Clearly state all pertinent details, and give pertinent dates, including estimated work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed com         2" hole to 127'. ran and Set 127' 13-3/8" J-55 csg at 00 sx Class "C" w/ 2% Cacl. Circulated cement to         Down 6/18/04. Drilled 12-1/4" hole to 1636'. Ran         8-5/8" 24# csg. Cemented to Surface w/ 400 sx 50/50         Cacl and 325 Sx Class "C" w/ 2% Cacl. Plug Down 6/2         " hole to 7741'. Ran 7768.65' 5-1/2" 17# N80 casing urface w/ 1220 sx 35/65 POZ "H" /w .2% BWOC FL-52         A in W/ 490 SX Class "H" w/ 1% BWOC FL25 & .1% BWOC         Icate.         A in W/ 490 SX Class "H" w/ 1% BWOC FL25 & .1% BWOC         Icate.         A 55709         H Scott Tav INFTLE       Agent         DATE: 09-0.         E-mail address:         OC DISTRICT SUPERVISOR/GENERAL MANAGErephone No.
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 13. Describe proposed or co of starting any proposed or recompletion. Drilled 17-1/2 cemented w/ 20 surface. Plug and set 1636' POZ "C" w/ 2% Drilled 7-7/8' cemented to su 6% Gel, tailed sodium metasi.	□       PLUG AND ABANDON       □       REMEDIAL WORK       □       ALTERING CASIN         □       MULTIPLE COMPL       □       CASING/CEMENT JOB       DXX         □       OTHER:       □       OTHER:         □       more than the state of the state all pertinent details, and give pertinent dates, including estimated work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed complete to 127'. ran and Set 127' 13-3/8" J-55 csg at 00 sx Class "C" w/ 2% Cacl. Circulated cement to         2" hole to 127'. ran and Set 127' 13-3/8" J-55 csg at 00 sx Class "C" w/ 2% Cacl. Circulated cement to         Down 6/18/04. Drilled 12-1/4" hole to 1636'. Ran         8-5/8" 24# csg. Cemented to Surface w/ 400 sx 50/50         Cacl and 325 Sx Class "C" w/ 2% Cacl. Plug Down 6/2         " hole to 7741'. Ran 7768.65' 5-1/2" 17# N80 casing         urface w/ 1220 sx 35/65 POZ "H" /w .2%         BWOC FL-52         4 in W/ 490 SX Class "H" w/ 1% BWOC FL25 \$\$ .1% BWOC         Icate.