

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
March 4, 2004

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-025-25928
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Anderson 'A'
8. Well Number 9
9. OGRID Number 000495
10. Pool name or Wildcat Eunice Monument G/SA

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
Amerada Hess Corporation

3. Address of Operator
P.O. Box 840
Seminole, TX 79360

4. Well Location

Unit Letter F : 2310 feet from the North line and 2310 feet from the West line

Section 17 Township 20S Range 37E NMPM County Lea

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3541' GL

Pit or Below-grade Tank Application (For pit or below-grade tank closures, a form C-144 must be attached)

Pit Location: UL Sect Twp Rng Pit type Depth to Groundwater Distance from nearest fresh water well
Distance from nearest surface water Below-grade Tank Location UL Sect Twp Rng ;
 feet from the line and feet from the line

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Plan to plug and abandon well, please see attached procedure.

THE COMMISSION MUST BE NOTIFIED 24 HOURS PRIOR TO THE BEGINNING OF PLUGGING OPERATIONS FOR THE C-103 TO BE APPROVED.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE Carol J. Moore TITLE Senior Advisor/Regulatory DATE 9/2/2004

Type or print name Carol J. Moore E-mail address: cmoore@hess.com Telephone No. (432)758-6738

(This space for State use)

SEP 03 2004

APPROVED BY Chris Williams ORIGINAL SIGNED BY CHRIS WILLIAMS DATE

Conditions of approval, if any:

OC DISTRICT SUPERVISOR/GENERAL MANAGER

OC DISTRICT SUPERVISOR/GENERAL MANAGER

COMPLETION SCHEMATIC		LEASE NAME	Anderson (A)	API #	30-025-25928	WELL NO.	9
		TYPE COMPLETION:					
		SINGLE X DUAL					
		LOCATION: 17-20S-37E UL F					
KB 3,553'		TD 3,832'	PBD 3,827'	KB 3,553'	DF		
8-5/8" SURF		COD	DOD	GL 3,541'			
		NO. PROD. WELLS ON LEASE		FLOWING	PUMPING	GAS LIFT	
		1			X		
		ZONE TO BE WORKED ON:			CURRENT COMPLETION ZONE:		
					Grayburg San Andres		
2-3/8" TUBING		CSG. PERFS:			OPEN HOLE :		
		3517-3720			No		
		CURRENT TEST (SHOW DATE)					
		GAS			OIL		
		GAS			OIL		
		CASING BREAKDOWN					
SN 3393		SURF.	SIZE: 8-5/8"	DEPTH	328'		
TOC 3413		INTER.	SIZE:	DEPTH			
CIBP 3450		PROD.	SIZE: 5 1/2"	DEPTH	3,827'		
		WORK PLAN					
		1 Notify OCD 24 hrs. prior to rigging up on well. 2 Test Casing to 500# for 30 min. 3 MIRU PU and NU BOP 4 Tag Cmt. @ 3413'. 5 Circ. Hole w/ plugging mud. (76 bbls.) 6 Pull Tbg. And spot cmt. Plug fr. 1250' to 1000'. (25 sx) Across salt top 7 Wait 4 hrs. and tag TOC 8 Pull Tbg. And spot cmt. Plug fr. 453' to surface. (45 sx) 9 Install Marker, cut off anchors, and clean location.					
5 1/2" PROD							
3,832' TD							
3,827' PBD							
1050' top of salt							
G/SA Perfs							
3517-3720							
(8)							
(5)							
(6)							
(4)							

PREPARED BY: Bill Petree

UPDATED: 08-30/04