	New Mexico O				
Form 3160-5		[625 N. Frenc		EVEL ADDALTED	
April 2004)	UNITED STATE DEPARTMENT OF THE	HopponM	88240	FORM APPROVED OM B No. 1004-0137 Events March 21 2007	
	BUREAU OF LAND MAN	IAGEMENT	en en j	Expires: March 31, 2007 5. Lease Serial No.	
SUNE	ORY NOTICES AND REI	PORTS ON W	ELLS	NMNM106916	
Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.			6. If Indian, Allottee or Tribe Name		
SUBMIT IN TRIPLICATE- Other instructions on reverse side.				7. If Unit or CA/Agreement, Name and/or No.	
1. Type of Well X Oil Well	Gas Well Other	 · · ·		8. Well Name and No.	
2. Name of Operator Echo Production, Inc.				East Livingston '31' Federal #3	
	Graham, TX 76450	3b. Phone No. (inch 940-549-32		30 -07.5-34054 10. Field and Pool, or Exploratory Area	
4. Location of Well <i>(Footage,</i> 1810 'FSL &	Sec., T., R., M., or Survey Description)			Livingston Ridge; Delaware, SE	
Sec 31 T22S				11. County or Parish, State Lea County, NM	
12. CHEC	K APPROPRIATE BOX(ES) TO	DINDICATE NAT	JRE OF NOTICE,	REPORT, OR OTHER DATA	
TYPE OF SUBMISSION	۲ 	· T	YPE OF ACTION		
Notice of Intent	Acidize	Deepen	Production (S		
	Alter Casing Casing Repair	Fracture Treat		Well Integrity 131415167	
Subsequent Report	Change Plans	Plug and Abandor		bandon casing	
Final Abandonment Not	ice Convert to Injection	Plug Back	Water Disposa		
If the proposal is to deep Attach the Bond under w following completion of testing has been complet determined that the site is	en directionally or recomplete horizontal hich the work will be performed or prov the involved operations. If the operation ed. Final Abandonment Notices shall be a ready for final inspection.)	lly, give subsurface local ride the Bond No. on fil a results in a multiple con filed only after all requi	tions and measured and t e with BLM/BIA. Require mpletion or recompletion	any proposed work and approximate duration thereof. VED rue vertical depths of all pertinent markers and sones. VED red subsequent reports shall be filed within 30 days Dbs in a new interval, a Form 31604 shall be filed on Ω CD nation, have been completed, and the operator has	
If the proposal is to deep Attach the Bond under w following completion of testing has been complet determined that the site is 8/30/04 9/01/04	en directionally or recomplete horizontal hich the work will be performed or prov the involved operations. If the operation ed. Final Abandonment Notices shall be s ready for final inspection.) Spud well at 9:00 p Drill to 802'. Ran	lly, give subsunface local ride the Bond No. on fil a results in a multiple con e filed only after all requi pm 13 3/8" 48	tions and measured and t e with BLM/BIA. Requ mpletion or recompletion irements, including recta # J-55 csg &	ne vertical depths of all pertinent markers and sonts. VED red subsequent reports shall be filed within 30 days bbs in a new interval, a Form 3160 4 shall be filed on a CD nation, have been completed, and the operator has	
If the proposal is to deep Attach the Bond under w following completion of testing has been complet determined that the site is 8/30/04 9/01/04 9/08/04	en directionally or recomplete horizontal hich the work will be performed or prov the involved operations. If the operation ed. Final Abandonment Notices shall be s ready for final inspection.) Spud well at 9:00 p Drill to 802'. Ran Poz 'C' w/6% gel ar Drill to 4595'. Ran	lly, give subsunface local ride the Bond No. on fill a results in a multiple con filed only after all requir pm 13 3/8" 48 nd 200 sx '(n 4595' 8 5/	tions and measured and t e with BLM/BIA. Requ mpletion or recompletion irements, including recta J – 55 csg & C' w/ 2% caC / 8" 32# J – 55	<pre>1. Circulate 80 sx. csg & cement w/ 1350 sx 65/3</pre>	
If the proposal is to deep Attach the Bond under w following completion of testing has been complet determined that the site is 8/30/04 9/01/04 9/08/04	en directionally or recomplete horizontal hich the work will be performed or prov the involved operations. If the operation ed. Final Abandonment Notices shall be s ready for final inspection.) Spud well at 9:00 p Drill to 802'. Ran Poz 'C' w/6% gel ar	lly, give subsunface local ride the Bond No. on fill a results in a multiple con filed only after all requir pm 13 3/8" 48 nd 200 sx '(n 4595' 8 5/	tions and measured and t e with BLM/BIA. Requ mpletion or recompletion irements, including recta J – 55 csg & C' w/ 2% caC / 8" 32# J – 55	<pre>1. Circulate 80 sx. csg & cement w/ 1350 sx 65/3 te 115 sx.</pre>	
If the proposal is to deep Attach the Bond under w following completion of testing has been complet determined that the site is 8/30/04 9/01/04 9/08/04	en directionally or recomplete horizontal hich the work will be performed or prov the involved operations. If the operation ed. Final Abandonment Notices shall be s ready for final inspection.) Spud well at 9:00 p Drill to 802'. Ran Poz 'C' w/6% gel ar Drill to 4595'. Ran Poz 'C' w/ 6% gel a	lly, give subsunface local ride the Bond No. on fill a results in a multiple con filed only after all requir pm 13 3/8" 48 nd 200 sx '(n 4595' 8 5/	tions and measured and t e with BLM/BIA. Requ mpletion or recompletion irements, including recta J – 55 csg & C' w/ 2% caC / 8" 32# J – 55	<pre>1. Circulate 80 sx. csg & cement w/ 1350 sx 65/3</pre>	
If the proposal is to deep Attach the Bond under w following completion of testing has been complet determined that the site is 8/30/04 9/01/04 9/08/04	en directionally or recomplete horizontal hich the work will be performed or prov the involved operations. If the operation ed. Final Abandonment Notices shall be s ready for final inspection.) Spud well at 9:00 p Drill to 802'. Ran Poz 'C' w/6% gel ar Drill to 4595'. Ran	lly, give subsunface local ride the Bond No. on fill a results in a multiple con filed only after all requir pm 13 3/8" 48 nd 200 sx '(n 4595' 8 5/	tions and measured and t e with BLM/BIA. Requ mpletion or recompletion irements, including recta J – 55 csg & C' w/ 2% caC / 8" 32# J – 55	1. Circulate 80 sx. csg & cement w/ 1350 sx 65/3 te 115 sx. ACCEPTED FOR RECORD	
If the proposal is to deep Attach the Bond under w following completion of testing has been complet determined that the site is 8/30/04 9/01/04 9/08/04	en directionally or recomplete horizontal hich the work will be performed or prov the involved operations. If the operation ed. Final Abandonment Notices shall be s ready for final inspection.) Spud well at 9:00 p Drill to 802'. Ran Poz 'C' w/6% gel ar Drill to 4595'. Ran Poz 'C' w/ 6% gel a	lly, give subsunface local ride the Bond No. on fill a results in a multiple con filed only after all requir pm 13 3/8" 48 nd 200 sx '(n 4595' 8 5/	tions and measured and t e with BLM/BIA. Requ mpletion or recompletion irements, including recta J – 55 csg & C' w/ 2% caC / 8" 32# J – 55	<pre>1. Circulate 80 sx. csg & cement w/ 1350 sx 65/3 te 115 sx.</pre>	
If the proposal is to deep Attach the Bond under w following completion of testing has been complet determined that the site is 8/30/04 9/01/04 9/08/04	en directionally or recomplete horizontal hich the work will be performed or prov the involved operations. If the operation ed. Final Abandonment Notices shall be s ready for final inspection.) Spud well at 9:00 p Drill to 802'. Ran Poz 'C' w/6% gel ar Drill to 4595'. Ran Poz 'C' w/ 6% gel a	lly, give subsunface local ride the Bond No. on fill a results in a multiple con filed only after all requir pm 13 3/8" 48 nd 200 sx '(n 4595' 8 5/	tions and measured and t e with BLM/BIA. Requ mpletion or recompletion irements, including recta # J-55 csg & C' w/ 2% caC /8" 32# J-55	1. Circulate 80 sx. csg & cement w/ 1350 sx 65/31 te 115 sx. ACCEPTED FOR RECORD SEP 14 2004	
If the proposal is to deep Attach the Bond under w following completion of testing has been complet determined that the site is 8/30/04 9/01/04 9/08/04	en directionally or recomplete horizontal hich the work will be performed or prov the involved operations. If the operation ed. Final Abandonment Notices shall be a ready for final inspection.) Spud well at 9:00 µ Drill to 802'. Ran Poz 'C' w/6% gel ar Drill to 4595'. Ran Poz 'C' w/ 6% gel a	lly, give subsunface local ride the Bond No. on fill a results in a multiple con filed only after all requir pm 13 3/8" 48 nd 200 sx '(n 4595' 8 5/	tions and measured and t e with BLM/BIA. Requ mpletion or recompletion irements, including recta # J-55 csg & C' w/ 2% caC /8" 32# J-55	1. Circulate 80 sx. csg & cement w/ 1350 sx 65/3 te 115 sx. ACCEPTED FOR RECORD	
If the proposal is to deep Attach the Bond under w following completion of testing has been complet determined that the site is 8/30/04 9/01/04 9/08/04 14. Ihereby certify that th Name (Printed/Type	en directionally or recomplete horizontal hich the work will be performed or prov the involved operations. If the operation ed. Final Abandonment Notices shall be a ready for final inspection.) Spud well at 9:00 µ Drill to 802'. Ran Poz 'C' w/6% gel ar Drill to 4595'. Ran Poz 'C' w/ 6% gel a	lly, give subsunface local ride the Bond No. on fill a results in a multiple con filed only after all requir pm 13 3/8" 48 nd 200 sx '(n 4595' 8 5/	tions and measured and t e with BLM/BIA. Requ mpletion or recompletion irements, including recta # J-55 csg & C' w/ 2% CaC /8" 32# J-55 'C'. Circula	1. Circulate 80 sx. csg & cement w/ 1350 sx 65/3 te 115 sx. ACCEPTED FOR RECORD SEP 14 2004 CARY COURLEY PETROLEUM ENGINEER	
If the proposal is to deep Attach the Bond under w following completion of testing has been complet determined that the site is 8/30/04 9/01/04 9/08/04 9/08/04 14. Ihereby certify that th Name (Printed/Type Tom Golden	en directionally or recomplete horizontal hich the work will be performed or prov the involved operations. If the operation ed. Final Abandonment Notices shall be a ready for final inspection.) Spud well at 9:00 p Drill to 802'. Ran Poz 'C' w/6% gel ar Drill to 4595'. Ran Poz 'C' w/ 6% gel a Poz 'C' w/ 6% gel a	lly, give subsunface local ride the Bond No. on fill a results in a multiple con- e filed only after all requi- pm 13 3/8" 48 nd 200 sx '(n 4595' 8 5/ and 200 sx ' and 200 sx '	tions and measured and t e with BLM/BIA. Requ mpletion or recompletion irements, including recta # J-55 csg & C' w/ 2% CaC /8" 32# J-55 'C'. Circula Operations	1. Circulate 80 sx. csg & cement w/ 1350 sx 65/3 te 115 sx. ACCEPTED FOR RECORD SEP 14 2004 CARY COURLEY PETROLEUM ENGINEER	
If the proposal is to deep Attach the Bond under w following completion of testing has been complet determined that the site is 8/30/04 9/01/04 9/08/04 9/08/04 14. Ihereby certify that th Name (Printed/Type Tom Golden	en directionally or recomplete horizontal hich the work will be performed or prov the involved operations. If the operation ed. Final Abandonment Notices shall be a ready for final inspection.) Spud well at 9:00 µ Drill to 802'. Ran Poz 'C' w/6% gel ar Drill to 4595'. Ran Poz 'C' w/ 6% gel a Poz 'C' w/ 6% gel a	lly, give subsunface local ride the Bond No. on fill a results in a multiple con- e filed only after all requi- tion 13 3/8" 48 and 200 sx 'C and 200 sx 'C and 200 sx ' Title Date	tions and measured and t e with BLM/BIA. Requ mpletion or recompletion irements, including recta # J-55 csg & C' w/ 2% CaC /8" 32# J-55 'C'. Circula Operations 9/09/04	1. Circulate 80 sx. csg & cement w/ 1350 sx 65/3 te 115 sx. ACCEPTED FOR RECORD SEP 14 2004 CABY COURLEY PETROLEUM ENGINEER Manager	
If the proposal is to deep Attach the Bond under w following completion of testing has been complet determined that the site is 8/30/04 9/01/04 9/08/04 9/08/04 14. Ihereby certify that th Name (Printed/Type Tom Golden	en directionally or recomplete horizontal hich the work will be performed or prov the involved operations. If the operation ed. Final Abandonment Notices shall be a ready for final inspection.) Spud well at 9:00 p Drill to 802'. Ran Poz 'C' w/6% gel ar Drill to 4595'. Ran Poz 'C' w/ 6% gel a Poz 'C' w/ 6% gel a	lly, give subsunface local ride the Bond No. on fill a results in a multiple con- e filed only after all requi- tion 13 3/8" 48 and 200 sx 'C and 200 sx 'C and 200 sx ' Title Date	tions and measured and t e with BLM/BIA. Requ mpletion or recompletion irements, including recta # J-55 csg & C' w/ 2% CaC /8" 32# J-55 'C'. Circula Operations 9/09/04	1. Circulate 80 sx. csg & cement w/ 1350 sx 65/3 te 115 sx. ACCEPTED FOR RECORD SEP 14 2004 CABY COURLEY PETROLEUM ENGINEER Manager	
If the proposal is to deep Attach the Bond under w following completion of testing has been complet determined that the site is 8/30/04 9/01/04 9/08/04 9/08/04 14. Ihereby certify that th Name (Printed/Type Tom Golden Signature	en directionally or recomplete horizontal hich the work will be performed or prov the involved operations. If the operation ed. Final Abandonment Notices shall be a ready for final inspection.) Spud well at 9:00 µ Drill to 802'. Ran Poz 'C' w/6% gel ar Drill to 4595'. Ran Poz 'C' w/ 6% gel a Poz 'C' w/ 6% gel a	lly, give subsunface local ride the Bond No. on fill a results in a multiple con- e filed only after all requi- tion 13 3/8" 48 and 200 sx 'C and 200 sx 'C and 200 sx ' Title Date	tions and measured and t e with BLM/BIA. Requ mpletion or recompletion irements, including recta # J-55 csg & C' w/ 2% CaC (8" 32# J-55 'C'. Circula Operations 9/09/04 STATE OFFICI	1. Circulate 80 sx. csg & cement w/ 1350 sx 65/3 te 115 sx. ACCEPTED FOR RECORD SEP 14 2004 CARY COURLEY PETROLEUM ENGINEER Manager	
If the proposal is to deep Attach the Bond under w following completion of testing has been complet determined that the site is 8/30/04 9/01/04 9/08/04 9/08/04 14. Ihereby certify that th Name (Printed/Type Tom Golden Signature	en directionally or recomplete horizontal hich the work will be performed or prov the involved operations. If the operation ed. Final Abandonment Notices shall be a ready for final inspection.) Spud well at 9:00 p Drill to 802'. Ran Poz 'C' w/6% gel ar Drill to 4595'. Rar Poz 'C' w/ 6% gel a e foregoing is true and correct d) THIS SPACE FOR	lly, give subsurface local ride the Bond No. on fill a results in a multiple con- e filed only after all requi- pm 13 3/8" 484 and 200 sx 'C and 200 sx 'C and 200 sx ' Title FEDERAL OR	tions and measured and t e with BLM/BIA. Requ mpletion or recompletion irements, including recta # J-55 csg & C' w/ 2% CaC /8" 32# J-55 'C'. Circula Operations 9/09/04	1. Circulate 80 sx. csg & cement w/ 1350 sx 65/3 te 115 sx. ACCEPTED FOR RECORD SEP 14 2004 CABY COURLEY PETROLEUM ENGINEER Manager	
If the proposal is to deep Attach the Bond under w following completion of testing has been complet determined that the site is 8/30/04 9/01/04 9/08/04 9/08/04 14. Ihereby certify that th Name (Printed/Type Tom Golden Signature Approved by Conditions of approval, if any certify that the applicant hold	en directionally or recomplete horizontal hich the work will be performed or prov the involved operations. If the operation ed. Final Abandonment Notices shall be a ready for final inspection.) Spud well at 9:00 p Drill to 802'. Ran Poz 'C' w/6% gel ar Drill to 4595'. Rar Poz 'C' w/ 6% gel a Poz 'C' w/ 6% gel a Drill to 4595'. Rar Poz 'C' w/ 6% gel a Drill to SPACE FOR THIS SPACE FOR	lly, give subsurface local ride the Bond No. on fill a results in a multiple con- e filed only after all requi- pm 13 3/8" 484 and 200 sx 'C and 200 sx 'C and 200 sx ' Title FEDERAL OR	tions and measured and t e with BLM/BIA. Requ mpletion or recompletion irements, including recta # J-55 csg & C' w/ 2% CaC (8" 32# J-55 'C'. Circula Operations 9/09/04 STATE OFFICI	1. Circulate 80 sx. csg & cement w/ 1350 sx 65/3 te 115 sx. ACCEPTED FOR RECORD SEP 14 2004 CARY COURLEY PETROLEUM ENGINEER Manager	
If the proposal is to deep Attach the Bond under w following completion of testing has been complet determined that the site is 8/30/04 9/01/04 9/08/04 9/08/04 14. Ihereby certify that th Name (<i>Printed/Type</i> Tom Golden Signature Approved by Conditions of approval, if any certify that the applicant hold which would entitle the appli	en directionally or recomplete horizontal hich the work will be performed or prov the involved operations. If the operation ed. Final Abandonment Notices shall be a ready for final inspection.) Spud well at 9:00 p Drill to 802'. Ran Poz 'C' w/6% gel ar Drill to 4595'. Rar Poz 'C' w/ 6% gel a Poz 'C' w/ 6% gel a Drill to 4595'. Rar Poz 'C' w/ 6% gel a Drill to 4595'. Rar	lly, give subsurface local ride the Bond No. on fill a results in a multiple con- e filed only after all requi- pm 13 3/8" 484 nd 200 sx 'C n 4595' 8 5/ and 200 sx 'C and 200 sx ' Title FEDERAL OR	tions and measured and t e with BLM/BIA. Requ mpletion or recompletion irements, including recta # J-55 csg & C' w/ 2% CaC /8" 32# J-55 'C'. Circula Operations 9/09/04 STATE OFFICI Title Office	1. Circulate 80 sx. csg & cement w/ 1350 sx 65/3 te 115 sx. ACCEPTED FOR RECORD SEP 14 2004 CARY COURLEY PETROLEUM ENGINEER Manager EUSE Date	
If the proposal is to deep Attach the Bond under w following completion of testing has been complet determined that the site is 8/30/04 9/01/04 9/08/04 9/08/04 14. Ihereby certify that th Name (<i>Printed/Type</i> Tom Golden Signature Approved by Conditions of approval, if any certify that the applicant hold which would entitle the applic	en directionally or recomplete horizontal hich the work will be performed or prov the involved operations. If the operation ed. Final Abandonment Notices shall be a ready for final inspection.) Spud well at 9:00 p Drill to 802'. Ran Poz 'C' w/6% gel ar Drill to 4595'. Rar Poz 'C' w/ 6% gel a Poz 'C' w/ 6% gel a Drill to 4595'. Rar Poz 'C' w/ 6% gel a Drill to 4595'. Rar	lly, give subsurface local ride the Bond No. on fill a results in a multiple con- e filed only after all requi- pm 13 3/8" 484 nd 200 sx 'C n 4595' 8 5/ and 200 sx 'C and 200 sx ' Title Date FEDERAL OR	tions and measured and t e with BLM/BIA. Requ mpletion or recompletion irements, including recta # J-55 csg & C' w/ 2% CaC /8" 32# J-55 'C'. Circula Operations 9/09/04 STATE OFFICI Title Office	1. Circulate 80 sx. csg & cement w/ 1350 sx 65/3 te 115 sx. ACCEPTED FOR RECORD SEP 14 2004 CARY COURLEY PETROLEUM ENGINEER Manager	