

**District I**  
1625 N. French Dr., Hobbs, NM 88240  
**District II**  
1301 W. Grand Avenue, Artesia, NM 88210  
**District III**  
1000 Rio Brazos Rd., Aztec, NM 87410  
**District IV**  
1220 S. St. Francis Dr., Santa Fe, NM 87505

Oil Conservation Division  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO. 30-025-36675

5. Indicate Type of Lease  
STATE ☐ FEE ☒

State Oil & Gas Lease No.

### WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> DRY <input type="checkbox"/> OTHER _____						7. Lease Name or Unit Agreement Name V Laughlin	
b. Type of Completion: NEW <input checked="" type="checkbox"/> WORK <input type="checkbox"/> DEEPEN <input type="checkbox"/> PLUG <input type="checkbox"/> DIFF. WELL OVER BACK RESVR. <input type="checkbox"/> OTHER						8. Well No. 5	
2. Name of Operator Amerada Hess Corporation						9. Pool name or Wildcat Monument Tubb, Southeast Monument Abo	
3. Address of Operator P.O. Box 840 Seminole, Texas 79360							
4. Well Location Unit Letter C : 330 Feet From The North Line and 1980 Feet From The West Line Section 9 Township 20S Range 37E NMPM County							
10. Date Spudded		11. Date T.D. Reached		12. Date Compl. (Ready to Prod.) 6/20/2004		13. Elevations (DF& RKB, RT GR, etc.) 3555' GL	
15. Total Depth 7263'		16. Plug Back T.D.		17. If Multiple Compl. How Many Zones?		18. Intervals Drilled By Rotary Tools Cable Tools	
19. Producing Interval(s), of this completion - Top, Bottom, Name 6466'-6551.3' Monument Tubb (47090), 7100'-7263' (open hole) Southeast Monument Abo (96764)						20. Was Directional Survey Made	
21. Type Electric and Other Logs Run GR/CCL						22. Was Well Cored No	
23. CASING RECORD (Report all strings set in well)							
CASING SIZE		WEIGHT LB./FT.		DEPTH SET		HOLE SIZE	
8 5/8"		24#		1239'		11"	
5 1/2"		17#		7100'		7 7/8"	
24. LINER RECORD							
SIZE		TOP		BOTTOM		SACKS CEMENT	
25. TUBING RECORD							
SIZE		DEPTH SET		PACKER SET			
2 7/8"		7160'					
26. Perforation record (interval, size, and number) Perf. w/4" csg. gun w/3 SPF in Monunent Tubb 6466'-6472.1', 6508'-6514.3', 6548'-6551.3' & Southeast Monument Abo 7100'-7263' open hole							
27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.							
DEPTH INTERVAL				AMOUNT AND KIND MATERIAL USED			
7100'-7263'				Acidized w/5000 gal. 15% HCL Acid			
6466'-6551.3'				Acidized w/4500 gal. 15% NEFE HCL w/Tubb add.			
				Frac'd w/78,000 gal Spectrafrac 35# XL Borate			
28. PRODUCTION							
Date First Production 6/20/2004		Production Method (Flowing, gas lift, pumping - Size and type pump) Pumping				Well Status (Prod. or Shut-in) Producing	
Date of Test 8/5/2004		Hours Tested 24		Choke Size 26/64		Prod'n For Test Period	
Flow Tubing Press. 35		Casing Pressure		Calculated 24-Hour Rate		Oil - Bbl. 119	
						Gas - MCF 313	
						Water - Bbl. 92	
						Oil Gravity - API - (Corr.) 39	
29. Disposition of Gas (Sold, used for fuel, vented, etc.) Sold						Test Witnessed By	
30. List Attachments							
C-102, C-103, C-104, C-105 Note: Refer to Administrative Order DHC-3299							
31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief							
Signature Carol J. Moore		Printed Name Carol J. Moore		Title Senior Advisor, Regulatory		Date 8/16/2004	

# INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

## INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy _____ 1200'	T. Canyon _____	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt _____ 1610'	T. Strawn _____	T. Kirtland-Fruitland _____	T. Penn. "C" _____
B. Salt _____ 2536'	T. Atoka _____	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates _____ 2550'	T. Miss _____	T. Cliff House _____	T. Leadville _____
T. 7 Rivers _____	T. Devonian _____	T. Menefee _____	T. Madison _____
T. Queen _____	T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg _____ 3500'	T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres _____ 4000'	T. Simpson _____	T. Gallup _____	T. Ignacio Otzte _____
T. Glorieta _____	T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Paddock _____	T. Ellenburger _____	T. Dakota _____	T. _____
T. Blinebry _____	T. Gr. Wash _____	T. Morrison _____	T. _____
T. Tubb _____ 6400'	T. Delaware Sand _____	T. Todilto _____	T. _____
T. Drinkard _____	T. Bone Springs _____	T. Entrada _____	T. _____
T. Abo _____ 6950'	T. _____	T. Wingate _____	T. _____
T. Wolfcamp _____	T. _____	T. Chinle _____	T. _____
T. Penn _____	T. _____	T. Permian _____	T. _____
T. Cisco (Bough C) _____	T. _____	T. Penn "A" _____	T. _____

### OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....	No. 3, from.....to.....
No. 2, from.....to.....	No. 4, from.....to.....

### IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....	feet.....
No. 2, from.....to.....	feet.....
No. 3, from.....to.....	feet.....

## LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology	From	To	Thickness In Feet	Lithology
0	1200	1200	Sand & Shale				
1200	1610	410	Anhydrite				
1610	2536	926	Salt				
2536	3500	964	Dolomite, Sand, Anhydrite				
3500	4000	500	Dolomite & Sand				
4000	6400	1400	Dolomite & Sand				
6400	6950	550	Dolomite				

Clear