

DISTRICT I
1625 N. French Dr., Hobbs NM 88240

DISTRICT II
1301 W. Grand Avenue, Artesia NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec NM 87410

DISTRICT IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, New Mexico 87504-2088

Form C-103
Revised June 10, 2003

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input checked="" type="checkbox"/> Other _____	7. Lease Name or Unit Agreement Name Reed AXV Com
2. Name of Operator Yates Petroleum Corporation	8. Well Number 1
3. Address of Operator 105 S. 4th Str., Artesia, NM 88210	9. OGRID Number 25575
4. Well Location Unit Letter <u>K</u> : <u>1870</u> feet from the <u>South</u> line and <u>2080</u> feet from the <u>West</u> line Section <u>12</u> Township <u>15S</u> Range <u>34E</u> NMPM _____ County <u>Lea</u>	10. Pool Name or Wildcat Und. <u>Morton Morrow</u> (Gas) <u>North</u>
11. Elevation (Show whether DF, RKB, RT, GR, etc.) 4063'	

12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: Re-Entry Operations ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

Spudded on surface plug @ 9:00 a.m. 2-17-04 w/7-7/8" bit. Drilled to top of stub @ 2290'. TIH w/4-3/4" bit and 1 cleaned out well to 10450'. Set 5-1/2" cement retainer @ 10340' and squeezed Wolfcamp perms w/100 sx H Neat. Moved in rotary tools 3-21-04. Drilled cement retainer (4-3/4" bit). Drilled to 13330'. Reached TD @ 6:15 p.m. 4-21-04. Set 3-1/2" 9.3# casing @ 13330'. Pumped 200 sx 15:61:11 POZ C w/additives. TOC @ 8730'. Perforated Austin, Mississippian (2 SPF) 13172-83' (22), 13188-202' (28), 13244-54' (20) and 13268-80' (80) w/total of 104 - .25" holes. Acidized w/3000 gal 20% NEFE acid w/90 ball sealers. Sandline stranded in lubricator. Fishing. TIH w/wireline spear and blow 3-1/2" dry w/N2 to top of fish. Recovered all sandline. Set 3-1/2" CIBP @ 13150' and capped w/35' cement. Perforated Morrow (6 JSPF) 12968-76' (48) and 12994-99' (30) w/total of 78 - .25" holes. Frac'd w/32000 gal 40# Medallion 40Q foam w/26200# 20/40 Interprop (5-19-04).

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Stormi Davis TITLE Regulatory Compliance Technician DATE 6/1/04

Type or print name Stormi Davis Email address _____ Telephone No. 505-748-1471

(This space for State use)

APPROVED BY [Signature] TITLE PETROLEUM ENGINEER DATE SEP 24 2004

Conditions of approval, if any: