

Submit To Appropriate District Office
State Lease - 6 copies
Fee Lease - 5 copies
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-105
Revised June 10, 2003

WELL API NO. 30-025-36516

5. Indicate Type of Lease
STATE ☐ FEE ☒

State Oil & Gas Lease No.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well:

OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER ☐

b. Type of Completion:

NEW ☒ WORK ☐ DEEPEN ☐ PLUG ☐ DIFF.
WELL OVER BACK RESVR. ☐ OTHER

2. Name of Operator

L.E. Jones Operating, Inc.

3. Address of Operator

P.O. Box 1185, Duncan, OK 73534

4. Well Location

Unit Letter A 866 Feet From The North Line and 991 Feet From The East Line
Section 33 Township 19S Range 38E NMPM Lea County

10. Date Spudded

1-1-04

11. Date T.D. Reached

1-18-04

12. Date Compl. (Ready to Prod.)

02-28-04

13. Elevations (DF& RKB, RT, GR, etc.)

3591 KB

14. Elev. Casinghead

3581'

15. Total Depth

7300'

16. Plug Back T.D.

6479'

17. If Multiple Compl. How Many Zones?

18. Intervals Drilled By

Rotary Tools

Cable Tools

0-7300'

19. Producing Interval(s), of this completion - Top, Bottom, Name

6001-6294, Blinebry

20. Was Directional Survey Made

Yes. Inclination

21. Type Electric and Other Logs Run

Induction, CNL, DEN, ML, GR, CAL

22. Was Well Cored

No

23. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8-5/8"	32#	1635'	12-1/4"	795 Sx	0'
5-1/2"	17#	6523'	7-7/8"	1410 Sx	0'

24. LINER RECORD

SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN

25. TUBING RECORD

SIZE	DEPTH SET	PACKER SET
2-7/8"	6296'	

26. Perforation record (interval, size, and number)

6001-004', 6012-15', 6066-78', 6090-96', 6098-6101',
6120-26', 6138-42', 6160-67', 6235-40', 6270-72', 6278-
80' & 6288-94', 1 SPF

27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.

DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED
6001-6294'	6000 gal 20% Norel
6001-6294'	55,608 gal SpectraFrac 3500 w/ 64,275# 20-40 Sand

28. PRODUCTION

Date First Production

02-28-04

Production Method (Flowing, gas lift, pumping - Size and type pump)

Pumping

Well Status (Prod. or Shut-in)

Prod.

Date of Test

03-15-04

Hours Tested

24

Choke Size

Prod'n For Test Period

Oil - Bbl

28

Gas - MCF

213

Water - Bbl.

20

Gas - Oil Ratio

10,650

Flow Tubing Press.

Casing Pressure

Calculated 24-Hour Rate

Oil - Bbl.

28

Gas - MCF

213

Water - Bbl.

20

Oil Gravity - API - (Corr.)

35.7°

29. Disposition of Gas (Sold, used for fuel, vented, etc.)

Sold

Test Witnessed By

30. List Attachments

Inclination

31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief

Signature

Dan W. Hammond

Printed Name

Dan W. Hammond

Title

Engineer

Date

07-08-04

E-mail Address

dhammond@texhoma.net

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy	1610'	T. Canyon	T. Ojo Alamo
T. Salt		T. Strawn	T. Penn. "B"
B. Salt		T. Atoka	T. Penn. "C"
T. Yates	2865'	T. Miss	T. Penn. "D"
T. 7 Rivers		T. Devonian	T. Leadville
T. Queen	3670'	T. Silurian	T. Madison
T. Grayburg		T. Montoya	T. Elbert
T. San Andres	4285'	T. Simpson	T. McCracken
T. Glorieta		T. McKee	T. Ignacio Otzte
T. Paddock		T. Ellenburger	T. Granite
T. Blinbry	6012'	T. Gr. Wash	T.
T. Tubb	6549'	T. Delaware Sand	T.
T. Drinkard	6918'	T. Bone Springs	T.
T. Abo	7183'	T.	T.
T. Wolfcamp		T.	T.
T. Penn		T.	T.
T. Cisco (Bough C)		T.	T.

No. 1, from 6001' to 6294' No. 3, from to
 No. 2, from to No. 4, from to
OIL OR GAS SANDS OR ZON

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.
 No. 1, from to feet.
 No. 2, from to feet.
 No. 3, from to feet.

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology	From	To	Thickness In Feet	Lithology
0'	1655'		Red Bed				
1655'	2792'		Salt & Anhydrite				
2792'	3835'		Anhydrite				
3835'	7300'		Dolomite				