

New Mexico Oil Conservation Division, District I  
1625 N. French Drive  
Hobbs, NM 88240

Form 3160-3  
(April 2004)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

APPLICATION FOR PERMIT TO DRILL OR REENTER

FORM APPROVED  
OMB No. 1004-0137  
Expires March 31, 2007

1a. Type of work: <input checked="" type="checkbox"/> DRILL <input type="checkbox"/> REENTER		5. Lease Serial No. NMNM106916
1b. Type of Well: <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/> Single Zone <input type="checkbox"/> Multiple Zone		6. If Indian, Allottee or Tribe Name
2. Name of Operator Echo Production, Inc.		7. If Unit or CA Agreement, Name and No.
3a. Address PO Box 1210, Graham, TX 76450		8. Lease Name and Well No. East Livingston 31 Federal #4
3b. Phone No. (include area code) 940-549-3292		9. API Well No. 30-025-36911
4. Location of Well (Report location clearly and in accordance with any State requirements.) At surface 2310' FNL & 1650' FEL At proposed prod. zone Unit 6		10. Field and Pool, or Exploratory Livingston Ridge, Delaware, SE
14. Distance in miles and direction from nearest town or post office* 30 miles east of Carlsbad, New Mexico		11. Sec., T. R. M. or Blk. and Survey or Area Sec 31 T22S R32E
15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any) 1650'	16. No. of acres in lease 640	17. Spacing Unit dedicated to this well 40
18. Distance from proposed location* to nearest well, drilling, completed, applied for, on this lease, ft. 1320'	19. Proposed Depth 9000'	20. BLM/BIA Bond No. on file rotary
21. Elevations (Show whether DF, KDB, RT, GL, etc.) 3517 GR	22. Approximate date work will start* 9/15/04	23. Estimated duration 8 weeks

24. Attachments

CARLSBAD CONTROLLED WATER BASIN

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No.1, shall be attached to this form:

- Well plat certified by a registered surveyor.
- A Drilling Plan.
- A Surface Use Plan (if the location is on National Forest System Lands, the SUPO shall be filed with the appropriate Forest Service Office).
- Bond to cover the operations unless covered by an existing bond on file (see item 20 above).
- Operator certification.
- Such other site specific information and/or plans as may be required by the authorized officer.

25. Signature Tom Golden	Name (Printed/Typed) Tom Golden	Date 7/29/04
Title Operations Manager		
Approved by (Signature) /s/ Joe G. Lara	Name (Printed/Typed) /s/ Joe G. Lara	Date 7 OCT 2004
Title FIELD MANAGER		
Office CARLSBAD FIELD OFFICE		

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Conditions of approval, if any, are attached.

APPROVAL FOR 1 YEAR

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*(Instructions on page 2)

OPER. OGRID NO. 6742  
PROPERTY NO. 32583  
POOL CODE 3938D  
EFF. DATE 10/14/04  
API NO. 30-025-36911

DECLARED WATER BASIN  
CEMENT BEHIND THE 1338"  
CASING MUST BE CIRCULATED

APPROVAL SUBJECT TO  
GENERAL REQUIREMENTS  
AND SPECIAL STIPULATIONS  
ATTACHED

WITNESS

## DISTRICT I

1625 N. FRENCH DR., HOBBS, NM 88240

## DISTRICT II

1301 W. GRAND AVENUE, ARTESIA, NM 88210

## DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

## DISTRICT IV

1220 S. ST. FRANCIS DR., SANTA FE, NM 87505

## State of New Mexico

Energy, Minerals and Natural Resources Department

## OIL CONSERVATION DIVISION

1220 SOUTH ST. FRANCIS DR.  
Santa Fe, New Mexico 87505

Form C-102

Revised JUNE 10, 2003

Submit to Appropriate District Office

State Lease - 4 Copies

Fee Lease - 3 Copies

## WELL LOCATION AND ACREAGE DEDICATION PLAT

☐ AMENDED REPORT

API Number <b>30-025-36A11</b>	Pool Code <b>39380</b>	Pool Name <b>Livingston Ridge Delaware SE</b>
Property Code <b>32583</b>	Property Name <b>EAST LIVINGSTON "31" FEDERAL</b>	Well Number <b>4</b>
OGRID No. <b>6742</b>	Operator Name <b>ECHO PRODUCTION, INC.</b>	Elevation <b>3517'</b>

## Surface Location

UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
G	31	22-S	32-E		2310'	NORTH	1650'	EAST	LEA

## Bottom Hole Location If Different From Surface

UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
Dedicated Acres <b>48</b>	Joint or Infill	Consolidation Code	Order No.						

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED  
OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

LOT 1 45.09 AC		<b>OPERATOR CERTIFICATION</b> I hereby certify the the information contained herein is true and complete to the best of my knowledge and belief. <u>Tom Golden</u> Signature <u>Tom Golden</u> Printed Name <u>Operations Manager</u> Title <u>7/28/04</u> Date
LOT 2		<b>SURVEYOR CERTIFICATION</b> I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief. JULY 21, 2004 Date Surveyed <u>GARY EIDSON</u> Signature & Seal of Professional Surveyor GARY EIDSON 04.11.0905 Certificate No. GARY EIDSON 12641
LOT 3 45.15 AC		
LOT 4 45.21 AC		
45.27 AC		

GEODETIC COORDINATES  
 NAD 27 NME  
 Y=491171.2 N  
 X=692447.8 E  
 LAT.=32°20'55.70" N  
 LONG.=103°42'36.57" W

HOLE PROGNOSIS  
FORM 3160-3 APPLICATION FOR PERMIT TO DRILL  
ECHO PRODUCTION, INC.  
EAST LIVINGSTON '31' FEDERAL #4  
2310' FSL & 1650' FEL  
SECTION 31-22S-32E  
LEA COUNTY, NEW MEXICO

In conjunction with Form 3160-3 Application for Permit to Drill, Echo Production, Inc. submits the following items in accordance with Onshore Oil and Gas Order Numbers 1 and 2, and all other applicable federal and state regulations.

1. Geological Name of Surface Formation:

Permian

2. Estimated Tops of Geologic Markers:

Rustler	750'	Cherry Canyon	5650'
Top of Salt	900'	Brushy Canyon	7100'
Base of Salt	4260'	Lower Brushy Canyon	8150'
Lamar	4550'	Bone Spring	8450'
Bell Canyon	4600'	Avalon Sand	8700'

3. Estimated Depths of Anticipated Fresh Water, Oil or Gas:

Surface	150'	Fresh Water
Delaware	7100'-8450'	Oil or Gas
Bone Spring	8450'	Oil or Gas
Avalon Sand	8700'	Oil or Gas

No other formations are expected to produce oil, gas or fresh water in measurable quantities. The surface fresh water sands will be protected by setting 13 3/8" casing at 800' and circulating cement back to surface. Any shallower zones above TD that contain commercial quantities of oil and/or gas will have cement circulated across the zone.

HOLE PROGNOSIS  
EAST LIVINGSTON '31' FEDERAL #4  
PAGE 2

4. Casing Program:

<u>Hole Size</u>	<u>Interval</u>	<u>OD Csg</u>	<u>Weight, Grade, JT. Cond. Type</u>
17 1/2"	0-800'	13 3/8"	48#, H-40, ST&C
11"	0-4550'	8 5/8"	24# & 32#, J-55, S-80, LT&C
7 7/8"	0-TD	5 1/2"	17#

5. Cementing Program:

- Surface Casing: 13 3/8" casing will be set at approximately 800' and cemented with approximately 670 sacks of Premium Plus cement with 2% CaCl and additives. The amount may be adjusted depending upon the fluid caliper results, however, cement in sufficient quantities to circulate will be utilized.
- Intermediate Casing: 8 5/8" casing will be set at approximately 4550' and cemented with approximately 1300 sacks of 35/65 Poz "c" with additives. The amount may be adjusted dependent upon fluid caliper results, however, cement in sufficient quantities to circulate will be utilized.
- Production Casing: If appropriate, 5 1/2" casing will be set at Total Depth. Echo will utilize cement in sufficient quantities to tie back 600' above any Delaware pay. Well will be cemented w/appropriate number of sacks of 50/50 POZ 'H' w/ additives and 100 sacks of 'C' Neat.

HOLE PROGNOSIS  
EAST LIVINGSTON '31' FEDERAL #4  
PAGE 3

6. Minimum Specifications for Pressure Control:

The blowout preventer equipment (BOP) show in Exhibit "A" will consist of a double ram-type (3000 psi WP) preventer and a bag-type (hydril) preventer (3000 psi WP). Both units will be hydraulically operated and the ram-type preventer will be equipped with blind rams on top and 4 ½" drill pipe rams on bottom. Both BOP's will be nipped up on the 13 3/8" surface casing and used continuously until TD is reached. All BOP's and accessory equipment will be tested to 1000 psi before drilling out of surface casing. Before drilling out of intermediate casing, the ram-type BOP and accessory equipment will be tested to 3000 psi and the hydril to 70% of rated working pressure (2100 psi).

7. Types and Characteristics of the Proposed Mud System:

- |                |  |
|----------------|--|
| O' to 800'     | Fresh water with lime, gel paper and fiber will be used for drilling purposes. Weight 8.4 – 8.6, Vis 29-36, PH > 8.  |
| 800' to 4550'  | Saturated brine water purchased from commercial sources with paper and fiber will be utilized. Weight 8.6-10.5, Vis 32-34, Ph 10.  |
| 4700' to 8800' | Brine and fresh water purchased from commercial sources with gel and starch, 3% KCl, 20-50 PPM Nitrates, Cl 30-75,000, caustic for control and paper for seepage will be utilized. Weight 8.5 – 8.9, Vis 29-34, Ph 9-10, WL 20-50. |

Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be available at the well site at all times.

HOLE PROGNOSIS  
EAST LIVINGSTON '31' FEDERAL #4  
PAGE 4

8. Auxiliary Well Control and Monitoring Equipment:

- A. A kelly cock will be kept in the drill string at all times.
- B. A full opening drill pipe stabbing valve (inside BOP) with proper drill pipe connections will be on the rig floor at all times.

9. Testing, Logging and Coring Program:

A Mudlogging unit will be on location from top of Delaware formation to TD. Mudlogging unit will be employed from approximately 4400' to 9000' (Total Depth).

If indicated, AIT-GR, CNL-LDT-GR logs and Caliper logs will be run at TD. The Gamma Ray AIT will be run from TD back to the intermediate casing. The Gamma Ray Compensated Neutron Log will be run from TD back to surface. If indicated, Echo may elect to run rotary sidewall cores from selected intervals from approximately 7100' to 9000' dependent upon logging results.

10. Abnormal Conditions, Pressures, Temperatures and Potential Hazards:

No abnormal pressures or temperatures are anticipated. Anticipated bottomhole pressure is 3600# PSI.

Loss of circulation is possible in the Delaware section of the hole, however, no major loss circulation zones have been reported in offsetting wells.

Six wells have been drilled and completed in the immediate area. To date, Hydrogen Sulfide has not been encountered. However, if Hydrogen Sulfide is encountered, a Hydrogen Sulfide training and appropriate breathing apparatus is located on site. If necessary, the well can be shut in utilizing the blow out preventer and other equipment to prevent the migration of Hydrogen Sulfide to the surface.

**11. Anticipated Starting Date and Duration of Operations:**

Road and location work will not begin until approval has been received from the BLM. The anticipated spud date is September 15, 2004. Once commenced, the drilling operation will be completed in approximately 20 days. If the well is productive, an additional 15 days will be required for completion and testing before a decision is made to install permanent facilities. In conjunction with Form 3160-3, Application for Permit to Drill, Echo Production, Inc submits the following items in accordance with Onshore Oil and Gas Order Numbers 1 and 2, and all other applicable federal and state regulations.

**SURFACE USE AND OPERATING PLAN  
FORM 3160-3 APPLICATION FOR PERMIT TO DRILL  
ECHO PRODUCTION, INC.  
EAST LIVINGSTON '31' FEDERAL #4  
2310' FSL & 1650' FEL  
SECTION 31-22S-32E  
LEA COUNTY, NEW MEXICO**

Submitted with Form 3160-5, Application For Permit to Drill covering the above proposed well. The purpose of the plan is to describe the location, the proposed construction activities, the operations, the surface disturbance involved, and the rehabilitation of the surface after completion of proposed well so that an appraisal can be made of the environment affected by the proposed well.

**1. Existing Roads:**

- A. The Well Location and Acreage Dedication Plat for the proposed wellsite was staked by Gary Eidson, Registered Professional Surveyor, Carlsbad, New Mexico and is attached.
- B. All roads to the location are shown on Exhibit "B". The existing roads are adequate for travel during drilling and production operations and  $\pm$  1334' of new road will be required.
- C. Directions to location: From Carlsbad; go east to county road 1 mile west of Lea and Eddy County line. Go north 7 miles and turn east on lease road  $\pm$  1  $\frac{3}{4}$  miles then south  $\pm$   $\frac{1}{4}$  mile to location.
- D. Routine grading and maintenance of existing roads will be conducted as necessary to maintain their condition as long as operations continue on the lease.

**2. Proposed Access Road:**

A new access road of approximately 1334' will be required as illustrated on Exhibit B.

- A. The average grade will be less than 5%.
- B. No turnouts will be necessary.
- C. No culverts, gates or low water crossing will be necessary.
- D. Surfacing material will consist of native caliche. If required, road across pad will be surfaced with a minimum of 6" of caliche. Caliche will be obtained from the nearest BLM approved caliche pit. Any additional materials that are required will be purchased from the dirt contractor.



**SURFACE USE AND OPERATING PLAN  
EAST LIVINGSTON '31' FEDERAL #4  
PAGE 2**

**3. Location of Existing Wells:**

All existing wells within a one mile radius of proposed well are show on Exhibit "C".

**4. Location of Existing and/or Proposed Facilities:**

Will utilize existing tank battery located  $\pm 1320'$  east of proposed well.

**5. Location and Type of Water Supply:**

The proposed well will be drilled with a combination of brine and fresh water mud systems as outlined in the Hole Prognosis. The water will be purchased from commercial water stations in the area and trucked to the location by transport over the existing access roads as indicated on Exhibit "B". No water well will be drilled on the location.

**SURFACE USE AND OPERATING PLAN  
EAST LIVINGSTON '31' FEDERAL #4  
PAGE 3**

**6. Source of Construction Materials:**

All caliche required for construction of the drill pad will be obtained from a BLM approved caliche pit. All roads and pads will be constructed of 6" rolled and compacted caliche.

**7. Methods of Handling Water Disposal:**

- A. Drill cuttings not retained for evaluation purposes will be disposed into the reserve pit.
- B. Drilling fluids will be contained in steel mud tanks. The reserve pit will contain any excess drilling fluid or flow from the well during drilling, cementing and completion operations. The reserve pit will be an earthen pit approximately 150' x 150' x 6' deep and fenced on three sides prior to drilling. The fourth side will be fenced immediately following rig removal. The reserve pit will be plastic lined (12 mil thickness) to minimize loss of drilling fluids and saturation of the ground with brine water. Drilling fluids will be allowed to evaporate in the reserve pits until dry.
- C. Water produced from the proposed well during completion may be disposed into the reserve pit or a steel tank (depending upon rates). After the proposed well is permanently placed on production, produced water will be collected in a fiberglass tank and piped to an approved disposal system. Produced oil will be collected in steel tanks until sold.
- D. A portable chemical toilet will be provided on the location for human waste during the drilling and completion operations. Compliance with current laws and regulations will be followed pertaining to the disposal of human waste.
- E. Garbage and trash produced during drilling or completion operations will be disposed in a separate trash trailer on location. All waste material will be contained to prevent scattering by the wind. All water and fluids will be disposed of into the reserve pit. Salts and other chemicals produced during drilling or testing will be disposed into the reserve pit. No toxic waste or hazardous chemicals will be produced by the operation.

**SURFACE USE AND OPERATING PLAN  
EAST LIVINGSTON '31' FEDERAL #4  
PAGE 4**

F. After the rig is moved out and the proposed well is either completed or abandoned, all waste materials will be removed within 30 days. No adverse materials will be left on the location. The reserve pit will be completely fenced and kept closed until dried. When the reserve pit is dry enough to breakout and fill and, as weather permits, the unused portion of the well site will be leveled and reseeded as per BLM specifications. Only that portion of the pad required for production operations will remain in use. In the event of a dry hole, only a dry hole marker will remain.

**8. Ancillary Facilities:**

No airstrip, campsite or other facility will be built as a result of the operations of the proposed well.

**9. Well Site Layout:**

- A. The drill pad layout is shown on Exhibit "D". Dimensions of the pad, pits and location of major rig components are shown. Top soil, if available, will be stockpiled per BLM specifications as determined at the on-site inspection. Since the pad is fairly level no major cuts will be required.
- B. Planned orientation for the rig and associated drilling equipment, reserve pit, pipe racks, turn-around and parking areas, and access road are shown on Exhibit "D". No permanent living facilities are planned, however, a temporary foreman/toolpusher's trailer will be on location during drilling operations.

**SURFACE USE AND OPERATING PLAN  
EAST LIVINGSTON '31' FEDERAL #4  
PAGE 5**

- C. The reserve pit will be lined with a high quality plastic sheeting (12 mil thickness).

**10. Plan for Restoration of the Surface:**

- A. Upon completion of the proposed operations, should the proposed well be abandoned, the pit area, after allowed to dry, will be broken out and leveled. The original topsoil will be returned to the entire location, and leveled and contoured to the original topography as closely as possible.

All trash, garbage and pit lining will be removed in order to leave the location in an aesthetically pleasing condition. All pits will be filled and the location leveled with 120 days after abandonment.

- B. The disturbed area will be revegetated and reseeded during the proper growing season with a seed mixture of native grasses as recommended by the BLM.
- C. Three sides of the reserve pit will be fenced prior to and during drilling operations. At the time the rig is removed, the reserve pit will be fence on the rig (fourth) side to prevent livestock or wildlife from becoming entrapped. The fencing will remain in place until the pit area is cleaned and leveled. No oil will be left on the surface of the fluid in the pit.
- D. Upon completion of the proposed operations, should the proposed well be productive, the reserve pit area will be treated as outlined above within the same prescribed time. The caliche from an area of the original drillsite not needed for production operations or facilities will be removed and used for construction of thicker pads or firewalls for the tank batter installation. Any additional caliche required for facilities will be obtained from a BLM approved caliche pit. Topsoil removed from the drillsite will be used to recontour the pit area and unused portions of the drill pad to the original natural level and reseeded as per BLM specifications.

SURFACE USE AND OPERATING PLAN  
EAST LIVINGSTON '31' FEDERAL #4  
PAGE 6

11. Surface Ownership:

The wellsite and lease are located entirely on Federal surface.

12. Other Information:

- A. The topography around the wellsite is rolling terrain with vegetation of sagebrush and native grass. The vegetation cover consists of prairie grasses and flowers. Wildlife in the area includes those typical of semiarid desert land.
- B. The soils are clayey sand over caliche base.
- C. There is no permanent or live water in the immediate area.
- D. There are no residences and other structures in the area.
- E. The land in the area is used primarily for grazing purposes.
- F. An archaeological study will be submitted separately.

13. Lessee's and Operator's Representative:


Tom Golden  
PO Box 1210  
Graham, Texas 76450  
Phone Number: (940) 549-3292 – office  
(940) 550-3690 – cellular  
(940) 549-3690 – home

SURFACE USE AND OPERATING PLAN  
EAST LIVINGSTON '31' FEDERAL #4  
PAGE 7

14. Certification:

I hereby certify that I, or persons under my direct supervision have inspected the proposed drillsite which currently exists; that the statements made in the plan are to the best of my knowledge, true and correct; and the work associated with the operations proposed herein will be performed by Echo Production, Inc. and its contractors and sub-contractors in conformity with the plan and the terms and conditions under which it is approved. This statement is subject to the provisions of 18 USC 1001 for the filing of a false statement.

ECHO PRODUCTION, INC.



Tom Golden  
Operations Manager

DATE: July 29, 2004

## EXHIBIT "A"


### EQUIPMENT DESCRIPTION

All equipment should be at least 3,000 psi WP or higher unless otherwise specified.

1. Bell nipple
2. Hydril bag type preventer
3. Ram type pressure operated blowout preventer with blind rams.
4. Flanged spool with one 3" and one 2" (minimum) outlet.
5. 2" (minimum) flanged plug or gate valve.
6. 2"x 2"x 2" (minimum) flanged.
7. 3" gate valve.
8. Ram type pressure operated blowout preventer with pipe rams.
9. Flanged type casing head with one side outlet.
10. 2" threaded (or flanged) plug or gate valve. Flanged on 5000# WP, threaded on 3000# WP or less.
11. 3" flanged spacer spool.
12. 3"x 2"x 2"x 2" flanged cross.
13. 2" flanged plug or gate valve.
14. 2" flanged adjustable choke.
15. 2" threaded flange.
16. 2" XXH nipple.
17. 2" forged steel 90° Ell.
18. Cameron (or equal) threaded pressure gauge.
19. Threaded flange.
20. 2" flanged tee.
21. 2" flanged plug or gate valve.
22. 2 1/2" pipe, 300' to pit, anchored.
23. 2 1/2" SE valve.
24. 2 1/2" line to steel pit or separator.

#### NOTES:

- 1). Items 3, 4 and 8 may be replaced with double ram type preventer with side outlets between the rams.
- 2). The two valves next to the stack on the fill and kill line to be closed unless drill string is being pulled.
- 3). Kill line is for emergency use only. This connection shall not be used for filling.
- 4). Replacement pipe rams and blind rams shall be on location at all times.
- 5). Only type U, LSW and QRC ram type preventers with secondary seals are acceptable for 5000 psi WP and higher BOP stacks.
- 6). Type E ram-type BOP's with factory modified side outlets may be used on 3000 psi or lower WP BOP stacks.



Minimum operating equipment for the preventers and hydraulically operated valves shall be as follows: (1) Multiple pumps, driven by a continuous source of power, capable of fluid charging the total accumulator volume from the nitrogen precharge pressure to its rated pressure within \_\_\_\_\_ minutes. Also, the pumps are to be connected to the precharge of nitrogen of not less than 750 PSI and connected so as to receive the aforementioned fluid charge when on must be sufficient to close all the pressure-operated devices simultaneously within \_\_\_\_\_ seconds after starting. (2) Accumulator fluid volume at least \_\_\_\_\_ percent of the original. (3) When requested, an additional source of are shall be additional pumps operated by separate power and equal in performance capabilities.

hydraulic operating system which is to be a closed system. (2) Accumulators with a precharge of nitrogen of not less than 750 PSI and connected so as to receive the aforementioned fluid charge, when the charging pumps shut down, the pressurized fluid volume stored in the accumulators must be sufficient to close all the pressure-operated devices simultaneously within \_\_\_\_\_ seconds. After that, the remaining accumulator pressure shall be not less than 1000 PSI with the remaining accumulator fluid volume at least \_\_\_\_\_ percent of the original. (3) When required, an additional source of power, remote and equivalent, is to be available to operate the above pumps; or there shall be additional pumps operated by separate power and equal in performance capabilities.


The closing manifold and remote closing manifold shall have a separate control for each pressure-operated device. Controls are to be labeled, with control handles indicating open and closed positions. A pressure reducer and regulator must be provided for operating the Hydril preventer. When requested, a second pressure reducer shall be available to limit operating fluid pressures to ram prevention. Gulf Legion No. 38 hydraulic oil, or an equivalent or better, is to be used as the fluid to operate the hydraulic equipment.

The choke manifold, choke flow line, relief line, and choke lines are to be supported by metal stands and adequately anchored. The choke flow line, relief line, and choke lines shall be constructed as straight as possible and without sharp bends. Easy and safe access is to be maintained to the choke manifold. If deemed necessary, walkways and stairways shall be erected in and around the choke manifold. All valves are to be selected for operation in the presence of oil, gas, and drilling fluids. The choke flow line valves and relief line valves connected to the drilling spool and all ram-type preventers must be equipped with stem extensions, universal joints if needed, and hand wheels which are to extend beyond the edge of the derrick substructure. All other valves are to be equipped with handles.

\* To include derrick floor mounted controls.



# LOCATION VERIFICATION MAP



SCALE: 1" = 2000'

CONTOUR INTERVAL:  
BOOTLEG RIDGE, N.M. - 10'

SEC. 31 TWP. 22-S RGE. 32-E

SURVEY \_\_\_\_\_ N.M.P.M.

COUNTY \_\_\_\_\_ LEA

DESCRIPTION 2310' FNL & 1650' FEL


ELEVATION \_\_\_\_\_ 3517'

OPERATOR \_\_\_\_\_ ECHO  
PRODUCTION, INC.

LEASE EAST LIVINGSTON "31" FEDERAL

U.S.G.S. TOPOGRAPHIC MAP  
BOOTLEG RIDGE, N.M.


EXHIBIT "B"



# SECTION 31, TOWNSHIP 22 SOUTH, RANGE 32 EAST, N.M.P.M.,

LEA COUNTY,



NEW MEXICO



## DIRECTIONS TO LOCATION

FROM THE INTERSECTION OF U.S. HWY. 62-180 AND CAMPBELL RD. (H29) GO SOUTH ON CAMPBELL RD. FOR APPROX. 14.8 MILES. TURN LEFT AND GO APPROX. 1.7 MILES EAST TO ROAD SURVEY. FOLLOW ROAD SURVEY FOR APPROX. 1334' SOUTH TO PROPOSED LOCATION.

## EXHIBIT "B"




PROVIDING SURVEYING SERVICES  
SINCE 1946  
**JOHN WEST SURVEYING COMPANY**  
412 N. DAL PASO  
HOBBS, N.M. 88240  
(505) 383-3117

## ECHO PRODUCTION, INC.

EAST LIVINGSTON "31" FEDERAL #4 WELL  
LOCATED 2310 FEET FROM THE NORTH LINE  
AND 1650 FEET FROM THE EAST LINE OF SECTION 31,  
TOWNSHIP 22 SOUTH, RANGE 32 EAST, N.M.P.M.,  
LEA COUNTY, NEW MEXICO.

Survey Date: 07/21/04	Sheet 1 of 1 Sheets
W.O. Number: 04.11.0905	Dr By: J. RIVERO
Date: 07/23/04	Disk: CD#10
04110905	Scale: 1"=100'

# VICINITY MAP



SCALE: 1" = 2 MILES

SEC. 31 TWP. 22-S RGE. 32-E

SURVEY \_\_\_\_\_ N.M.P.M.

COUNTY \_\_\_\_\_ LEA


DESCRIPTION 2310' FNL & 1650' FEL


ELEVATION \_\_\_\_\_ 3517'

OPERATOR \_\_\_\_\_ ECHO PRODUCTION, INC.

LEASE EAST LIVINGSTON "31" FEDERAL

EXHIBIT "B"








Exhibit "D"

East Livingston '31' Federal #4

2310' FNL & 1650' FEL

Section 31 T22S R32E

**STATEMENT ACCEPTING RESPONSIBILITY FOR OPERATIONS**

**Operator Name:** ECHO PRODUCTION, INC.  
**Street or PO Box:** PO Box 1210  
**City, State:** Graham, Texas  
**Zip Code:** 76450

The undersigned accepts all applicable terms, conditions, stipulations, and restrictions concerning operations conducted on the leased land or portion thereof, as described below:

**Lease No.:** NM NM106916 (East Livingston '31' Federal)

**Legal Description of Land:** All of Sec 31 T22S R32E except SW/4 of SW/4

**Formation(s) (if applicable):** Delaware

**Bond Coverage:** (State if individually bonded or another's bond)  
Statewide Bond - Echo Production, Inc.

**BLM Bond File No.:** NM 2692

**Authorized Signature:** 

**Title:** Operations Manager

**Date:** July 29, 2004