

Appropriate District Office: Lease - 5 copies District I 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505		State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505		Form C-105 Revised June 10, 2003	
WELL COMPLETION OR RECOMPLETION REPORT AND LOG				WELL API NO. 30-025-36485 5. Indicate Type of Lease STATE ☒ FEE ☐ State Oil & Gas Lease No. 33115	
1a. Type of Well: OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER ☐ b. Type of Completion: NEW ☒ WORK ☐ DEEPEN ☐ PLUG ☐ DIFF. WELL OVER BACK RESVR. ☐ OTHER ☐				7. Lease Name or Unit Agreement Name New Mexico 36 State	
2. Name of Operator Pride Energy Company				8. Well No. 1	
3. Address of Operator PO Box 701950 Tulsa, OK. 74170-1950				9. Pool name or Wildcat Skaggs, Drinkard	
4. Well Location Unit Letter J 2310 Feet From The South Line and 2310 Feet From The East Line Section 36 Township 19S Range 37E NMPM 19a County					
10. Date Spudded 11/10/03		11. Date T.D. Reached 12/29/03		12. Date Compl. (Ready to Prod.) 3/19/04	
13. Elevations (DF& RKB, RT, GR, etc.) 3,594 GR		14. Elev. Casinghead			
15. Total Depth 7200		16. Plug Back T.D. 7152		17. If Multiple Compl. How Many Zones? 1	
18. Intervals Drilled By All		Rotary Tools		Cable Tools	
19. Producing Interval(s), of this completion - Top, Bottom, Name 7,042-7,046 Drinkard				20. Was Directional Survey Made No	
21. Type Electric and Other Logs Run Dual Laterolog, Micro Laterolog, Gamma Ray Log, CN				22. Was Well Cored No	
23. CASING RECORD (Report all strings set in well)					
CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8.625	24	1547'	12.25	615 sx to surf.	None
5.50	17	7200'	7.875	1781 sx 2 stgs	None
24. LINER RECORD					
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	
25. TUBING RECORD			SIZE	DEPTH SET	PACKER SET
			2 7/8	7,004	
26. Perforation record (interval, size, and number) 7,042-7,046, 4 jsf			27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC. DEPTH INTERVAL AMOUNT AND KIND MATERIAL USED 7042-7046 15 1/2 NEFE Acid - 500 gals		
28. PRODUCTION					
Date First Production 3/19/04		Production Method (Flowing, gas lift, pumping - Size and type pump) Pumping - 1.25" x 20' RHBC Insert Rod		Well Status (Prod. or Sealed) Producing	
Date of Test 3/23/04	Hours Tested 24 hrs	Choke Size Open	Prod'n For Test Period 10	Oil - Bbl 8	Gas - MCF 43
Flow Tubing Press. 150#	Casing Pressure 150#	Calculated 24-Hour Rate 10	Oil - Bbl 8	Gas - MCF 43	Water - Bbl. 39
29. Disposition of Gas (Sold, used for fuel, vented, etc.) Sold					
30. List Attachments					Test Witnessed By
31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief Signature John W. Pride Printed Name John W. Pride Title _____ Date June 25, 2004 E-mail Address john@pride-energy.com					

KZ

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
T. Anby	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Salt	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt 1500	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates 2790	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers 3040	T. Devonian	T. Menefee	T. Madison
T. Queen 3040	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg 4085	T. Montoya	T. Mancos	T. McCracken
T. San Andres	T. Simpson	T. Gallup	T. Ignacio Otzte
T. Glorieta	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T.
T. Blinbry	T. Gr. Wash	T. Morrison	T.
T. Tubb 6498	T. Delaware Sand	T. Todillo	T.
T. Drinkard 6805	T. Bone Springs	T. Entrada	T.
T. Abo -	T.	T. Wingate	T.
T. Wolfcamp -	T.	T. Chinle	T.
T. Penn -	T.	T. Permian	T.
T. Cisco (Bough C)	T.	T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from 6836 to 6858
 No. 2, from 6998 to 7006
 No. 3, from 7042 to 7046
 No. 4, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.
 No. 2, from to feet.
 No. 3, from to feet.

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology	From	To	Thickness In Feet	Lithology
0	1530	1530	SS, SH, EVAPORITES				
1530	4085	2555	SS, SH				
4085	6498	2415	LS, SS, SH				
6498	6805	307	SDYLS, LMY, SS, SH				
6805	7177	372	SDYLS, LMY, SS, SH				