Submit 3 Copies To Appropriate District Office State of New Mexico	Form C-103		
<u>District I</u> Energy, Minerals and Natural Resources	May 27, 2004		
1625 N. French Dr., Hobbs, NM 88240 District II	WELL API NO.		
1301 W. Grand Ave., Artesia, NM 88210 OIL CONSERVATION DIVISION	30-025-08042 5. Indicate Type of Lease		
District III 1220 South St. Francis Dr.	STATE STEE		
1000 Rio Brazos Rd., Aztec, NM 87410 District IV Santa Fe, NM 87505	6. State Oil & Gas Lease No.		
1220 S. St. Francis Dr., Santa Fe, NM	0583950		
87505 SUNDRY NOTICES AND REPORTS ON WELLS	7. Logge Nome on Unit Agreement No.		
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A	7. Lease Name or Unit Agreement Name		
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH	MCA Unit		
PROPOSALS.)  1. Type of Well: Oil Well Gas Well Other Injector	8. Well Number 59W		
2. Name of Operator	9. OGRID Number		
ConocoPhillips Company	217817		
3. Address of Operator	10. Pool name or Wildcat		
4001 Penbrook Street Odessa, Texas 79762	Maljamar; Grayburg-San Andres		
4. Well Location			
Unit Letter X : 1,980 feet from the East line and 1,98	of feet from the South line		
Section 19 Township 17-S Range 32-E	NMPM County Lea		
11. Elevation (Show whether DR, RKB, RT, GR, etc.)			
3,938' DF			
Pit or Below-grade Tank Application or Closure			
Pit type_STEELDepth to Groundwater_70'_Distance from nearest fresh water well_11/2 mile	es_ Distance from nearest surface water_N/A		
Pit Liner Thickness: STEEL mil Below-Grade Tank: Volume180bbls; Column180bbls; Column	onstruction Material STEEL		
12. Check Appropriate Box to Indicate Nature of Notice,			
12. Check Appropriate Box to indicate Nature of Notice,	Report of Other Data		
NOTICE OF INTENTION TO: SUBS	SEQUENT REPORT OF:		
PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐ REMEDIAL WORK	•		
TEMPORARILY ABANDON	LLING OPNS.□ P AND A 🛛		
PULL OR ALTER CASING  MULTIPLE COMPL  CASING/CEMENT	JOB $\square$		
OTHER: OTHER:	23456789		
13 Describe proposed or completed operations. (Clearly state all pertinent details and	give pertinent dates including estimated date		
of starting any proposed work). SEE RULE 1103. For Multiple Completions: Att	ach wellhore diagram of proposed completion		
or recompletion.	way way of grant 199 obosed com Bright		
•	100 miles		
	Sqaor Ty To		
SEE ATTACHED WELLBORE DIAGRAM	Sqaor Ty To		
	5000H 74 33		
09/21/04 Tuesday	131415.65 031.100 862.8212.60		
	131415.65 031.100 862.8212.60		
09/21/04 Tuesday Notified BLM & OCD. MIRU Triple N rig #25 and plugging equipment. NU BOI	131415.65 031.100 862.8212.60		
09/21/04 Tuesday Notified BLM & OCD. MIRU Triple N rig #25 and plugging equipment. NU BOI 09/22/04 Wednesday	P & enviro-val. SDFN.		
09/21/04 Tuesday Notified BLM & OCD. MIRU Triple N rig #25 and plugging equipment. NU BOB 09/22/04 Wednesday Notified BLM & OCD. Reviewed JSA's. RIH w/ workstring and tagged cement re	etainer @ 3,350'. Circulated hole w/ mud,		
09/21/04 Tuesday Notified BLM & OCD. MIRU Triple N rig #25 and plugging equipment. NU BOR 09/22/04 Wednesday Notified BLM & OCD. Reviewed JSA's. RIH w/ workstring and tagged cement repumped 30 sx C cmt 3,350 – 3,078'. Perforated casing @ 1,840'. RIH w/ packer, to	etainer @ 3,350'. Circulated hole w/ mud, unable to establish rate @ 1,500 psi.		
09/21/04 Tuesday Notified BLM & OCD. MIRU Triple N rig #25 and plugging equipment. NU BOB 09/22/04 Wednesday Notified BLM & OCD. Reviewed JSA's. RIH w/ workstring and tagged cement re pumped 30 sx C cmt 3,350 – 3,078'. Perforated casing @ 1,840'. RIH w/ packer, to Pumped 35 sx C cmt 1,894 – 1,690'. WOC 2 and tagged cmt @ 1,700'. Pumped 2	etainer @ 3,350'. Circulated hole w/ mud, unable to establish rate @ 1,500 psi.  5 sx C cmt 807 – 662'. WOC and tagged		
09/21/04 Tuesday Notified BLM & OCD. MIRU Triple N rig #25 and plugging equipment. NU BOB 09/22/04 Wednesday Notified BLM & OCD. Reviewed JSA's. RIH w/ workstring and tagged cement re pumped 30 sx C cmt 3,350 – 3,078'. Perforated casing @ 1,840'. RIH w/ packer, to Pumped 35 sx C cmt 1,894 – 1,690'. WOC 2 and tagged cmt @ 1,700'. Pumped 2 cmt @ 660'. Pumped 25 sx C cmt 403 – 258'. Pumped 25 sx C cmt 50' to surface.	etainer @ 3,350'. Circulated hole w/ mud, unable to establish rate @ 1,500 psi. 5 sx C cmt 807 – 662'. WOC and tagged RDMO.		
09/21/04 Tuesday Notified BLM & OCD. MIRU Triple N rig #25 and plugging equipment. NU BOR 09/22/04 Wednesday Notified BLM & OCD. Reviewed JSA's. RIH w/ workstring and tagged cement re pumped 30 sx C cmt 3,350 – 3,078'. Perforated casing @ 1,840'. RIH w/ packer, to Pumped 35 sx C cmt 1,894 – 1,690'. WOC 2 and tagged cmt @ 1,700'. Pumped 2 cmt @ 660'. Pumped 25 sx C cmt 403 – 258'. Pumped 25 sx C cmt 50' to surface.  App.	etainer @ 3,350°. Circulated hole w/ mud, unable to establish rate @ 1,500 psi. 5 sx C cmt 807 – 662°. WOC and tagged RDMO.  Droved as to plugging of the Well Bore.		
09/21/04 Tuesday Notified BLM & OCD. MIRU Triple N rig #25 and plugging equipment. NU BOB 09/22/04 Wednesday Notified BLM & OCD. Reviewed JSA's. RIH w/ workstring and tagged cement re pumped 30 sx C cmt 3,350 – 3,078'. Perforated casing @ 1,840'. RIH w/ packer, to Pumped 35 sx C cmt 1,894 – 1,690'. WOC 2 and tagged cmt @ 1,700'. Pumped 2 cmt @ 660'. Pumped 25 sx C cmt 403 – 258'. Pumped 25 sx C cmt 50' to surface.  App. Cut off wellhead and anchors, installed dry hole marker. Leveled location.	etainer @ 3,350°. Circulated hole w/ mud, unable to establish rate @ 1,500 psi. 5 sx C cmt 807 – 662°. WOC and tagged RDMO. Proved as to plugging of the Well Bore. Dollity under bond is retained until		
09/21/04 Tuesday Notified BLM & OCD. MIRU Triple N rig #25 and plugging equipment. NU BOB 09/22/04 Wednesday Notified BLM & OCD. Reviewed JSA's. RIH w/ workstring and tagged cement re pumped 30 sx C cmt 3,350 – 3,078'. Perforated casing @ 1,840'. RIH w/ packer, to Pumped 35 sx C cmt 1,894 – 1,690'. WOC 2 and tagged cmt @ 1,700'. Pumped 2 cmt @ 660'. Pumped 25 sx C cmt 403 – 258'. Pumped 25 sx C cmt 50' to surface.  App. Cut off wellhead and anchors, installed dry hole marker. Leveled location.	etainer @ 3,350°. Circulated hole w/ mud, unable to establish rate @ 1,500 psi. 5 sx C cmt 807 – 662°. WOC and tagged RDMO.  Droved as to plugging of the Well Bore.		
09/21/04 Tuesday Notified BLM & OCD. MIRU Triple N rig #25 and plugging equipment. NU BOR  09/22/04 Wednesday Notified BLM & OCD. Reviewed JSA's. RIH w/ workstring and tagged cement re pumped 30 sx C cmt 3,350 – 3,078'. Perforated casing @ 1,840'. RIH w/ packer, to Pumped 35 sx C cmt 1,894 – 1,690'. WOC 2 and tagged cmt @ 1,700'. Pumped 2 cmt @ 660'. Pumped 25 sx C cmt 403 – 258'. Pumped 25 sx C cmt 50' to surface.  App. Cut off wellhead and anchors, installed dry hole marker. Leveled location.	etainer @ 3,350°. Circulated hole w/ mud, unable to establish rate @ 1,500 psi. 5 sx C cmt 807 – 662°. WOC and tagged RDMO. Proved as to plugging of the Well Bore. Solity under bond is retained until face restoration is completed.		
Notified BLM & OCD. MIRU Triple N rig #25 and plugging equipment. NU BOR 09/22/04 Wednesday  Notified BLM & OCD. Reviewed JSA's. RIH w/ workstring and tagged cement repumped 30 sx C cmt 3,350 – 3,078'. Perforated casing @ 1,840'. RIH w/ packer, Pumped 35 sx C cmt 1,894 – 1,690'. WOC 2 and tagged cmt @ 1,700'. Pumped 2 cmt @ 660'. Pumped 25 sx C cmt 403 – 258'. Pumped 25 sx C cmt 50' to surface. App. Cut off wellhead and anchors, installed dry hole marker. Leveled location.  I hereby certify that the information above is true and complete to the best of my knowledge.	etainer @ 3,350°. Circulated hole w/ mud, unable to establish rate @ 1,500 psi. 5 sx C cmt 807 – 662°. WOC and tagged RDMO. Proved as to plugging of the Well Bore. Solity under bond is retained until ace restoration is completed.		
09/21/04 Tuesday Notified BLM & OCD. MIRU Triple N rig #25 and plugging equipment. NU BOR  09/22/04 Wednesday Notified BLM & OCD. Reviewed JSA's. RIH w/ workstring and tagged cement re pumped 30 sx C cmt 3,350 – 3,078'. Perforated casing @ 1,840'. RIH w/ packer, to Pumped 35 sx C cmt 1,894 – 1,690'. WOC 2 and tagged cmt @ 1,700'. Pumped 2 cmt @ 660'. Pumped 25 sx C cmt 403 – 258'. Pumped 25 sx C cmt 50' to surface.  App. Cut off wellhead and anchors, installed dry hole marker. Leveled location.	etainer @ 3,350°. Circulated hole w/ mud, unable to establish rate @ 1,500 psi. 5 sx C cmt 807 – 662°. WOC and tagged RDMO. Proved as to plugging of the Well Bore. Solity under bond is retained until ace restoration is completed.		
Notified BLM & OCD. MIRU Triple N rig #25 and plugging equipment. NU BOB 09/22/04 Wednesday  Notified BLM & OCD. Reviewed JSA's. RIH w/ workstring and tagged cement repumped 30 sx C cmt 3,350 − 3,078'. Perforated casing @ 1,840'. RIH w/ packer, Pumped 35 sx C cmt 1,894 − 1,690'. WOC 2 and tagged cmt @ 1,700'. Pumped 2 cmt @ 660'. Pumped 25 sx C cmt 403 − 258'. Pumped 25 sx C cmt 50' to surface. App. Cut off wellhead and anchors, installed dry hole marker. Leveled location.  I hereby certify that the information above is true and complete to the best of my knowledge grade tank has been/will be constructed or closed according to NMOCD guidelines ⊠, a general permit □ 3.	etainer @ 3,350°. Circulated hole w/ mud, unable to establish rate @ 1,500 psi. 5 sx C cmt 807 – 662°. WOC and tagged RDMO. Proved as to plugging of the Well Bore. Solity under bond is retained until face restoration is completed.		
Notified BLM & OCD. MIRU Triple N rig #25 and plugging equipment. NU BOB 09/22/04 Wednesday  Notified BLM & OCD. Reviewed JSA's. RIH w/ workstring and tagged cement repumped 30 sx C cmt 3,350 − 3,078'. Perforated casing @ 1,840'. RIH w/ packer, Pumped 35 sx C cmt 1,894 − 1,690'. WOC 2 and tagged cmt @ 1,700'. Pumped 2 cmt @ 660'. Pumped 25 sx C cmt 403 − 258'. Pumped 25 sx C cmt 50' to surface. App. Cut off wellhead and anchors, installed dry hole marker. Leveled location.  I hereby certify that the information above is true and complete to the best of my knowledge grade tank has been/will be constructed or closed according to NMOCD guidelines ⋈, a general permit □ surface.  TITLE James F. Newman, P. SIGNATURE  TITLE James F. Newman, P. SIGNATURE	etainer @ 3,350°. Circulated hole w/ mud, unable to establish rate @ 1,500 psi. 5 sx C cmt 807 – 662°. WOC and tagged RDMO. Proved as to plugging of the Well Bore. Polity under bond is retained until face restoration is completed.  E and belief. I further certify that any pit or belower an (attached) alternative OCD-approved plan .  E. (Triple N Services) DATE 10/02/04		
Notified BLM & OCD. MIRU Triple N rig #25 and plugging equipment. NU BOB  09/22/04 Wednesday Notified BLM & OCD. Reviewed JSA's. RIH w/ workstring and tagged cement re pumped 30 sx C cmt 3,350 − 3,078'. Perforated casing @ 1,840'. RIH w/ packer, re Pumped 35 sx C cmt 1,894 − 1,690'. WOC 2 and tagged cmt @ 1,700'. Pumped 2 cmt @ 660'. Pumped 25 sx C cmt 403 − 258'. Pumped 25 sx C cmt 50' to surface.  App Cut off wellhead and anchors, installed dry hole marker. Leveled location.  I hereby certify that the information above is true and complete to the best of my knowledge grade tank has been/will be constructed or closed according to NMOCD guidelines ⋈, a general permit □  SIGNATURE  TITLE James F. Newman, P.  Type or print name  James F. Newman  E-mail address: jim@triplene	etainer @ 3,350°. Circulated hole w/ mud, unable to establish rate @ 1,500 psi. 5 sx C cmt 807 – 662°. WOC and tagged RDMO. Proved as to plugging of the Well Bore. Polity under bond is retained until face restoration is completed.  E and belief. I further certify that any pit or belower an (attached) alternative OCD-approved plan .  E. (Triple N Services) DATE 10/02/04		
Notified BLM & OCD. MIRU Triple N rig #25 and plugging equipment. NU BOB 09/22/04 Wednesday  Notified BLM & OCD. Reviewed JSA's. RIH w/ workstring and tagged cement repumped 30 sx C cmt 3,350 − 3,078'. Perforated casing @ 1,840'. RIH w/ packer, Pumped 35 sx C cmt 1,894 − 1,690'. WOC 2 and tagged cmt @ 1,700'. Pumped 2 cmt @ 660'. Pumped 25 sx C cmt 403 − 258'. Pumped 25 sx C cmt 50' to surface. App. Cut off wellhead and anchors, installed dry hole marker. Leveled location.  I hereby certify that the information above is true and complete to the best of my knowledge grade tank has been/will be constructed or closed according to NMOCD guidelines ⋈, a general permit □ surface.  TITLE James F. Newman, P. SIGNATURE  TITLE James F. Newman, P. SIGNATURE	etainer @ 3,350°. Circulated hole w/ mud, unable to establish rate @ 1,500 psi. 5 sx C cmt 807 – 662°. WOC and tagged RDMO. Proved as to plugging of the Well Bore. Polity under bond is retained until face restoration is completed.  E and belief. I further certify that any pit or belower an (attached) alternative OCD-approved plan .  E. (Triple N Services) DATE 10/02/04		
Notified BLM & OCD. MIRU Triple N rig #25 and plugging equipment. NU BOR 09/22/04 Wednesday  Notified BLM & OCD. Reviewed JSA's. RIH w/ workstring and tagged cement re pumped 30 sx C cmt 3,350 − 3,078'. Perforated casing @ 1,840'. RIH w/ packer, pumped 35 sx C cmt 1,894 − 1,690'. WOC 2 and tagged cmt @ 1,700'. Pumped 2 cmt @ 660'. Pumped 25 sx C cmt 403 − 258'. Pumped 25 sx C cmt 50' to surface. App. Cut off wellhead and anchors, installed dry hole marker. Leveled location.  I hereby certify that the information above is true and complete to the best of my knowledge grade tank has been/will be constructed or closed according to NMOCD guidelines ⊠, a general permit □ surface. TITLE James F. Newman, P.J. Type or print name  For State Use Only  Femail address: jim@triplems	etainer @ 3,350°. Circulated hole w/ mud, unable to establish rate @ 1,500 psi. 5 sx C cmt 807 – 662°. WOC and tagged RDMO. Proved as to plugging of the Well Bore. Polity under bond is retained until acce restoration is completed.  E and belief. I further certify that any pit or belower an (attached) alternative OCD-approved plan .  E. (Triple N Services) DATE 10/02/04  Services.com Telephone No. 432-687-1994		
Notified BLM & OCD. MIRU Triple N rig #25 and plugging equipment. NU BOR  09/22/04 Wednesday  Notified BLM & OCD. Reviewed JSA's. RIH w/ workstring and tagged cement re pumped 30 sx C cmt 3,350 − 3,078'. Perforated casing @ 1,840'. RIH w/ packer, re Pumped 35 sx C cmt 1,894 − 1,690'. WOC 2 and tagged cmt @ 1,700'. Pumped 2  cmt @ 660'. Pumped 25 sx C cmt 403 − 258'. Pumped 25 sx C cmt 50' to surface.  App.  Cut off wellhead and anchors, installed dry hole marker. Leveled location.  I hereby certify that the information above is true and complete to the best of my knowledge grade tank has been/will be constructed or closed according to NMOCD guidelines ⋈, a general permit □  SIGNATURE  TITLE James F. Newman, P.  Type or print name  James F. Newman  E-mail address: jim@triplens  For State Use Only  APPROVED BY:  TITLE OC FIELD REPRES	etainer @ 3,350°. Circulated hole w/ mud, unable to establish rate @ 1,500 psi. 5 sx C cmt 807 – 662°. WOC and tagged RDMO. Proved as to plugging of the Well Bore. Polity under bond is retained until face restoration is completed.  E. (Triple N Services) DATE 10/02/04  Services.com Telephone No. 432-687-1994  ENTATIVE II/STAFFMANAGER		
Notified BLM & OCD. MIRU Triple N rig #25 and plugging equipment. NU BOR 09/22/04 Wednesday  Notified BLM & OCD. Reviewed JSA's. RIH w/ workstring and tagged cement re pumped 30 sx C cmt 3,350 − 3,078'. Perforated casing @ 1,840'. RIH w/ packer, pumped 35 sx C cmt 1,894 − 1,690'. WOC 2 and tagged cmt @ 1,700'. Pumped 2 cmt @ 660'. Pumped 25 sx C cmt 403 − 258'. Pumped 25 sx C cmt 50' to surface. App. Cut off wellhead and anchors, installed dry hole marker. Leveled location.  I hereby certify that the information above is true and complete to the best of my knowledge grade tank has been/will be constructed or closed according to NMOCD guidelines ⊠, a general permit □ surface. TITLE James F. Newman, P.J. Type or print name  For State Use Only  Femail address: jim@triplems	etainer @ 3,350°. Circulated hole w/ mud, unable to establish rate @ 1,500 psi. 5 sx C cmt 807 – 662°. WOC and tagged RDMO. Proved as to plugging of the Well Bore. Polity under bond is retained until acce restoration is completed.  E and belief. I further certify that any pit or belower an (attached) alternative OCD-approved plan .  E. (Triple N Services) DATE 10/02/04  Services.com Telephone No. 432-687-1994		

The state of the s

emitevas som

					Date: September 29, 2004
3938'	<del>-</del> -				
	<u>-</u>	Subarea :		Maljamar	
		Lease & Well N	lo.:	MCA Unit No. 59W 1980' FSL & 1980' FEL Center NW/4 SE/4 Section 19,	
Mill mand substr		Legal Description	on:		
	25 sx C cmt 50' - surface			T-17-S, R-32-E, NMPM Mer	idian
		County:	Lea	State :	New Mexico
		Field :		Maljamar (GB-SA)	
		Date Spudded :		May 25, 1942 IPP:	
198	25 sx C cmt 403 - 258'	API Number :		30-025-08042	
		Status:		PLUGGED 09/22/04	
		Drilled as Mitch	ell-B No. 1	1	
Š	8-5/8" 28# @ 754' w/50 sx (12-1/4" Hole)		Data	C	
	0-010 20# @ 104 W.30 3X (12-1/4 Flote)		Date	Comments	
	25 sx C cmt 807 - 660' TAGGED		2/15/68	Convert to water injection 550 E	<u> </u>
	25 SX C CIRC 807 - 860 TAGGED		3/8/71	Mill from 3973-3985 Top of Fish	l
	903 904! Carld w/80 au to au faire		3/12/71	Drill 3999-4041	_
	803-804' Sqz'd w/80 sx to surface in 7" x 8-5/8" annulus		12/7/74	Fill hole w/crushed rock to 3570	
, m	III / X 0-5/6 attitutus			Run 8 jts 4-1/2" Liner (365' tot	al). Top Liner @ 3191'
			44.55	Btm of liner @ 3573' w/50 sx	
			11/75	Ran csg inspection log 3191 to	surt, OK 800 psi
			9/21/76	Sqz 803'-804' w/80 sx	
			9/25/76 9/29/76	Leak in 7" casing below 900'	
			10/5/76	Squeeze 3220' w/100 sacks Cla	
			4/2/92		
			4/2/92	Set packer @ 3384, RBP @ 34	
			12/14/04	in 30 min, test backside - hold, r Set Cement Retainer @ 3350',	
			12/14/54	Temporarily Abandoned	iay down tubing
			1/3/95		well for unbala material in Over a
			11/3/03	Sundry Notice for uphole in either	well for uphole potential in Queen
			12/15/03		
			12/10/00	procedure by 10/19/04	orm with or submit plugging
				procedure by 10/10/04	
	35 sx C cmt 1,894 - 1,700' TAGGED				
	(unable to sqz perfs @ 1,840')				
					•
			ł		<b>27</b> 7
					LA.7
	TOC @ 2,000'				
				ACTUAL PLUGGING	3 PROCEDURE
					-
			1)	30 sx C cmt on existing CICF	R 3,350 - 3,078'
				35 sx C cmt 1,894 - 1,700'	
			l í	(unable to sqz perfs @ 1,840')	
			3)	25 sx C cmt 807 - 660' TAG	GED
			4)	25 sx C cmt 403 - 258'	

## JRE

- 4) 25 sx C cmt 403 258'
- 5) 25 sx C cmt 50' surface

30 sx C cmt on existing CICR 3,350 - 3,078'

3220' Sqz'd w/100 sx to Liner Top

Cement Retainer @ 3350'

7" 20# @ 3477' w/150 sx (TOC @ 2,000') 4-1/2" Liner, 9.5# @ 3190-3573 w/50 sx

OH 3573-3995'

Formation Tops:

Top of fish @ 3985' Plug 3986-3995

3588-3675 3688-3727 6th Zone 7th Zone 9th Zone 3927-3995

PBTD: 3800' OTD: 3995 NTD: 4040

TRIPLE N
LA SERVICES INC.
MIDLANG TX