

Submit 3 Copies To Appropriate District  
Office  
District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
1301 W. Grand Ave., Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM  
87505

State of New Mexico  
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

Form C-103  
Revised June 10, 2003

<b>SUNDRY NOTICES AND REPORTS ON WELLS</b> (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-025-34295
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>		5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
2. Name of Operator Me-Tex Oil & Gas, Inc.		6. State Oil & Gas Lease No.
3. Address of Operator P.O. Box 2070, Hobbs, NM 88241		7. Lease Name or Unit Agreement Name J. Cooper
4. Well Location Unit Letter <u>G</u> : <u>1450</u> feet from the <u>North</u> line and <u>1867</u> feet from the <u>East</u> line Section <u>3</u> Township <u>20S</u> Range <u>37E</u> NMPM County <u>Lea</u>		8. Well Number 2
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3561' GR		9. OGRID Number 014462
		10. Pool name or Wildcat Northwest Skaggs Drinkard

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

- PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐  
OTHER: ☐

SUBSEQUENT REPORT OF:

- REMEDIAL WORK ☒ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

- Kill well with 25 bbls. brine water, release pkr. and P.O.H.
- Perforate additional drinkard with 4" Select-Fire Gun, 2 JSPF, 180 degree phasing as follows: 6,743', 46', 49', 50', 51', 55', 56', 94', 95', 6,802', 03', 06', 08', 11', 12', 29', 33', 34', 40', 42', 44', and 46' (total 44 holes).
- Set pkr. @ 6,681'.
- Acidized perfs. 6,743' - 6,846' w/3,000 gals. 15% anti-sludge Hcl acid w/ball sealers.
- Flowed for clean-up and returned to sales line.
- Release Pkr. & P.O.H., R.I.H. w/production tbg. w/bull plug. M.A. -6,900'; 4' Perf sub - 6,865', S.N. - 6,864', 12 jnt. 2-3/8" tbg., 5-1/2" X 2-3/8" T.A. - 6,486' & 210 jts. 2-3/8" tbg. Set T.A. with 14 pts. Tension, flange well head, rig to run rods. 1" x 10' gas anchor, 2' x 1-1/2" x 16' RHBC Pump, 123 3/4" rod; 89 - 7/8" rods, 4', 6', & 8' - 7/8" subs, 22' - 1-1/4" polish rods w/10' - 1-1/2" polish rod liner, seat pump.
- Electrify and set pumping unit. Return to production.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tonia Harper TITLE Production Clerk DATE Oct. 1, 2004

Type or print name Tonia Harper E-mail address: tharper@zianet.com Telephone No. 505-397-7750

(This space for State use)

APPROVED BY Larry W. Wain TITLE OC FIELD REPRESENTATIVE II/STAFF MANAGER DATE OCT 25 2004

Conditions of approval, if any