This form is <u>not</u> to be used for reporting packer leakage tests in Southeast New Mexico

NEW MEXICO OIL CONSERVATION DIVISION

Page 1 Revised June 10, 2003

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST

bp Operator 20	Annual and Dunal	uction Company t. Farmington.	, . NM 8740]	Lease Na	me	RIDDUEF	Well LS No. 5	
		A Sec 3						
	Name of Res	servoir or Pool	Type of Prod. (Oil or Gas)		1	ethod of Prod. ow of Art. Lift)	Prod. Medium (Tbg. Or Csg.)	
Upper Completion	S. BLANCE	s PC	GAS			FLOW	тва	
Lower Completion	BLANCO M	nv	GAS		<u></u>	FLOW	TBG	
		Pre	e-Flow Shut-	In Pressure Da	ta			
Upper	Hour, Date, Shut	-In	Length of Time Shut-In		SI Press. Psig		Stabilized? (Yes or No)	
Completion	10/5/04		72 HOURS		 -	216	YES	
Lower Completion	Hour, Date, Shut-In		Length of Time Shut-In 72 HOURS		SIF	Press. Psig 1년 및	Stabilized? (Yes or No) YES	
_			Flow To	est No. 1				
Commenced at (hour, date)*				Zone producing (U		per or Lower):		
Time (Hour, Date)	Lapsed Time Since*	Pres Upper Compl.	ssure Lower Comp	Prod. Zo ol. Temp		Remarks		
10 /5	DAY 1	177	142			BOTH ZONES SHUT IN		
10/6	DAY 2	206	142			BOTH ZONES SHUT IN		
10/7	DAY 3	216	142		-	BOTH ZONES SHUT IN		
1018	DAY 4	178	143			FLOW UPPER ZONE		
10/9	DAY 5	163	146			FLOW "	ZONE	
10/10	DAY 6	160	152			FLOW "	ZONE .	
roduction rate	e during test	DID NOT	bross O	ver 10%	, — I	CONTINUE	Tesi	
)il:	BOPD based o	nBbl	s. In	Hrs		Grav.	GOR	
as:	MCFP	D; Test thru (Orifi	ce or Meter):					
		 Mie	d-Test Shut-l	In Pressure Dat	a		•	
Upper Completion	er Hour, Date, Shut-In					ess. Psig	Stabilized? (Yes or No)	
Lower Completion	Hour, Date, Shut	-In	Length of Time Shut-In		SI Pr	ess. Psig	Stabilized? (Yes or No)	
			(Continue on	reverse side)		· · ·		



Flow Test No. 2.

Commenced a	at (hour, date)**			Zone producing (Upper or Lower):				
Time	Lapsed Time	e <u>Pressure</u>		Prod. Zone	Remarks			
(Hour, Date)	Since**	Upper Compl.	Lower Compl					
10/11		178	154	hV .	BOTH ZONES SHUT IN			
10/12		313	158		0 0 0			
10/13		324	163		the contract of the contract o			
10/19		228	142		From LOWER ZONE			
19/15	·	244	133		and the second			
10/16		- 250 ·	133					
Production rate during test Oil:BOPD based on		on	Bbls. In	Hrs	Grav GOR			
Gas:	MCFPI	O; Test thru (Orif	ice or Meter): _					
hereby certify			ed is true and c	omplete to the best	of my knowledge.			
Approved	OCT 1 g		20	Operator br	America Production Company			
New Mexico Oi	il Conservation D	ixision	By St	By Sheri Bradshaw				
By Chr	wh TY			_ Title <u>F</u> j	eld Tech SS			
Title DEPUTY	OIL & GAS INSPEC	TOR, DIST. 🚜		_,	ss 1 0/8/01			
*								

Northwest New Mexico Packer Leakage Test Instructions

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and unually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when equested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage est, the operator shall notify the Division in writing of the exact time the est is to be commenced. Offset operators shall also be so notified.
- 1. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain hut-in until the well-head pressure in each has stabilized, provided lowever, that they need not remain shut-in more than seven days.
- For Flow Test No. 1, one zone of the dual completion shall be roduced at the normal rate of production while the other zone remains hut-in. Such test shall be continued for seven days in case of a gas well and 24 hours in the case of an oil well. Note: if, on an initial packer eakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- . Following completion of Flow Test No. 1, the well shall again be hut-in, in accordance with Paragraph 3 above.

- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hour tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 11-16-98, with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).