## This form is <u>not</u> to be used for reporting eacker leakage tests a Southeast New Mexico

## NEW MEXICO OIL CONSERVATION DIVISION

Page 1 Revised June 10, 2003

## NORTHWEST NEW MEXICO PACKER LEAKAGE TEST

bp perator <u>20</u>	America Prod O Energy Cour	uction Company t, Farmington	y <b>, NM</b> 87401	Lease N	ame _	WARREN F	Well 1 <u>LS</u> No. <u>1</u>	
ocation Of V	Vell: Unit Letter_	KSec_ <u>3</u>	15Twp	<u> </u>	9 1	<u>  API # 30-0<sup>5</sup> 45</u>	-07142	
	Name of Res	servoir or Pool	Type of Prod. (Oil or Gas)			lethod of Prod. low or Art. Lift)	Prod. Medium (Tbg. Or Csg.)	
Upper Completion	S BLANC	o PC		GAS		FLOW	твс .	
Lower Completion	BLANCO	mV		GAS		FLOW	TBG	
		Pr		In Pressure Da	ata			
Upper Completion	Hour, Date, Shut	104	72 HC	Length of Time Shut-In 72 HOURS		Press. Psig 1년 6	Stabilized? (Yes or No) YES	
Lower Completion	Hour, Date, Shut		Length of Time Shut-In 72 HOURS		SI	Press. Psig	Stabilized? (Yes or No) YES	
			Flow To	est No. 1				
Commenced	at (hour, date)*				ng (Up	per or Lower):		
Time Hour, Date)	Lapsed Time Since*	Pre Upper Compl.	ssure Lower Comp	Prod. Z		Remarks		
10/12	DAY 1	131	141		i	BOTH ZONES SHUT IN		
10/13	DAY 2	145	148			BOTH ZONES SHUT IN		
10/14	DAY 3	146	152			BOTH ZONES SHUT IN		
10/15	DAY 4	150	140			FLOW LOWE	R ZONE	
10/16	DAY 5	151	134			FLOW "	ZONE	
10/17	DAY 6	152	132			FLOW "	ZONE .	
oduction rat	e during test							
l:	BOPD based o	nBbl	ls. In	Hrs	<del></del>	Grav.	GOR	
s:	MCFP	D; Test thru (Orif	ice or Meter):			<del></del>		
		 <b>M</b> i	id-Test Shut-l	in Pressure Da	ata		•	
Upper ompletion	Hour, Date, Shut	ı-In	Length of Time Shut-In		SI Pı	ess. Psig	Stabilized? (Yes or No)	
Lower ompletion	Hour, Date, Shut	i-In	Length of Ti	me Shut-In	SI Pı	ess. Psig	Stabilized? (Yes or No)	
			(Continue on	reverse side)			15 10 17 20 x	

## Flow Test No. 2

Commenced a	it (hour, date)**		11077 1	<del></del>	ne producing (U	oper or Lower)	:		
Time (Hour, Date)	Lapsed Time Since**	Upper Compl.	essure Lower Comp	`	Prod. Zone	Remarks			
			·	1;	,				
		, '		·					
-									
		,					-		
				-					
il: BOPD based on Bbls. In MCFPD; Test thru (Orifice or Meter):					_ Hrs	Grav	GOR		
emarks:	!	ion herein contair			lete to the best o	of my knowled	ge.		
proved	OCT 1 o	2004	20	<b>-</b>	Operator bp	America Pr	oduction Company		
Phul The						eri Bradsha eld Tech	w 8		
tle DEPUTY OIL & GAS INSPECTOR, DIST. #8					E-mail Address				
-		•			Date i	0/18/04	( · · · · ·		

Northwest New Mexico Packer Leakage Test Instructions

A packer leakage test shall be commenced on each multiply opleted well within seven days after actual completion of the well, and ually thereafter as prescribed by the order authorizing the multiple opletion. Such tests shall also be commenced on all multiple opletions within seven days following recompletion and/or chemical fracture treatment, and whenever remedial work has been done on a l during which the packer or the tubing have been disturbed. Tests ll also be taken at any time that communication is suspected or when nested by the Division.

At least 72 hours prior to the commencement of any packer leakage, the operator shall notify the Division in writing of the exact time the is to be commenced. Offset operators shall also be so notified.

The packer leakage test shall commence when both zones of the dual upletion are shut-in for pressure stabilization. Both zones shall remain t-in until the well-head pressure in each has stabilized, provided rever, that they need not remain shut-in more than seven days.

For Flow Test No. 1, one zone of the dual completion shall be luced at the normal rate of production while the other zone remains -in. Such test shall be continued for seven days in case of a gas well 24 hours in the case of an oil well. Note: if, on an initial packer age test, a gas well is being flowed to the atmosphere due to the lack pipeline connection the flow period shall be three hours.

Following completion of Flow Test No. 1, the well shall again be in, in accordance with Paragraph 3 above.

- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hour tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Til Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 11-16-98, with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).