This form is <u>not</u> to be used for reporting packer leakage tests in Southeast New Mexico

NEW MEXICO OIL CONSERVATION DIVISION

Page 1

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST

Revised June 10, 2003

bp Operator <u>20</u>	America Prod O Energy Cour	uction Company t, Farmington	y NM 87401	_ Lease Na	ıme _`	McCulley	Well LS No. 5 M						
Location Of V	Vell: Unit Letter_	D Sec &	24 Twp 28	<u>N</u> Rge	9 1	√ API # 30-0 ¹ 45	- 26544						
	Name of Res	servoir or Pool	Type of I (Oil or C		lethod of Prod. ow of Art. Lift)	Prod. Medium (Tbg. Or Csg.)							
Upper Completion	BLANCO	m v	GAS.	FLOW		TBG							
Lower Completion	BASIN	DK	GAS	FLOW		TRG							
Pre-Flow Shut-In Pressure Data													
Upper Completion	Hour, Date, Shut		Length of Time	SI Press. Psig		Stabilized? (Yes or No) YES							
Lower Completion	Hour, Date, Shut	-In	Length of Time 72 HOURS	SI	Press. Psig	Stabilized? (Yes or No) YES							
	,		Flow Test N	lo. 1									
Commenced at (hour, date)* Zone producing (Upper or Lower):													
Time (Hour, Date)	Lapsed Time Since*	Pre Upper Compl.	ssure Lower Compl.	Prod. Zone Temp.		Remarks							
10/5	DAY 1	119	180			BOTH ZONES S	SHUT IN						
10 / 6	DAY 2	191	197			BOTH ZONES S	SHUT IN						
10 / 7	DAY 3	123	203			BOTH ZONES S	SHUT IN						
16 18	DAY 4	124	174		i	FLOW LOWER	ZONE						
10 /9	DAY 5	125	163		i	FLOW "	ZONE						
10/10	DAY 6	126	162			FLOW "	ZONE						
roduction rate	e during test	DID	NOT CROSS	OU ER	- 00	NTINUE TE	<u>.</u> Si						
il:	BOPD based on Bbls		. In Hrs		Grav		GOR						
as:	MCFP	D; Test thru (Orif	ice or Meter):										
Mid-Test Shut-In Pressure Data													
Upper Completion	Hour, Date, Shut	-In	Length of Time Shut-In		SI Press. Psig		Stabilized? (Yes or No)						
Lower Completion	Hour, Date, Shut	-In	Length of Time S	SI Pr	ess. Psig	Stabilized? (Yes or No)							
(Continue on reverse side)													

			Flow Te	st No	. 2-						
Commenced at (hour, date)**					Zone producing (Upper or Lower):						
Time	Lapsed Time	<u>Pressure</u>		Prod. Zone		e Remarks	Remarks				
(Hour, Date)	Since**	Upper Compl.	Lower Compl	i.	Temp.		٠.				
	,	mv		DK							
10/11	· · · · ·	127.	187	\rightarrow	•	Dour	Zones	<u> Dhut</u>	<u></u>		
10/12		130	207	٠,	*	15,		· · · · · ·	11		
10/13		133	217	"	•,		15	• • •	· 13		
10/14		131	991			Fiou	UPPER	ZONE	•		
10/15		123	221	,		.7	13	ь			
10/16		122	a35			· ·	£ (, ,				
Production rate	during test										
Oil: BOPD based on Bbls. In MCFPD; Test thru (Orifice or Meter):					_ Hrs	Grav.		_GOR	· ·		
Gas: Remarks:	MCFPI); Test thru (Onli	ice or Meter): _	*					 		
Ciliaiks.	•	•									
21					:						
hereby certify	that the informati	on herein contain	ed is true and c	ompl	ete to the be	st of my know	vledge.	1			
	OCTIO								•		
Approved	OCT 1 g	<u> </u>	20	•	Operator_	bp America	a Product	ion Compa	any		
New Mexico Oil	Conservation D	lvision			D.,	Chaus Dun	da h				
					ъу	Sheri Bra	usnaw 🤫	ユ			
By Chan	hIta		-	_	Title	Field Tecl	ń.,				
,		•				•					
ritle DEPUTY OIL & GAS INSPECTOR, DIST. #3					E-mail Address						

Date Northwest New Mexico Packer Leakage Test Instructions

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and innually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests thall also be taken at any time that communication is suspected or when equested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage est, the operator shall notify the Division in writing of the exact time the est is to be commenced. Offset operators shall also be so notified.
- 1. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain hut-in until the well-head pressure in each has stabilized, provided lowever, that they need not remain shut-in more than seven days.
- I. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains hut-in. Such test shall be continued for seven days in case of a gas well and 24 hours in the case of an oil well. Note: if, on an initial packer eakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- Following completion of Flow Test No. 1, the well shall again be hut-in, in accordance with Paragraph 3 above.

- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hour tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on -Northwest New Mexico Packer Leakage Test Form Revised 11-16-98, with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).