

Submit 3 Copies To Appropriate District Office

District I

1625 N. French Dr., Hobbs, NM 88240

District II

1301 W. Grand Ave., Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised June 10, 2003

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-025-33667
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator Me-Tex Oil & Gas, Inc.		6. State Oil & Gas Lease No.
3. Address of Operator P.O. Box 2070, Hobbs, NM 88241		7. Lease Name or Unit Agreement Name State H
4. Well Location Unit Letter <u>H</u> : <u>1800</u> feet from the <u>North</u> line and <u>990</u> feet from the <u>East</u> line Section <u>3</u> Township <u>20S</u> Range <u>37E</u> NMPM County <u>Lea</u>		8. Well Number 1
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3571' GR		9. OGRID Number 014462
		10. Pool name or Wildcat Northwest Skaggs Drinkard

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☒ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1. Kill well with 20 bbls. brine water, release pkr. and P.O.H.
2. Perforate additional drinkard with 4" Select-Fire Gun, 2 JSPF, 180 degree phasing as follows: 6,723', 25', 29', 35', 44', 47', 50', 55', 58', 72', 74', 77', 80', 89', 92', 96', 6800', 01', 06', and 13' (total 40 holes).
3. Set pkr. @ 6,710'.
4. Acidized perms. w/3,000 gals. 15% Ne-Fe anti-sludge Hcl acid w/ball sealers.
5. Flowed for clean-up.
6. Release Pkr. & P.O.H., R.I.H. w/ M.A. -6,828'; 3' Perf sub -6,817', S.N. -6,816', 10 jnt. 2-3/8" tbg., 5-1/2" X 2-3/8" T.A. -6,498' & 213 jts. 2-3/8" tbg., 1-6' & 1-4' 2-3/8" sub. Set T.A. with 16 pts. Tension, flange well head, rig to run rods. 6' gas anchor, 2' x 1-1/2" x 16' Pump, 182- 3/4" rod; 88 - 7/8" rods, 4', & 8' - 7/8" subs, 26' - 1-1/4" polish rods w/10' - 1-1/2" polish rod liner, seat pump.
7. Return to production.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tonia Harper TITLE Production Clerk DATE Oct. 10, 2004

Type or print name Tonia Harper E-mail address: tharper@zianet.com Telephone No. 505-397-7750

(This space for State use)

APPROVED BY Paul B. Harper TITLE PETROLEUM ENGINEER DATE NOV 02 2004
Conditions of approval, if any: