

Original

Submit 3 Copies To Appropriate District Office

District I

1625 N. French Dr., Hobbs, NM 88240

District II

1301 W. Grand Ave., Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103

March 4, 2004

WELL API NO. 30-025-02212	
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>	
6. State Oil & Gas Lease No. B-1576	
7. Lease Name or Unit Agreement Name West Vacuum Unit	
8. Well Number 10	
9. OGRID Number	
10. Pool name or Wildcat Vacuum Grayburg San Andres	
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>	
2. Name of Operator Chevron USA Inc	
3. Address of Operator 15 Smith Rd, Midland, TX 79705	
4. Well Location Unit Letter <u>D</u> : <u>660</u> feet from the <u>North</u> line and <u>660</u> feet from the <u>West</u> line Section <u>34</u> Township <u>17-S</u> Range <u>34-E</u> NMPM <u>Lea</u> County	
11. Elevation (Show whether DR, RKB, RT, GR, etc.)	

Pit or Below-grade Tank Application (For pit or below-grade tank closures, a form C-144 must be attached)

Pit Location: UL D Sect 34 Twp 17S Rng 34E Pit type Steel Depth to Groundwater 87 Distance from nearest fresh water well Over 1000'
Distance from nearest surface water 660 feet from the North line and 660 feet from the West line (Steel Tank)

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1. Notify OCD 24 hrs prior to MI and RU.
2. RIH Tag TOC on CIBP at +4140, spot 25sx, plug from 4140-3900 (San Andres).
3. Displace hole w/MLF, 9.5# Brine w/20# gel P/BBL. 12.5
4. Spot 25sx, plug from 2800-2500 (Yates, B-Salt).
5. Spot 25sx, plug from 1700-1400 (8 5/8 Shoe, T-Salt) WOC Tag.
6. Perf 4 holes at 300, sqz 75sx, plug from 300-Surf, 4 1/2 x 8 5/8 csqs (Surf).
7. Install dry hole marker.

THE OIL CONSERVATION DIVISION MUST
BE NOTIFIED 24 HOURS PRIOR TO THE
CLOSING OF PLUGGING OPERATIONS

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE Jimmy Bagley TITLE Consultant DATE 11-1-04

Type or print name Jimmy Bagley E-mail address: _____ Telephone No. 432-561-8600


(This space for State use)

APPROVED BY Larry W. Wink TITLE OCD FIELD REPRESENTATIVE II/STAFF MANAGER DATE _____

Conditions of approval, if any: _____

NOV 08 2004

PLUGGING & ABANDONMENT WORKSHEET (2 STRING CSNG)
OPERATOR CHEVRON USA INC.
LEASENAME WEST VACUUM UNIT

SECT 34 **TWN** 17-S **RNG** 34-E
FROM 660 **N/S L** 660 **E/W L**
TD: 4750 **FORMATION @ TD** S. ANDRES
PBTD: **FORMATION @ PBTD**

8 5/8
@ 1594
TOC SURF

4 1/2
@ 4749
TOC 556

TD 4750

	SIZE	SET @	TOC	TOC DETERMINED BY
SURFACE	8 5/8	1594	SURF	CIRC
INTMED 1				
INTMED 2				
PROD	4 1/2	4749	556	T.S.
	SIZE	TOP	BOT	TOC DETERMINED BY
LINER 1				
LINER 2				
	CUT & PULL @		TOP - BOTTOM	
INTMED 1			PERFS	4679 - 4718
INTMED 2			OPENHOLE	-
PROD				

REQUIRED PLUGS DISTRICT I

RUTLER (ANY)	
YATES	
QUEEN	
GRAYBURG	
MAN ANDRES	
CAPTAN DEEF	
DELAWARE	
BELL CANYON	
CHEERY CANYON	
BERRY CANYON	
BONE SPRING	
CLARETTA	
ELDERNEY	
TUNE	
OLDHEAD	
ABO	
WC	
PRIN	
STRAWN	
ATOKA	
MOSSOW	
MES	
DEVORAN	

PLUG	TYPE	BACKS	DEPTH
PLUG	PLUG	CSMT	
EXAMPLES			
PLUG #1	OH	35 SXS	6400'
PLUG #2	SHOE	50 SXS	3350'-5450'
PLUG #3	CIRP/35'		4800'
PLUG #4	CIRP	25 SXS	4800'
PLUG #5	STUB	50 SXS	3600'-3700'
PLUG #6	RETNR SQZ	200 SXS	400'
PLUG #7	SURF	10 SXS	0-10'
PLUG #1	S. ANDRES	25	4140
PLUG #2	YATES	25	2800
PLUG #3	8 5/8 S	25	1700
PLUG #4	SURF	75	300
PLUG #5			
PLUG #6			
PLUG #7			
PLUG #8			
PLUG #9			
PLUG #10			
PLUG #11			
PLUG #12			
PLUG #13			
PLUG #14			
PLUG #15			
PLUG #16			
PLUG #17			
PLUG #18			
PLUG #19			
PLUG #20			