		New Mexico ()	il Conserv	ation	Division, D	istrict I		
		. <b>1</b>	1625 N. Fre	ench ]	Drive			
	Form 3160-5 HDUTED OT ATTEC							
	(April 2004) (April 2004) DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT SUNDRY NOTICES AND REPORTS ON WELLS					FORM APPROVED OM B No. 1004-0137 Expires: March 31, 2007 5. Lease Serial No. 029405A		
	Do not use this form for proposals to drill or to re-onter an						n, Allottee or Tribe Name	
	abandoned well. Use Form 3160-3 (APD) for such proposals.						a relocate of the reame	
	SUBMIT IN TRIPLICATE- Other instructions on reverse side.					7. If Unit c	r CA/Agreement, Name and/or	
	Oil Well     Gas Well     Other      Name of Operator     ConocoPhillips Company ATTN: Celeste Dale					8. Well Name and No.		
	ConocoPhil	lips Company ATTN: Cele	ste Dale			<u>i</u>	MCA Unit #51 9. API Well No.	
	3a Address 3b. Phone No. (include area code)					30-025		
	4001 Fembrook, Odessa, Texas 79762     432-368-1244       4. Location of Well (Footage, Sec., T., R., M., or Survey Description)				<ol> <li>Field and Pool, or Exploratory Area Maljamar; Grayburg-San Andres</li> <li>County or Parish, State</li> </ol>			
	Unit Letter "E", 660' FWL & 1980' FNL, Section 20, T-17-S, R-32-E							
	2, 000 1 02 @ 1900 FNL, Section 20, 1-17-5, R-32-E						Lea, New Mexico	
	12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, R					LEPORT, OR OTHER DATA		
	TYPE OF SUBMISSION			ТҮР	E OF ACTION			
	Notice of Intent	Acidize	Deepen		Production (S	tart/Resume)	Water Shut-Off	
		Alter Casing	Fracture Tre		Reclamation	,	Well Integrity	
	Subsequent Report	Casing Repair	New Constr		Recomplete	÷ .	Other	
	Final Abandonment Notice	Convert to Injection	Plug and Ab	andon	Water Disposa			
	Attach the Bond under which the following completion of the inv	he work will be performed or pro volved operations. If the operational Abandonment Notices shall he	vide the Bond No.	on file wi	nated starting date of is s and measured and to th BLM/BIA. Requi- tion or recompletion ents, including restar-	ue vertical deptite	s of all pertinent markers and zo ports shall be filed within 30 da a Form 3160 A shall be filed of completed, and the operator ha	
	Attach the Bond under which the following completion of the invitesting has been completed. Find determined that the site is ready SEE ATTACHED WELL! 09/16/04 thru 09/20/04 Notified BLM & OCD. M. 3,574'. Circulated hole w/ 60 sx C cmt 1.640 – 1.540'	he work will be performed or pro- volved operations. If the operation nal Abandonment Notices shall be of final inspection.) BORE DIAGRAM IRU Triple N rig #25 and pla mud, pumped 25 sx C cmt 3 WOC and targend art of the	ugging equipment 574 - 3,274'. Per	t. NU Burforated	nated starting date of is s and measured and to th BLM/BIA. Requi- ction or recompletion ents, including restar- control of the start of the control of the start of the start of the start of the start of the control of the start of the start of the start of the start of the control of the start of the	ue verticardeptifi eassubsequent re a new interval nation, have been <i>NOV</i> <i>Hobb</i> <i>OCD</i> WH w/ workst W/ w/ packer,	i of all pertinent markers and zc ports shall be filed within 30 dz a Form 3160 4 shall be filed o completed, and the operator ha 250 251 750 251 ring and tagged CICR @ established rate, and soue	
	Attach the Bond under which the following completion of the investigation for the investigation of the investigati	he work will be performed or pro- volved operations. If the operation nal Abandonment Notices shall be of final inspection.) BORE DIAGRAM IRU Triple N rig #25 and plu- mud, pumped 25 sx C cmt 3 WOC and tagged cmt @ 1, Pagged cmt @ 1,090°. Perfor- rated casing @ 400°, circulated	ugging equipment 574 – 3,274'. Per 480'. Perforated rated casing @ 84 ed 95 sx C cmt 40	t. NU B requirem t. NU B rforated casing ( 5'. RIH 0' to sur	op & enviro-vat casing @ 1,640'. P1,250', RIH w/ J	ue verticardeptifi eassubsequent re a new interval nation, have been <i>NOV</i> <i>Hobb</i> <i>OCD</i> WH w/ workst W/ w/ packer,	i of all pertinent markers and zo ports shall be filed within 30 da a Form 3160 4 shall be filed of completed, and the operator ha VED Complete and the operator ha vestablished rate, and source	
	Attach the Bond under which the following completion of the investigation for the investigation of the investigati	he work will be performed or pro- volved operations. If the operation nal Abandonment Notices shall be of final inspection.) BORE DIAGRAM IRU Triple N rig #25 and plu mud, pumped 25 sx C cmt 3 WOC and tagged cmt @ 1, Tagged cmt @ 1 000? Perfo	ugging equipment 574 – 3,274'. Per 480'. Perforated rated casing @ 84 ed 95 sx C cmt 40	t. NU B requirem t. NU B rforated casing ( 5'. RIH 0' to sur	op & enviro-vat casing @ 1,640'. P1,250', RIH w/ J	ue verticardeptifi eassubsequent re a new interval nation, have been <i>NOV</i> <i>Hobb</i> <i>OCD</i> WH w/ workst W/ w/ packer,	i of all pertinent markers and zo ports shall be filed within 30 da a Form 3160 4 shall be filed of completed, and the operator ha VED Completed and the operator has very shall be filed of completed and the operator has very shall be filed of completed and the operator has very shall be filed of completed and the operator has very shall be filed of completed and the operator has very shall be filed of completed and the operator has very shall be filed of completed and the operator has very shall be filed of completed and the operator has very shall be filed of completed and the ope	
	Attach the Bond under which the following completion of the investigation for the investigation of the investigati	he work will be performed or pro- volved operations. If the operation nal Abandonment Notices shall be of final inspection.) BORE DIAGRAM IRU Triple N rig #25 and plu- mud, pumped 25 sx C cmt 3 WOC and tagged cmt @ 1, Pagged cmt @ 1,090°. Perfor- rated casing @ 400°, circulated	ugging equipment 574 – 3,274'. Per 480'. Perforated rated casing @ 84 ed 95 sx C cmt 40	t. NU B requirem t. NU B rforated casing ( 5'. RIH 0' to sur	op & enviro-vat casing @ 1,640'. P1,250', RIH w/ J	ue verticardeptifi ea subsequent real hation, have been MOV Hobb. OCD RHH w/ workst Chew/ packer, wacker and squ ueezed 55 sx C	i of all pertinent markers and zo ports shall be filed within 30 da a Form 3160 4 shall be filed of completed, and the operator ha VED Complete and the operator ha vestablished rate, and source	
=	Attach the Bond under which the following completion of the investige has been completed. Find determined that the site is ready SEE ATTACHED WELL 09/16/04 thru 09/20/04 Notified BLM & OCD. M 3,574'. Circulated hole w/ 60 sx C cmt 1,640 – 1,540'. 1,150'. SI over weekend. 7 tagged cmt @ 690'. Perfor Cut off wellhead and anchor	he work will be performed or pro- volved operations. If the operation nal Abandonment Notices shall by for final inspection.) BORE DIAGRAM IRU Triple N rig #25 and plu mud, pumped 25 sx C cmt 3 WOC and tagged cmt @ 1, Tagged cmt @ 1,000'. Perfor 'ated casing @ 400', circulated ors, installed dry hole marke	ugging equipment 574 – 3,274'. Per 480'. Perforated rated casing @ 84 ed 95 sx C cmt 40	t. NU B requirem t. NU B rforated casing ( 5'. RIH 0' to sur	op & enviro-vat casing @ 1,640'. P1,250', RIH w/ J	ue verticardeptifi ea subsequent real hation, have been MOV Hobb. OCD RIH w/ workst Chew/ packer, wacker and squ ueezed 55 sx C	s of all pertinent markers and zo ports shall be filed within 30 da a Form 3160 shall be filed or completed, and the operator ha VED ring and tagged CICR @ established rate, and squee eezed 55 sx C cmt 1,250 - cmt 845 - 695'. WOC and	
=	Attach the Bond under which the following completion of the investiging has been completed. Find determined that the site is ready SEE ATTACHED WELL! 09/16/04 thru 09/20/04 Notified BLM & OCD. M 3,574'. Circulated hole w/ 60 sx C cmt 1,640 – 1,540'. 1,150'. SI over weekend. 7 tagged cmt @ 690'. Perfor Cut off wellhead and ancho	he work will be performed or pro- volved operations. If the operation nal Abandonment Notices shall be of final inspection.) BORE DIAGRAM IRU Triple N rig #25 and plu mud, pumped 25 sx C cmt 3 WOC and tagged cmt @ 1, Tagged cmt @ 1,090°. Perfor rated casing @ 400°, circulated ors, installed dry hole marke	ugging equipment 574 – 3,274'. Per 480'. Perforated rated casing @ 84 ed 95 sx C cmt 40	t. NU B requirem t. NU B rforated casing ( 5'. RIH 0' to sur	op & enviro-vat casing @ 1,640'. P1,250', RIH w/ J	Le vericardeptifi ea subsequent real hation, have been MOV hobb OCD RUH w/ workst Chew/ packer, wacker and squ ueezed 55 sx C	s of all pertinent markers and zo ports shall be filed within 30 da a Form 3160 4 shall be filed or completed, and the operator ha VED ring and tagged CICR @ established rate, and squee eezed 55 sx C cmt 1,250 - cmt 845 - 695'. WOC and	
=	Attach the Bond under which the following completion of the investigal has been completed. Find determined that the site is ready SEE ATTACHED WELL 09/16/04 thru 09/20/04 Notified BLM & OCD. M. 3,574'. Circulated hole w/ 60 sx C cmt 1,640 – 1,540'. 1,150'. SI over weekend. 7 tagged cmt @ 690'. Perfor Cut off wellhead and ancho	he work will be performed or pro- volved operations. If the operation nal Abandonment Notices shall be of final inspection.) BORE DIAGRAM IRU Triple N rig #25 and plu mud, pumped 25 sx C cmt 3 WOC and tagged cmt @ 1, Tagged cmt @ 1,090°. Perfor rated casing @ 400°, circulated ors, installed dry hole marke	ugging equipment in results in a multip of filed only after all ugging equipment (574 – 3,274'. Per 480'. Perforated rated casing @ 84 ed 95 sx C cmt 40 er. Leveled location	t. NU B requirem t. NU B rforated casing ( 5'. RIH 0' to sur	ated starting date of is and measured and to th BLM/BIA. Requi- ction or recompletion ents, including rotar of the start of the start of the start of the start of the start of the start of the start of the start of the start of the start of the start of the start of the start of the start of the start of the start of the start of the start o	ue verticar deputie eassubsequent re a a new interval nation, have been <i>MUV</i> <i>Hobb</i> <i>OCO</i> RIH w/ workst RIH w/ workst RIH w/ workst racker and squ ueezed 55 sx C	ports shall be filed within 30 da a Form 3160,4 shall be filed or completed, and the operator ha VED stablished rate, and squee eezed 55 sx C cmt 1,250 - cmt 845 - 695'. WOC and	
=	Attach the Bond under which the following completion of the investiging has been completed. Find determined that the site is ready SEE ATTACHED WELL! 09/16/04 thru 09/20/04 Notified BLM & OCD. M 3,574'. Circulated hole w/ 60 sx C cmt 1,640 – 1,540'. 1,150'. SI over weekend. 7 tagged cmt @ 690'. Perfor Cut off wellhead and ancho	he work will be performed or pro- volved operations. If the operation nal Abandonment Notices shall be of final inspection.) BORE DIAGRAM IRU Triple N rig #25 and plu mud, pumped 25 sx C cmt 3 WOC and tagged cmt @ 1, Tagged cmt @ 1,090°. Perfor rated casing @ 400°, circulated ors, installed dry hole marke	ugging equipment on results in a multip of filed only after all ugging equipment (574 - 3,274'. Per 480'. Perforated rated casing @ 84 ed 95 sx C cmt 40 er. Leveled location	t. NU B requirem t. NU B rforated casing ( 5'. RIH 0' to sur	ated starting date of is and measured and to th BLM/BIA. Requi- ction or recompletion ents, including rotar of the start of the start of the start of the start of the start of the start of the start of the start o	ue verticar deputie ea subsequent re a a new interval nation, have been <i>MUV</i> <i>Hobb</i> <i>OCD</i> RIH w/ workst RIH w/ workst RIH w/ workst RIH w/ packer, nacker and squ ueezed 55 sx C	of all pertinent markers and zo ports shall be filed within 30 da a Form 3160 shall be filed of completed, and the operator ha VED 53 ring and tagged CICR @ established rate, and squee eezed 55 sx C cmt 1,250 - cmt 845 - 695'. WOC and OPPROVED	
=	Attach the Bond under which the following completion of the investiging has been completed. Find determined that the site is ready SEE ATTACHED WELLI 09/16/04 thru 09/20/04 Notified BLM & OCD. M 3,574'. Circulated hole w/ 60 sx C cmt 1,640 – 1,540'. 1,150'. SI over weekend. 7 tagged cmt @ 690'. Perfor Cut off wellhead and ancho 14. I hereby certify that the foreg Name ( <i>Printed/Typed</i> ) James F. Newman	he work will be performed or pro- volved operations. If the operation nal Abandonment Notices shall be of final inspection.) BORE DIAGRAM IRU Triple N rig #25 and plu mud, pumped 25 sx C cmt 3 WOC and tagged cmt @ 1, Tagged cmt @ 1,090°. Perfor rated casing @ 400°, circulated ors, installed dry hole marke	ugging equipment pe filed only after all ugging equipment 574 – 3,274'. Per 480'. Perforated rated casing @ 84 ed 95 sx C cmt 40 er. Leveled location Ti	t. NU Ba requirem t. NU Ba rforated casing ( 15'. RIH 0' to sur on.	ineer, Triple N Ser	Le verticardeputs a a new interval hation, have been MOV h Hobb. OCD RIH w/ workst Wirew/ packer. wacker and squ ueezed 55 sx C	of all pertinent markers and zc ports shall be filed within 30 da a Form 3160, shall be filed of completed, and the operator ha VED stablished rate, and squee established rate, and squee established rate, and squee ezed 55 sx C cmt 1,250 - cmt 845 - 695'. WOC and OCT 2 8 2004	
-	Attach the Bond under which the following completion of the investiging has been completed. Find determined that the site is ready SEE ATTACHED WELLI 09/16/04 thru 09/20/04 Notified BLM & OCD. M. 3,574°. Circulated hole w/ 60 sx C cmt 1,640 – 1,540°. 1,150°. SI over weekend. 7 tagged cmt @ 690°. Perfor Cut off wellhead and ancho 14. I hereby certify that the foreg Name ( <i>Printed/Typed</i> ) James F. Newman Signature	he work will be performed or provolved operations. If the operational Abandonment Notices shall be for final inspection.) BORE DIAGRAM IRU Triple N rig #25 and plumud, pumped 25 sx C cmt 3 WOC and tagged cmt @ 1, Tagged cmt @ 1,090°. Perforated casing @ 400°, circulated ors, installed dry hole marked ors, installed dry hole marked to rect a, P.E.	ugging equipment pe filed only after all ugging equipment 574 – 3,274'. Per 480'. Perforated rated casing @ 84 ed 95 sx C cmt 40 er. Leveled location Ti	t. NU Berrequirem t. Statut, S. NIE t. Statut, S. St	and measured and to s and measured and to th BLM/BIA. Requi- ction or recompletion ents, including to N OP & enviro-vate casing @ 1,640? ) 1,250'. RIH w/ p 1,250'. RIH w/ p face. RDMO.	Le vericardeptifi ea subsequent re a a new interval hation, have been MOV h Hobb. OCD RUH w/ workst UNE w/ packer, packer and squ ucces, Inc. V02/2004 ETR USE	of all pertinent markers and zo ports shall be filed within 30 da a Form 3160, shall be filed or completed, and the operator ha VED completed, and the operator has vED completed, and th	
	Attach the Bond under which the following completion of the investiging has been completed. Find determined that the site is ready SEE ATTACHED WELL 09/16/04 thru 09/20/04 Notified BLM & OCD. M. 3,574'. Circulated hole w/ 60 sx C cmt 1,640 – 1,540'. 1,150'. SI over weekend. 7 tagged cmt @ 690'. Perfor Cut off wellhead and ancho I4. I hereby certify that the foreg Name (Printed/Typed) James F. Newman Signature Approved by Conditions of approval, if any, are att	he work will be performed or provolved operations. If the operational Abandonment Notices shall be of final inspection.) BORE DIAGRAM IRU Triple N rig #25 and plumud, pumped 25 sx C cmt 3 WOC and tagged cmt @ 1, Tagged cmt @ 1,090°. Performated casing @ 400°, circulated correct and correct and the provided of the second secon	ugging equipment or results in a multip of filed only after all ugging equipment (574 - 3,274'). Per 480'. Perforated rated casing @ 84 ed 95 sx C cmt 40 or. Leveled location FEDERAL O	t. NU Bar requirem t. NU Bar rforated casing ( 55'. RIH 0' to sur on. tle Engi ate <b>R STA</b>	and measured and to s and measured and to th BLM/BIA. Requi- ction or recompletion ents, including to N OP & enviro-vate casing @ 1,640? ) 1,250'. RIH w/ p 1,250'. RIH w/ p face. RDMO.	Le verticardeputs a a new interval hation, have been MOV h Hobb. OCD RIH w/ workst Wirew/ packer. wacker and squ ueezed 55 sx C	of all pertinent markers and zo ports shall be filed within 30 da a Form 3160, shall be filed or completed, and the operator ha VED 53 ring and tagged CICR @ established rate, and squee ezed 55 sx C cmt 1,250 – cmt 845 – 695'. WOC and OPROVED OCT 28 2004 ARY GOURLEY OLEUM ENGINEER	
	Attach the Bond under which the following completion of the investiging has been completed. Find determined that the site is ready SEE ATTACHED WELL 09/16/04 thru 09/20/04 Notified BLM & OCD. M. 3,574'. Circulated hole w/ 60 sx C cmt 1,640 – 1,540'. 1,150'. SI over weekend. 7 tagged cmt @ 690'. Perfor Cut off wellhead and ancho I4. I hereby certify that the foreg Name ( <i>Printed/Typed</i> ) James F. Newman Signature Approved by Conditions of approval, if any, are att certify that the applicant holds legal o	he work will be performed or provolved operations. If the operational Abandonment Notices shall be of final inspection.) BORE DIAGRAM IRU Triple N rig #25 and plumud, pumped 25 sx C cmt 3 WOC and tagged cmt @ 1, Tagged cmt @ 1,090°. Performated casing @ 400°, circulated correct and correct and the provided of the second secon	ugging equipment or results in a multip of filed only after all ugging equipment (574 - 3,274'). Per 480'. Perforated rated casing @ 84 ed 95 sx C cmt 40 or. Leveled location FEDERAL O	t. NU Bar requirem t. NU Bar rforated casing ( 55'. RIH 0' to sur on. tle Engi ate <b>R STA</b>	ineer, Triple N Ser	Le vericardeptifi ea subsequent re a a new interval hation, have been MOV h Hobb. OCD RUH w/ workst UNE w/ packer, packer and squ ucces, Inc. V02/2004 ETR USE	of all pertinent markers and zo ports shall be filed within 30 da a Form 3160, shall be filed or completed, and the operator ha VED 53 ring and tagged CICR @ established rate, and squee ezed 55 sx C cmt 1,250 – cmt 845 – 695'. WOC and OPROVED OCT 28 2004 ARY GOURLEY OLEUM ENGINEER	
	Attach the Bond under which the following completion of the investiging has been completed. Find determined that the site is ready SEE ATTACHED WELLI 09/16/04 thru 09/20/04 Notified BLM & OCD. M. 3,574'. Circulated hole w/ 60 sx C cmt 1,640 – 1,540'. 1,150'. SI over weekend. 7 tagged cmt @ 690'. Perfor Cut off wellhead and ancho II. I hereby certify that the forege Name (Printed/Typed) James F. Newman Signature Approved by Conditions of approval, if any, are att certify that the applicant holds legal o which would entitle the applicant to c Title 18 USC Section 1001 and Title A	he work will be performed or provolved operations. If the operational Abandonment Notices shall be of final inspection.) BORE DIAGRAM IRU Triple N rig #25 and plumud, pumped 25 sx C cmt 3 WOC and tagged cmt @ 1, Tagged cmt @ 1,090°. Performated casing @ 400°, circulated operations, installed dry hole marked poing is true and correct h, P.E. THIS SPACE FOR I ached. Approval of this notice of requitable title to those rights in onduct operations thereon.	ugging equipment or results in a multip pe filed only after all ugging equipment 574 – 3,274'. Per 480'. Perforated rated casing @ 84 ed 95 sx C cmt 40 er. Leveled location FEDERAL O does not warrant or n the subject lease	t. NU Berforated to sur	and the starting date of is and measured and to the BLM/BIA. Requi- ction or recompletion ents, including to the completion of the enviro-vale completion of	UL verticar deputs a a new interval hation, have been MOV h Hobb. OCD RUH w/ workst UNE w/ packer. packer and squ ueezed 55 sx C A F vices, Inc. V02/2004 ETR Date	of all pertinent markers and zo ports shall be filed within 30 da a Form 3160, shall be filed or completed, and the operator ha VED 53 ring and tagged CICR @ established rate, and squee eezed 55 sx C cmt 1,250 - cmt 845 - 695'. WOC and OPROVED UCT 28 2004 ARY GOURLEY OLEUM ENGINEER	
	Attach the Bond under which the following completion of the invitesting has been completed. Find determined that the site is ready SEE ATTACHED WELL 09/16/04 thru 09/20/04 Notified BLM & OCD. M. 3,574'. Circulated hole w/ 60 sx C cmt 1,640 – 1,540'. 1,150'. SI over weekend. 7 tagged cmt @ 690'. Perfor Cut off wellhead and ancho II4. I hereby certify that the foreg Name ( <i>Printed/Typed</i> ) James F. Newman Signature Approved by Conditions of approval, if any, are att certify that the applicant holds legal o which would entitle the applicant to c Title 18 U.S.C. Section 1001 and Title 4 States any false, fictitious or fraudulen	he work will be performed or provolved operations. If the operational Abandonment Notices shall be of final inspection.) BORE DIAGRAM IRU Triple N rig #25 and plumud, pumped 25 sx C cmt 3 WOC and tagged cmt @ 1, Tagged cmt @ 1,090°. Performated casing @ 400°, circulated operations, installed dry hole marked poing is true and correct h, P.E. THIS SPACE FOR I ached. Approval of this notice of requitable title to those rights in onduct operations thereon.	ugging equipment or results in a multip pe filed only after all ugging equipment 574 – 3,274'. Per 480'. Perforated rated casing @ 84 ed 95 sx C cmt 40 er. Leveled location FEDERAL O does not warrant or n the subject lease	t. NU Berforated to sur	and the starting date of is and measured and to the BLM/BIA. Requi- ction or recompletion ents, including to the completion of the enviro-vale completion of	UL verticar deputs a a new interval hation, have been MOV h Hobb. OCD RUH w/ workst UNE w/ packer. packer and squ ueezed 55 sx C A F vices, Inc. V02/2004 ETR Date	of all pertinent markers and zo ports shall be filed within 30 da a Form 3160, shall be filed or completed, and the operator ha VED 53 ring and tagged CICR @ established rate, and squee eezed 55 sx C cmt 1,250 - cmt 845 - 695'. WOC and OPROVED UCT 28 2004 ARY GOURLEY OLEUM ENGINEER	
	Attach the Bond under which the following completion of the investiging has been completed. Find determined that the site is ready SEE ATTACHED WELLI 09/16/04 thru 09/20/04 Notified BLM & OCD. M. 3,574'. Circulated hole w/ 60 sx C cmt 1,640 – 1,540'. 1,150'. SI over weekend. 7 tagged cmt @ 690'. Perfor Cut off wellhead and ancho II. I hereby certify that the forege Name (Printed/Typed) James F. Newman Signature Approved by Conditions of approval, if any, are att certify that the applicant holds legal o which would entitle the applicant to c Title 18 USC Section 1001 and Title A	he work will be performed or provolved operations. If the operational Abandonment Notices shall be of final inspection.) BORE DIAGRAM IRU Triple N rig #25 and planud, pumped 25 sx C cmt 3 WOC and tagged cmt @ 1,090°. Performant of the second se	ugging equipment or results in a multip pe filed only after all ugging equipment 574 – 3,274'. Per 480'. Perforated rated casing @ 84 ed 95 sx C cmt 40 er. Leveled location FEDERAL O does not warrant or n the subject lease	t. NU Berforated to sur	and the starting date of is and measured and to the BLM/BIA. Requi- ction or recompletion ents, including to the completion of the enviro-vale completion of	UL verticardeptifi a a new interval hation, have been MOV h Hobb. OCD RUH w/ workst UNE w/ packer. packer and squ ueezed 55 sx C A F vices, Inc. V02/2004 ETR Date	a Form 3160, shall be filed within 30 dz a Form 3160, shall be filed of completed, and the operator ha VED established rate, and sque eszed 55 sx C cmt 1,250 - cmt 845 - 695'. WOC and OPPROVED OUCT 28 2004 ARY GOURLEY OLEUM ENGINEER	

Ĵ

PLUGGED WELLBORE SKETCH

ConocoPhillips Company -- Permian Basin Business Unit

Date: September 29, 2004



9/29/2004