

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator

BURLINGTON

RESOURCES OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

1500' FNL, 1600' FWL, Sec. 8 T-31-N, R-9-W, NMPM

2004 OCT 27 PM 1 59

RECEIVED

070 FARMINGTON 17A

Lease Number
NMSF-078438

6. If Indian, All. or
Tribe Name

Unit Agreement Name
San Juan 32-9 Unit

Well Name & Number

San Juan 32-9 Unit #17A

9. API Well No.

30-045-22893

10. Field and Pool

Blanco Mesaverde

County and State

San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

Type of Action

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☒ Casing Repair

☐ Altering Casing

☒ Other -

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut off

☐ Conversion to Injection

13. Describe Proposed or Completed Operations

10/1/04 MIRU. ND WH. NU BOP. TOO H w/2-3/8" tbg. SDON.

10/4/04 TIH w/6-1/4" blade bit, tag @ 3815'. TOO H w/bit. TIH w/RBP, tag @ 3615'. SDON.

10/5/04 TOO H w/RBP. TIH w/mill to 3815'. TOO H w/mill. TIH w/RBP, set @ 3797'. SDON.

10/6/04 (Verbal approval from Steve Mason, BLM, to squeeze). TIH w/7" pkr, set @ 3460'. PT csg, pump in 2-1/2 bpm @ 600 psi. Isolate hole in csg @ 3233-3263' & 1993-2024'. Re-set pkr @ 3045'. Dumped 15 gals sand down tubing. TOO H w/tbg & pkr. SDON.

10/7/04 (Verbal approval from Wayne Townsend, BLM, to squeeze). TIH w/RBP, set @ 3230'. TIH w/pkr, set @ 2117'. PT below 2117' to 3230' @ 1200 psi, good test. Keep pulling up, still testing to 1200 psi @ 2011' to 3230', 1993' up tested OK, tested down from 2024' to 3230' @ 1200 psi, OK. TOO H w/pkr. Re-set RBP @ 2117'. TIH w/pkr to 2050', PT RBP to 1000 psi, OK. TOO H w/pkr. TIH, latch onto RBP & release. SDON.

10/8/04 TOO H w/RBP. TIH w/pkr, set @ 2490'. Load backside w/wtr. TOO H w/pkr. TIH w/RBP, set @ 2478'. TIH w/pkr, set @ 2100'. PT RBP to 500 psi, OK. Rls pkr. Re-set pkr @ 1746'. Pump down tbg, check injection rate again. Dump sand down tbg. SDON.

10/11/04 Sqz csg leak @ 1993-2024' w/404 sxs Type III cmt w/2% KCL (562 cu. ft.). WOC. SDON.

Continued on back

14. I hereby certify that the foregoing is true and correct.

Signed Tammy J. Jans Title Regulatory Specialist Date 10/26/04

ACCEPTED FOR RECORD

NOV 02 2004

(This space for Federal or State Office use)

APPROVED BY

Title

Date

CONDITION OF APPROVAL, if any:

FARMINGTON FIELD OFFICE

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCD

10/12/04 Rls pkr & TOOH. TIH w/bit. Mill out cmt to 2041', shavings of metal @ 2010 to 2041'. PT csg to 400 psi/30 mins, OK. SDON.

10/13/04 TIH to RBP, tag sand. TOOH to 1500'. Start air package, CO sugar water to flow back tank. TIH to 2450'. CO water & sand to flowback tank. TOOH w/bit. TIH, latch onto RBP & rls. TOOH w/RBP. TIH w/pkr, set @ 3045'. PT csg, pump 1.4 bpm @ 1000#, dropped to 500#. Load csg above pkr. PT to 400#, holding steady. SDON.

10/14/04 Sqz csg leak @ 3233-3263' w/404 sxs Type III cmt w/2% KCL (562 cu. ft.). SDON.

10/15/04 Rls pkr & TOOH w/pkr. TIH w/bit, tag @ 3102'. Drill out cmt @ 3102-3260'. PT backside to 450 psi/30 mins, OK. SDON.

10/18/04 TIH, tag RBP @ 3786'. TOOH w/bit. TIH, latch onto RBP & release. TOOH w/RBP. SDON.

10/19/04 TIH w/mill, tag up @ 5973'. CO from 5973' to 6108'. SDON.

10/20/04 Tag @ 6093'. CO to 6211'. TOOH w/mill. TIH w/tbg, pump 500 gals 28% HCL acid. SDON.

10/21/04 TIH, tag up @ 6133'. Circ & CO to PBTD @ 6211'. SDON.

10/22/04 Land-199-jts 2-3/8" 4.7# J-55 tbg, set @ 6161'. SN @ 6128'. ND BOR. NU WH. RD. Rig released.