SEP-25-01 TUE 01:45 PM FAX: PAGE Sep-25-2001 09:31pm From-CONOCO MIDLAND 9156885780 +Submit 3 Conies T-379 P.001/001 State of New Mexico F-785 to Appropriate Energy, Minerals and Natural Resources Department District Office Form C 103 DISTRICT | P.O. Box 1980, Hobbs, NM 58240 Revised 1-1-89 OIL CONSERVATION DIVISION WELL API NO. P.O. Box 2088 P.O. Drawer DD, Artesia. NM 88210 Santa Fe, New Mexico 87504-2088 30-025-35480 DISTRICT III 1000 Rig Brazos Rd., Aziec, NM 87410 5. Indicate Type of Lense STATE FEE 6. State Oil & Gas Lease No. SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT 7. Lease Name or Unit Agreement Name (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: óil Well 2. Name of Operator State F1 Conoco inc. 8, Well No. 3. Address of Operator 10 Desta Dr. Sta 100W, Midland, Tx 79705-4500 9. Pool name or Wildcat 4. Well Location South Cass Strawn Unit Letter 990 Feet From The Nonh Line and 990 Feet From The West Line Section Township 215 Range 36E NMPM 10. Elevation (Show whether DF, RKB, RT, GR, crc.) County Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT PULL OR ALTER CASING CASING TEST AND CEMENT JOB OTHER: OTHER 12. Describe Proposed of Completed Operations (Clearly state all parlinent details, and give pertinent dates, including earmated date of starting any proposed Conoco proposes to P&A this wellbore as follows: 1. TIH open end with drill pipe. 2. Circulate mud(10 ppg brine w/ 25#/bbl salt gel) to surface. 3. Spot a cement plug (34 sxs Class C neat) 1/8,020' to 8,120' 4. Spot a cement plug (34 sxs Class C neat) f/6,629 to 6,729 5. Spot a cement plug (34 sxs Class C neat) f/5,164' to 5,264' 6. Spot a cement plug (34 sxs Class C neat) f/3,428' to 3,528' 7. Spot a cement plug (34 sxs Class C neat) f/2,456' to 2,556' 8. Spot a coment plug (34 sxs Class C neat + 2% bwoc CaCL) f/1,470' to 1,570' tag this plug. 9. Spot a cement plug (25 sxs Class C neat) 1/250' to 350'. 9 Spot a cement plug (10 sxs Class C neat) @ surface. 12. I hereby cerufy that the information above is true and complete to the best of my knowledge and belief. Sr. Drlg Eng. 9/25/01 TYPE OR PRINT NAME YOUR H. Cho TELEPHONE NO. 915-686-6524 (this space for State Use)

> URIGINAL SIGNED BY GARY W. WINK

CEIFHANDEDDESENITATIVE ILISTAFF MANAGER

NOV 3 0 2004

CONITIONS OF APPROVA