Submit 3 Copies To Appropriate District Office District I	State of New Mexico Energy, Minerals and Natural Resources			Form C-103 Revised March 25, 1999
1625 N. French Dr., Hobbs, NM 87240 District II	•••		WELL API NO.	30-025-36113
811 South First Artesia, NM 87210 District III			5. Indicate Type o	
1000 Rio Brazos Rd., Aztec, NM 87410	2040 South Pachec Santa Fe, NM 8750		STATE X	
District IV 2040 South Pacheco, Santa Fe, NM 87505	Santa Fe, Nivi 8/30	13	6. State Oil & Ga	as Lease No.
SUNDRY NOTICES AND REPORTS ON WELLS  (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)  1. Type of Well:  Oil Well  Gas Well  OtherDry			7. Lease Name or Hole In The Wall	Unit Agreement Name
2. Name of Operator Concho Oil & Gas Crop.			8. Well No. 1	
3. Address of Operator 110 W. Louisiana, Ste 410 Midland, Texas 79701			9. Pool name or Wildcat South Saunders; Permo Penn	
4. Well Location				
Unit Letter H : 2	feet from the North	line and <u>800</u>	feet fron	n the East line
Section 33	Township 15S R	ange 33E	NMPM	County Lea
	10. Elevation (Show whether DR 4172' GR	, RKB, RT, GR, etc.)		
11. Check Ap	propriate Box to Indicate Na	ature of Notice, I	Report or Other D	ata
NOTICE OF INT	TENTION TO: PLUG AND ABANDON	SUB REMEDIAL WOR	SEQUENT REF	PORT OF: ALTERING CASING [
TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DR	ILLING OPNS. X	PLUG AND X
PULL OR ALTER CASING	MULTIPLE COMPLETION	CASING TEST AI	ND X	ABANDONMENT
OTHER:		OTHER:		
12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and proposed work). SEE RULE 1103. For Multiple Completions: Attach diagram of proposed completion or recompletion.  2-11-03 Spud 17 1/2" hole 2-12-03 Ran 9 jts. 13 3/8" 48# H-40 ST&C csg set @ 430'. Cmt'd w/475 sx Cl C + 2% CaCl2 & 1/4# CF. Circ 30 sx to surface. WOC 22 hours.  2-23-03 Ran 103 jts. 8 5/8" 32# NS-80 ST&C 8rd Csg set @ 4410'. Cmt'd w/1500 sx 50/50 Poz C + 5% salt, 1/4 CF + 3# LCM-1 + 10% gel & tailed in w/200 sx Cl C + 1% CaCl2. Hole size 11". WOC 24 hrs.  3-28-03 Ran 99 jts. 7" FJ 26# P-110 ST&L csg. set @ 4380' in 11" hole. Cmt'd w/300 sx 50/50/ Poz C + 2% gel, 5% salt, 8/10% FL-62. WOC 19 hrs.  4-12-03 Ran Platform Express Log.  4-13-03 Spotted cmt plugs, as follows: 25 sx H @ 10,830'; 50 sx H @ 9570'; 50 sx H @ 7959'; 50 sx H @ 5905' 25 st C @ 44.54-13-03 Spotted cmt plugs, as follows: 25 sx C @ 1674'; 50 sx C @ 473' - Tag @ 200'; 25 sx C @ 63' Circ. to surface. Set dry hole marker. Well P&A  Approved as to Plugging of the Well Bore.  Liability under bond is retained until  Surface restoration is completed.				
I hereby certify that the information above is true and complete to the best of my knowledge and belief.				
SIGNATURE SNACO	( / / / .	Regulatory Analyst	-	DATE 05/08/2003
Type or print name Brenda Coffman	1		Telep	hone No. (915)683-7443
(This space for State use)	> ,			
APPROVED BY  Conditions of approval, if any:	TITLE	PETROLEUM	ENGINEER	MAY <sub>TE</sub> 2 9 2003