

DISTRICT I

P.O. Box 1980, Hobbs, NM 88240

DISTRICT II

P.O. Box Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088

Santa Fe, New Mexico 87504-2088

Amended

WELL API NO.	30-025-36510
5. Indicate Type of Lease	STATE ☒ FEE ☐
6. State Oil / Gas Lease	
7. Lease Name or Unit Agreement Name	BELL STATE "16" COM
8. Well No.	1
9. Pool Name or Wildcat	WILDCAT; STRAWN

WELL COMPLETION OR RECOMPLETION REPORT AND LOG							
1a. Type of Well: OIL WELL ☐ GAS WELL ☒ DRY ☐ OTHER ☐							
b. Type of Completion: NEW WELL ☐ WORKOVER ☐ DEEPEN ☐ PLUG BACK ☐ DIFF RES. ☐ OTHER RECOMPLETION ☐							
2. Name of Operator CHEVRON USA INC							
3. Address of Operator 15 SMITH ROAD, MIDLAND, TX 79705							
4. Well Location Unit Letter <u>N</u> : <u>660'</u> Feet From The <u>SOUTH</u> Line and <u>1980'</u> Feet From The <u>WEST</u> Line Section <u>16</u> Township <u>21-S</u> Range <u>35-E</u> NMPM <u>LEA</u> COUNTY							
10. Date Spudded 7/19/2004	11. Date T.D. Reached 3/22/2004	12. Date Compl. (Ready to Prod.) 7/28/2004	13. Elevations (DF & RKB, RT, GR, etc.) 3639'	14. Elev. Csghead			
15. Total Depth 12677'	16. Plug Back T.D. 12165'	17. If Mult. Compl. How Many Zones?	18. Intervals Drilled By	Rotary Tools	Cable Tools		
19. Producing Interval(s), of this completion - Top, Bottom, Name 11,274'-11,459' STRAWN					20. Was Directional Survey Made NO		
21. Type Electric and Other Logs Run N/A					22. Was Well Cored NO		
23. <i>[Signature]</i> CASING RECORD (Report all Strings set in well)							
CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENT RECORD	AMOUNT PULLED		
13 3/8"	54.5#	1360'	17 1/2"	1570 SX	593 SX		
9 5/8"	40#	5460'	12 1/4"	1985 SX	NO CIRC		
7"	26#	10,850'	8 3/4"	1680 SX	321 SX		
24. LINER RECORD							
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN			
4 1/2"	10,458	12,677'	325 SX				
25. TUBING RECORD							
SIZE	DEPTH SET	PACKER SET					
2 7/8"	11,145'	11,130'					
26. Perforation record (interval, size, and number) 11274'-11459'							
27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.							
DEPTH INTERVAL			AMOUNT AND KIND MATERIAL USED				
11,274-11,459'			ACIDIZE W/6500 GALS 20% ANTI-SLUDGE				
28. PRODUCTION							
Date First Production 8/21/2004	Production Method (Flowing, gas lift, pumping - size and type pump) FLOWING				Well Status (Prod. or Shut-in) PROD		
Date of Test 8-22-04	Hours tested 24 HRS	Choke Size	Prod'n For Test Period	Oil - Bbl. 48	Gas - MCF 1529	Water - Bbl. 0	Gas - Oil Ratio 31862
Flow Tubing Press.	Casing Pressure	Calculated 24-Hour Rate	Oil - Bbl.	Gas - MCF	Water - Bbl.	Oil Gravity - API (Corr.)	
29. Disposition of Gas (Sold, used for fuel, vented, etc.)						Test Witnessed By	
30. List Attachments							
31. I hereby certify that the information on both sides of this form is true and complete to the best of my knowledge and belief.							
SIGNATURE <i>Denise Leake</i>				TITLE		DATE 11/8/2004	
TYPE OR PRINT NAME Denise Leake				Telephone No.		915-687-7375	

[Signature]

INSTRUCTIONS

Yell State 16" #1

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true verticle depths shall be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy	T. Canyon
T. Salt	T. Strawn 11258
B. Salt	T. Atoka 11545
T. Yates	T. <i>McCrack</i> 12202
T. 7 Rivers	T. Devonian
T. Queen	T. Silurian
T. Grayburg	T. Montoya
T. San Andres	T. Simpson
T. Glorieta	T. McKee
T. Paddock	T. Ellenburger
T. Blinebry	T. Gr. Wash
T. Tubb	T. Delaware 5581
T. Drinkard	T. Bone Springs 7709
T. Abo	T.
T. Wolfcamp 10496	T.
T. Penn	T.
T. Cisco (Bough C)	T.

Northwestern New Mexico

T. Ojo Alamo	T. Penn "B"
T. Kirtland-Fruitland	T. Penn "C"
T. Pictured Cliffs	T. Penn "D"
T. Cliff House	T. Leadville
T. Menefee	T. Madison
T. Point Lookout	T. Elbert
T. Mancos	T. McCracken
T. Gallup	T. Ignacio Otzte
T. Base Greenhorn	T. Granite
T. Dakota	T.
T. Morrison	T.
T. Todilto	T.
T. Entrada	T.
T. Wingate	T.
T. Chinle	T.
T. Permian	T.
T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from	to
No. 2, from	to

No. 3, from	to
No. 4, from	to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in the hole.

No. 1, from	to	feet
No. 2, from	to	feet
No. 3, from	to	feet

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
SURF	1870	1870	RED BEDS				
1870	1910	40	ANHYDRITE				
1910	2970	1060	SALT				
2970	5581	2611	LIME & DOLOMITE				
5581	7709	2128	SAND & SALT				
7709	8873	1164	LIME & SHALE				
8873	9255	382	SAND				
9255	9559	304	LIME				
9559	9950	391	SAND				
9950	10376	426	LIME				
10376	10496	120	SAND				
10496	12202	1706	LIME, SHALE, SAND				
12202	12680	478	SHALE & SAND				