DEC-01-2004 WED 01:38 PM YATES PETROLEUM LAND

FAX NO. 5057484572

P. 02

Form C-144 March 12, 2004

District 1 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

۰.

State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

For drilling and production facilities, submit to appropriate NMOCD District Office. For downstream facilities, submit to Santa Fe office

Pit or Below-Gra	de Tank Registration or Closur	e
Is pit or below-grade tank covered by a "general plan"? Yes XX No		
Type of action: Registration of a pit of	r below-grade tank XX Closure of a pit or below-gra	de tank
Operator: Yates Petroleum CorporationTelephone: (505) 748-4347e-mail address: debbiec@ypenm.com		
Address: <u>105 South 4th Street, Artesia, NM 88210</u> Facility or well name: <u>East Sand Springs State Unit #9</u> API #: <u>30-025-36985</u> U/L or Qtr/Qtr <u>D</u> Sec <u>35</u> T <u>105</u> R <u>34E</u>		
County: Lea Latitude Longitude NAD: 1927 🗌 1983 🗋 Surface Owner Federal 🛄 State 🔲 Private 🐹 Indian 🗍		
Pit Type: Drilling Production Disposal	Below-grade tank	
Workover Emergency	Volume:bb) Type of fluid: Construction material:	
	Double-walled, with leak detection? Yes [] If not, explain why not.	
Liner type: Synthetic XX Thickness 12 mil	sourcewared, whith teak detection? Tes [] if not, explain why not.	
Clay Volume 24,000 bbl		
Depth to ground water (vertical distance from bottom of pit to seasonal high	Less than 50 feet	(20 points)
water elevation of ground water.)	50 feet or more, but less than 100 feet	(10 points)
	100 feet or more	(0 points)
Wellhead protection area: (Less than 200 feet from a private domestic	Yes	(20 points)
water source, or less than 1000 feet from all other water sources.)	No	(0 points)
Distance to surface water: (horizontal distance to all wetlands, playas,	Less than 200 feet	(20 points)
irrigation canals, ditches, and perennial and ephemeral watercourses.)	200 feet or more, but less than 1000 feet	(10 points)
	1000 feet or more	(D points)
	Ranking Score (Total Points)	20 Points
If this is a pit closure: (1) attach a diagram of the facility showing the pit's relationship to other equipment and tanks. (2) Indicate disposal location:		
onsite 🗋 offsite 🔲 If offsite, name of facility (3) Attach a general description of remedial action taken including remediation start date and end		
date. (4) Groundwater encountered: No 🗌 Yes 🗋 If yes, show depth below ground surfaceft. and attach sample results. (5) Attach soil sample results and a		
diagram of sample locations and excavations. I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that the above-described pit or below-grade tank has been/will be constructed or down averaging to NMACED mitching.		
been/will be constructed or closed according to NMOCD guidelines , a general permit XX, or an (attached) alternative OCD-approved plan .		
Date: December 1, 2004 Printed Name/Title Clifton R. May/Regulatory Agent Signature Clifta R. May		
Your certification and NMOCD approval of this application/closure does not relieve the operator of hability should the contents of the pit or tank contaminate ground water or		
otherwise endanger public health or the environment. Nor does it relieve the or regulations.	operator of its responsibility for compliance with any o	ther federal, state, or local laws and/or
Арргоуи		
Date:		
Printed NEECTIN 3 2004 CHIM ENGINEER	Signature and Fland	-

YATES PETROLEUM CORPORATION General Plan was approved 4/15/04

The reserve pit will be to the North. The Southeast corner of the pit will be approximately 60' North of the well bore. The pit will be a 150' X 150' and 6' deep with a capacity of 24,000 bbls.



Standard reserve pit. All Reserve pits are double Horse shoe size varies with depth of well