

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
Artesia, NM 88210

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

OCT 13 '87

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

ARTESIA, OFFICE

OIL WELL ☐ GAS WELL ☐ OTHER ☒ Dry Hole

2. NAME OF OPERATOR

Hilliard Oil & Gas, Inc.

3. ADDRESS OF OPERATOR

3000 North Garfield Suite 120 Midland, TX 79705

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

800' FSL & 1840' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, OR, etc.)

4059' GR

5. LEASE DESIGNATION AND SERIAL NO.

NM 19611

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

None

8. FARM OR LEASE NAME

McClellan "A" Fed. Com.

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Cedar-Point Strawn

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 27 T-15-S R-30-E

12. COUNTY OR PARISH 13. STATE

Chaves

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

X

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

X

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plug and abandon as follows:

Plug #1	250 sx CI "H" + 6# Salt/sk + 10# Sd/sk	10,300'-9,875'
#2	250 sx CI "H" + 6# Salt/sk + 10# Sd/sk	9,875'-9,450'
#3	60 sx CI "H" Neat	8,250'-8,100'
#4	60 sx CI "H" Neat	6,250'-6,100'
#5	37 sx CI "H" Neat	3,370'-3,270'
#6	28 sx CI "H" Neat	550'-450'
#7	12 sx CI "H" Neat	50'-0'

Cut off csg 4' below ground level. Welded steel plate & dry hole marker on stub.
All cementing done by Halliburton.

18. I hereby certify that the foregoing is true and correct

SIGNED

Pat Caley

TITLE Drilling Manager

DATE July 27, 1984

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

Approved as to plugging of the well bore.
Liability under bond is retained until
surface restoration is completed.

*See Instructions on Reverse Side

APPROVED
DATE
PETER W. CHESTER

OCT 6 1987

BUREAU OF LAND MANAGEMENT
DEWELL RESOURCE AREA