NUMBER OF COPIE	SRECE	VED				-	
DIS	TRIBUTI	ÔN					
SANTA FE	T		ľ			ŀ.	
FILE							N
U.S.G.S.		1		1-			1
LAND OFFICE		1					
TRANSPORTER	OIL	1			· · ·		
	GAS		•	1	1		
PRORATION OFFIC	E	1					
OPERATOR		1	. * *	Ť			

Approved

R

Title.

OIL CONSERVATION COMMISSION

Engineer District 1,

NEW MEXICO OIL CONSERVATION COMMISSION

(Form C-102) (Revised 7/1/52)

Santa Fe, New Mexico

MISCELLANEOUS NOTICES MAR 16 3 19 PH '64

HODES OFFICE O.C.C.

strict Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

TO CHANGE PLANS		Notice of Intention to Temporarily Abandon Well		3 of Intention LL Deeper	
Notice of Intention to Plug Well	x	Notice of Intention to Plug Back		l of Intention Liner	
Notice of Intention fo Squeeze		Notice of Intention to Acidize		of Intention fot (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)	Nотіа (Отні	B OF INTENTION	
OIL CONSERVATION COM SANTA FE, NEW MEXICO		Hobbs, New M	exico	3/14/64	L
Gentlemen :	4 4 4 5 4 4 4 4				n de la composition no secondo de la composit
Following is a Notice of In	tention to de	certain work as described below a			
	ny or Operator	Continental S	State "B" Well No	<u>1</u>	0
SW 1/ SE 1/4 of (40-acre Subdivision)	Sec17	, T 16 8 , R 32	8,NMPM.,	Me sa Queen	
Lea	Co	unty.			
ibject well consid	dered r	INSTRUCTIONS IN THE RU	and well re	pair cannot be	i
andoned plugging 20 sx cement off point co 1300-1200; 2 All interval	to be plug i nsidere 5 sx ce s betwe be ret	It is our proposal performed in the f from 3485-3385; 25 ed to be approximat ement plug 420-340; een plugs to be fil turned to natural c well site.	ollowing mar sx cement pl ely 2480'); cement plug led with muc	ner: .ug 2490-2390 (25 sx cement p 10 sx to surf 1. Surface are	shoot lug ace. a at
pandoned plugging 20 sx cement off point co 1300-1200; 2 All interval well site to	to be plug i nsidere 5 sx ce s betwe be ret	performed in the f from 3485-3385; 25 ad to be approximat ament plug 420-340; sen plugs to be fil turned to natural c	ollowing mar sx cement pl ely 2480'); cement plug led with muc	ner: .ug 2490-2390 (25 sx cement p 10 sx to surf 1. Surface are	shoot lug ace. a at
bandoned plugging 20 sx cement off point co 1300-1200; 2 All interval well site to site marker	to be plug i nsidere 5 sx ce s betwe be ret	performed in the f from 3485-3385; 25 ad to be approximat ament plug 420-340; sen plugs to be fil turned to natural c	ollowing mar sx cement pl ely 2480'); cement plug led with muc	ner: .ug 2490-2390 (25 sx cement p 10 sx to surf 1. Surface are	shoot lug ace. a at
bandoned plugging 20 sx cement off point co 1300-1200; 2 All interval well site to site marker	to be plug i nsidere 5 sx ce s betwe be rei set at	performed in the f from 3485-3385; 25 ad to be approximat ement plug 420-340; een plugs to be fil turned to natural c well site.	ACTUS DRILL	ner: ug 2490-2390 (25 sx cement p 10 sx to surf 1. Surface are in appropriate	shoot lug ace. a at
Approved App	to be plug i nsidere 5 sx ce s betwe be rei set at	performed in the form 3485-3385; 25 ad to be approximatement plug 420-340; een plugs to be fil turned to natural c well site.	ACTUS DRILL	Iner: Lug 2490-2390 (25 sx cement p 10 sx to surf 1. Surface are in appropriate	shoot lug ace. a at

Send Communications regarding well to:

	Name. Mr.		Geo. W. J		Baker			
****						, Hobbs		