State of New Mexico Energy, Minerals and Natural Resources Department

mit 3 Copie DISTRICTI OIL CONSERVATION DIVISION P.O. Box 1980, Hobbs, NM 88240 P.O. Box 2088 DISTRICT II Santa Fe. New Mexico 87504-2088 P.O. Drawer DD, Artesia, NM \$8210

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT REBERVOIR, USE APPLICATION FOR PERMIT (FORM C-101) FOR SUCH PROPOSALS.)

COMME

DISTRICT III 1000 Rio Brazos Rd., Aziec, NM 87410

Type of Well:

	Form C-103 Revised 1-1-29
	WELL API NO. 30-025-00383
	5. Indicate Type of Lesse STATE FEE
	6. State Oil & Ges Lesse No. B 9683
	7. Lease Name or Unit Agreement Name
	ANDERSON RANCH <002991>
	8. Well No.
	9. Pool same of Wildow ANDERSON RANCH MORROW
EAST	
LEA County	
Report, or Other Data	

MET [Name of Oper CONOCO INC. <005073> 3. Address of Operator 10 Desta Drive Ste 100 W. Midland, TX Well Location NORTH 1980 1980 G Unit Letter Feet From The 32 E 16 S 11 Section 10. Elevation (Show week) GL 4315 Check Appropriate Box to Indicate Nature of Notice, 11. NOTICE OF INTENTION TO: SU PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING TEMPORARILY ABANDOM CHANGE PLANS COMMENCE DRILLING OPNS PLUG AND ABANDONMEN PULL OR ALTER CASING CASING TEST AND CEMENT JOB OTHER PLUG DEVONIAN & SIDETRACK OTHER. 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. 6-24-98 MIRU. RIG W/ CEMENT RETAINER SET @ 10539', STING INTO RETAINER, PUMPED 5 bbl INTO PERFS. TESTED TBG TO 2500 PSI. PUMPED 20 SX CEMENT BELOW RETAINER & SPOT 20 SX ON TOP OF RETAINER TO PLUG OFF THE DEVONIAN PRODUCING ZONE.

GIH W/ 4 4 3/4" DRILL COLLARS & 6" BIT TAGGED @ 10,294', DRILLED CMT TO 10,250' CIRC CLEAN POOH.
6-29-94 RDMO DA&S WELL SERVICING.
7-1-94 MIRU McVAY RIG #4. GIH W/ HOMCO 5 1/2" BTM TRIP WHIPSTOCK, TYPE 1545 MILL &
ORIENTATION SUB. ORIENTATED W/S DUE SOUTH - SET W/S, TOP OF WINDOW @ 10467. MILL FROM
10467 TO 10480'. CIRC CLEAN, POOH. GIH W/ 6" BIT, BTM HOLE REAMER & BIT SUB, REAM THRU
WINDOW. DRILLED A 6" HOLE FROM 10481 TO 12,357'.
GIH W/ 53 JTS 4 1/2" 11.60 N-80 LT&S CSG LINER. HANG LINER TOP SET @ 10,134' AND BOTTOM
OF LINER SET @ 12,355'. SHOE SET @ 12,355' AND COLLAR SET @ 12,311'. LEAD SLURRY 430 SX
CLASS 'H' CMT W/ .9% FL-62 + .3% CD-32 + .3% SMS & .3% R 3. DISPLACED W/ 109 bbl FW.
CMT RETURNS 13.5 bbl. BUMPED PLUG @ 8:47 am ON 7-27-94 W/ 3200 PSI. RELEASED RIG @ 9 pm
ON 7-27-94. CURRENTLY WAITING ON COMPLETION RIG. POOH.

BILL R. KEATHLY TYPE OR PRINT NAME (This space for State Use)

Orig. Signed by Paul Kautz Geologist

SR. REGULATORY SPEC.

AUG 25 199

8-2-94

915-686-5424

Anderson Ranch De

DATE

TELEPHONE NO.

CONDITIONS OF AFFROVAL, IF ANY: