

N.M. OIL CONS. COMMISSION  
P. BOX-1980  
HOBBS, NEW MEXICO 88240

Form 3160-5  
(June 1990)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

**SUBMIT IN TRIPLICATE**

1. Type of Well  
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

WTI 1993, Ltd.

3. Address and Telephone No.

4714 Valley Ridge Court Ft. Collins, CO 80526 303-225-2905

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FWL & 660' FNL  
Sec. 10-T22S-R32E

5. Lease Designation and Serial No.

NM-55952

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Barr None Fed. #3

9. API Well No.

10. Field and Pool, or Exploratory Area

Undesignated Delaware

11. County or Parish, State

Lea Co., NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☐ Other

- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

10-25-94

Notify BLM-Hobbs of plugging of above well. Plugged in following manner:

1. Welder removed plate from 20" conductor pipe.
2. Run line into hole to 213' to insure hole still dry.
3. Filled 17 1/2" hole with 35 yds ready mix from 213' to the surface.
4. Cutoff 20' conductor to 4' below surface. Installed regulation dry hole mkr.

Dry hole marker installed on 1/2" plate welded to top of 20" conductor.

Approved as to plugging of the well bore.  
Liability under bond is retained until  
surface restoration is completed.

14. I hereby certify that the foregoing is true and correct

Signed

Title Agent

Date 10-27-94

(This space for Federal or State office use)

Approved by Orig. Signed by Shannon J. Shaw  
Conditions of approval, if any:

Title

PETROLEUM ENGINEER

Date

2/16/95