

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*

(See other in-
structions on
reverse side)FOR APPROVED
OMB NO. 1004-0137

Expires: December 31, 1991

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a. TYPE OF WELL:		OIL WELL ☐	GAS WELL ☒	DRY ☐	11/12 PM 2 39	
b. TYPE OF COMPLETION:		NEW WELL ☒	WORK OVER ☐	DEEP-EN ☐	PLUG BACK ☐	DIFF. RESVR ☐
2. NAME OF OPERATOR		BURLINGTON RESOURCES OIL & GAS COMPANY				
3. ADDRESS AND TELEPHONE NO.		PO BOX 4289, Farmington, NM 87499 (505) 326-9700				
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*		At surface SEC. 10, T28N, R11W, NMPM NESE 1793 FSL, 593 FEL At top prod. interval reported below At total depth				
14. PERMIT NO.		DATE ISSUED		12. COUNTY OR PARISH		13. STATE
				San Juan		New Mexico
15. DATE SPUNDED	16. DATE T.D. REACHED	17. DATE COMPL. (Ready to prod.)		18. ELEVATIONS (OF, RKB, RT, BR, ETC.)*		19. ELEV. CASINGHEAD
6/14/83	6/22/83	11/1/04		5581' KB, 5579' GR		
20. TOTAL DEPTH, MD & TVD		21. PLUG, BACK T.D., MD & TVD		22. IF MULTIPLE COMPL. HOW MANY*		23. INTERVALS DRILLED BY
6140'		6094'				ROTARY TOOLS
24. PRODUCTION INTERVAL (S) OF THIS COMPLETION-TOP, BOTTOM, NAME (MD AND TVD)*						CABLE TOOLS
2632' to 2979' Otero Chacra						yes
26. TYPE ELECTRIC AND OTHER LOGS RUN		27. WAS WELL CORED		25. WAS DIRECTIONAL SURVEY MADE		
GR/CBL/CCL		No		No		
28. CASING RECORD (Report all strings set in well)						
CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD		AMOUNT PULLED
9 5/8" J-55	36	315'	12 1/4"	236 cu. ft.		
7" J-55	23	5164'	8 3/4"	2216 cu. ft.		
29. LINER RECORD						
SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	30. TUBING RECORD	
4 1/2"	4960'	6140'	206 cu ft		SIZE	DEPTH SET (MD)
					2 3/8	6016'
31. PERFORATION RECORD (interval, size and number)				32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.		
2632', 2652', 2657', 2664', 2671', 2677', 2694', 2703', 2750' 2758', 2771', 2776', 2783', 2790', 2800', 2807', 2811', 2817', 2850', 2874', 2930', 2941', 2945', 2973', 2979'				DEPTH INTERVAL (MD)		
				2632' - 2979'		
				AMOUNT AND KIND OF MATERIAL USED		
				FRAC W/10,000 gal 75% quality foam pad, 200,000# 20/40 AZ SAND, Displace w/22 fluid bbls & 26,100 scf N2		
33. PRODUCTION						
DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)			WELL STATUS (Producing or shut-in)	
11/1/04		Flowing			SI	
DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROOF FOR TEST PERIOD	OIL-BBL	GAS-MCF	WATER-BBL
11/1/04	1 hour					
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL-BBL	GAS-MCF	WATER-BBL	OIL GRAVITY-API (CORR.)
SI 236	336		0	0	0	
34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)						TEST WITNESSED BY
To be sold						
35. LIST OF ATTACHMENTS						
None						
36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records						

SIGNED Joni Clark TITLE Regulatory Specialist DATE 11/9/04

*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department of agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

ACCEPTED FOR RECORD

NOV 24 2004

NMOCD

FARMINGTON FIELD OFFICE
BY [Signature]

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill-stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.
Ojo Alamo	390'	620'	White, cr-gr ss.
Kirtland	620'	1190'	Gry sh interbedded w/tight, gry, fine-gr ss.
Fruitland	1190'	1650'	Dk gry-gry carb sh, coal, grn silts, light-med gry, tight, fine gr ss.
Pictured Cliffs	1650'	1720'	Bn-Gry, fine grn, tight ss.
Lewis	1720'	2250'	Shale w/siltstone stringers
Chacra	2250'	3360'	Gry fn grn silty, glauconitic sd stone w/drk gry shale
Cliff House	3360'	3990'	ss. Gry, fine-grn, dense sil ss.
Menefee	na	na	Med-dark gry, fine gr ss, carb sh & coal
Point Lookout	3990'	4210'	Med-light gry, very fine gr ss w/frequent sh breaks in lower part of formation
Mancos	4210'	5240'	Dark gry carb sh.
Gallup	5240'		Lt gry to brn calc carb micac glauc silts & very fine gr gry ss w/irreg.interbed sh

38. GEOLOGIC MARKERS

NAME	TOP	
	MEAS. DEPTH	TRUE VERT. DEPTH
Ojo Alamo	390'	
Kirtland	620'	
Fruitland	1190'	
Pictured Cliffs	1650'	
Lewis	1720'	
Chacra	2250'	
Cliffhouse	3360'	
Menefee	na'	
Point Lookout	3990'	
Mancos	4210'	
Gallup	5240'	