Submit 3 Copies To Appropriate District State of New Mexico Form C-103 Office May 27, 2004 Energy, Minerals and Natural Resources District I WELL API NO. 1625 N. French Dr., Hobbs, NM 88240 30 025 02557 District II OIL CONSERVATION DIVISION 1301 W. Grand Ave., Artesia, NM 88210 5. Indicate Type of Lease District III 1220 South St. Francis Dr. STATE V FEE \square 1000 Rio Brazos Rd., Aztec, NM 87410 Santa Fe, NM 87505 6. State Oil & Gas Lease No. District IV 1220 S. St. Francis Dr., Santa Fe, NM E-1830 87505 SUNDRY NOTICES AND REPORTS ON WELLS 7. Lease Name or Unit Agreement Name (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A STATE "A" DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH 8. Well Number PROPOSALS.) 1. Type of Well: Oil Well Gas Well Other 2. Name of Operator 9. OGRID Number HAL J. RASMUSSEN OPERATING, L.P. 3. Address of Operator 10. Pool name or Wildcat 550 W. TEXAS, SUITE 200, MIDLAND, TEXAS 79702 WILSON SEVEN RIVERS, WEST 4. Well Location feet from the SOUTH line and 1980 Unit Letter O : 660 feet from the EAST line Section 16 Township 21-S Range 34-E **NMPM** LEA County 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3740'DF Pit or Below-grade Tank Application 🗌 or Closure 🔲 Pit type STEEL Depth to Groundwater 110 Distance from nearest fresh water well Distance from nearest surface water Pit Liner Thickness: Below-Grade Tank: Volume bbls; Construction Material 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON П REMEDIAL WORK ALTERING CASING □ COMMENCE DRILLING OPNS. **TEMPORARILY ABANDON** П **CHANGE PLANS** P AND A 四 **PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB** OTHER: OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. SET CIBP @ 3926' W/ 25 SX CEMENT ON TOP. PERFORATED @ 1800', SQUEEZED 85 SX, TAG @ 1693'. PERFORATED @ 260', SQUEEZED 85 SX, TAG @ 160'. PERFORATED @ 160', SQUEEZED 120 SX TO SURFACE. Approved as to plugging of the Well Bore. Hobbs Liability under bond is retained until surface restoration is completed. I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or belowgrade tank has been/will be constructed or closed according to NMOCD guidelines ____, a general permit ____ or an (attached) alternative OCD-approved plan _____. SIGNATURE TITLE AGENT DATE_12/1/2004_ Type or print name TOMMY TAYLOR E-mail address: ttaylor@tetratec.com Telephone No. 432 570 5382 TITLE TITLE For State Use Only

Conditions of Approval (if any