

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

2040 Pacheco St.
Santa Fe, NM 87505

WELL API NO.

30-025-36678

Indicate Type of Lease

STATE ☒

FEE

State Oil & Gas Lease No.

32360

Lease Name or Unit Agreement Name

South Kernnitz 28 State

Well No.

1

Pool name or Wildcat

Kernnitz, Atoka-Morrow, South

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

Type of Well:

OIL
WELL

GAS
WELL

☒

OTHER

Name of Operator

Edge Petroleum Operating Co., Inc.

Address of Operator

1301 Travis Suite 2000, Houston, Texas 77002

Well Location

Unit Letter G : 1980 Feet From The North Line and 2130 Feet From The East Line

Section 28 Township 16S Range 34E NMPM Lea County

Elevation (Show whether DF, RKB, RT, GR, etc.)

GB 4100' KB 4122'

11

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ANBANDONMENT ☒

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

10-07-04 Tag existing CIBP @ 10,600'. Circulate well with plugging mud. Spot 25 sks of c cement @ 7,605'. Tagged @ 7,399'.

10-11-04 Pulled stretch on casing 2,800' free. Spot 25 sks of c cement with 2% CaCl @ 4,565'. WOC & attempt to tag plug-No tag.

10-12-04 Spot 45 sks of cement with 2% CaCl @ 4,565'. WOC & tag TOC @ 4,330'. Cut casing @ 2,600'.

10-13-04 LD 60 jts of range 3 LT & C 20# P-110 5 1/2" casing. TIH with tubing to 2,650' Spot 40 sks of c cement with 2% CaCl. Tagged @ 2,473'. Spot 45 sks of cement @ 1,655' WOC. Tagged TOC @ 1,491'.

10-14-04 Spot 50 sks of cement with 2% CaCl @ 542'. WOC Tagged TOC @ 392'. Spot 30 sk surface plug 60'-surface.

Cut off wellhead and anchors 3' BGL. Installed dry hole marker. Clean location.

Approved as to plugging of the Well Bore.

Liability under bond is retained until
surface restoration is completed.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE P & A Manager

DATE 11-08-04

TYPE OR PRINT NAME Jack Shelton

TELEPHONE NO 432-523-5155

(This space for State Use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL IF ANY:

QC FIELD REPRESENTATIVE II/STAFF MANAGER

DEC 22 2004