

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. Oil Cons. Division
1625 N. French Dr.
Hobbs, NM 88240

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT-" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well
Oil ☐ Well Gas ☐ Well ☒ Other Injector

2. Name of Operator

Texaco E&P Inc.

3. Address and Telephone No.

P.O. Box 3109, Midland, Texas 79702 (915) 688-4438

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit O, 330 FSL, 1980 FEL, Section 19, T-24-S, R-38-E

5. Lease Designation and Serial No.

LC-067968-NM10185

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

West Dollarhide Drinkard Unit # 11

9. API Well No.

30 025 12213

10. Field and Pool, or Exploratory Area

Dollarhide, Drinkard, Tubbs, Queen

11. County or Parish, State

Lea County, New Mexico

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other _____

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 1) Notify BLM of intent to plug
- 2) MIRU, NU BOP
- 3) Set CIBP @ 6560, mix and circulate 10# mud, cap W/20 sx (Drinkard)
- 4) Spot 20 sx cement fm 6076-6176 (Tubbs)
- 5) Perf/Sqz 40 sx cement fm 3500-3600 (Queen)
- 6) Perf/Sqz 40 sx cement fm 3175-3275 (8 5/8 shoe) WOC/Tag
- 7) Perf/Sqz 40 sx cement fm 2610-2710 (b-salt) WOC/Tag
- 8) Perf/Sqz 40 sx cement fm 1265-1365 (t-salt) WOC/Tag
- 9) Spot 5 sx cement fm 50'
- 10) RDMO, cut off well head, install dry hole marker, clean location

**SEE ATTACHED FOR
CONDITIONS OF APPROVAL**

14. I hereby certify that the foregoing is true and correct

Signed

Title Engineer

Date 12/01/99

(This space for Federal or State office use)

(ORIG. SGD.) ALEXIS C. SWOBODA

Title PETROLEUM ENGINEER

Date DEC 07 1999

Approved by

Conditions of approval, if any: