

DISTRICT I

P.O. Box 1980, Hobbs, NM 88240

DISTRICT II

P.O. Box Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088

Santa Fe, New Mexico 87504-2088

WELL API NO.

30-025-12228

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil / Gas Lease No.

B-1732

SUNDRY NOTICES AND REPORTS ON WELL
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. Name of Operator
TEXACO EXPLORATION & PRODUCTION INC.

3. Address of Operator
205 E. Bender, HOBBS, NM 88240

4. Well Location

Unit Letter M : 660 Feet From The SOUTH Line and 660 Feet From The WEST Line

Section 28 Township 24S Range 38E NMPM LEA COUNTY

7. Lease Name or Unit Agreement Name
WEST DOLLARHIDE DRINKARD UNIT

8. Well No.
38

9. Pool Name or Wildcat
DOLLARHIDE TUBB DRINKARD

10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3210'GL, KB=14'

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPERATION ☐ PLUG AND ABANDONMENT ☒
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. 3-21-96, MIRU, INSTALL BOP, TOH, TAG @ 6534', TEST LINER TO 550 PSI-HELD. DRILLCEMENT FROM 6534' TO CIBP @ 6578'.
2. 3-22-96, DRILL CIBP @ 6578'M DRILL SCALE TO 6850', CIRCULATE @ 3/4 BBP @ 550 PSI. SET 5' CEMENT RETAINER @ 6350'.
3. 3-25-96, RUN STINGER TO 6345', DISPLACE CASING W/85 BBLS 10# BRINE MUD. SQUEEZE DRINKARD PERFS 6637'-6781' W/100 SX CEMENT @ 850 PSI. SPOT CEMENT FROM 6350'-6300'. PULL TBG TO 4019'. SPOT 30 SX CEMENT FROM 4019'-3646'. PULL TBG TO 2813'/ SPOT 25 SC CEMENT FROM 2813'-2500'. PULL TBG TO 1308'. SPOT 25 SX CEMENT FROM 1308'-1000'. PULL TBG TO 364' SPOT 30 SX CEMENT FROM 364' TO SURFACE. REMOVE BOP. FILL 5' TO TOP. CUT OFF WELL HEAD. INSTALL DRY HOLE MARKER.
4. RD, CHANGE STATUS TO PLUG & ABANDON EFFECTIVE 3-25-96.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Paula S. Ives TITLE Engineering Assistant

DATE 4/29/96

TYPE OR PRINT NAME Paula S. Ives

Telephone No. 397-0432

(This space for State Use)

APPROVED BY Charles Pessin TITLE OIL & GAS INSPECTOR

DATE MAY 28 1996

CONDITIONS OF APPROVAL, IF ANY: