

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
B-2422	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator		8. Farm or Lease Name
TEXACO Inc.		Eunice Monument Unit
3. Address of Operator		9. Well No.
P. O. Box 728, Hobbs, New Mexico 88240		37
4. Location of Well		10. Field and Pool, or Wildcat
UNIT LETTER A, 660 FEET FROM THE North LINE AND 660 FEET FROM		Eunice Monument (G-SA)
THE East LINE, SECTION 30 TOWNSHIP 20-S RANGE 37-E NMPM.		
15. Elevation (Show whether DF, RT, GR, etc.)		12. County
3532' DF		Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input checked="" type="checkbox"/> Repair Water Flow

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. PULLED RODS AND PUMP. INSTALL BOP. PULL TUBING.
2. SET RBP @ 3514' AND SPOT 2 SX SAND ON PLUG.
3. PERFORATE 7" CSG W/2-JS @ 1164'.
4. SET CEMENT RETAINER @ 1044'. CEMENT PERFORATIONS @ 1164' W/280 SX CLASS H CEMENT CONTAINING 2% CACL. CEMENT CIRCULATED. SQUEEZE W/ ADDL 200 SX CLASS H CEMENT CONTAINING 2% CACL. WOC. DOC.
5. TESTED 7" CASING TO 600# FOR 30 MINUTED, 1:30-2:00 PM, 12-7-83. TESTED OK.
6. INSTALL PUMPING EQUIPMENT. TEST AND RETURN TO PRODUCTION.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Asst. Dist. Mgr. DATE 12-22-83

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR

APPROVED BY _____ TITLE _____ DATE DEC 27 1983

CONDITIONS OF APPROVAL, IF ANY: