

30-025-28764

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-101
Revised 1-1-65

5A. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
5. State Oil & Gas Lease No. 15782-C
7. Unit Agreement Name
8. Farm or Lease Name W.A. RAMSEY (NCT-D)
9. Well No. 3
10. Field and Pool, or Wildcat DOLLARHIDE DRINKARD
12. County LEA
19. Proposed Depth 6900
19A. Formation DRINKARD
20. Rotary or C.T. ROTARY
21. Elevations (Show whether DF, RT, etc.) 3213 GL
21A. Kind & Status Plug. Bond BLANKET
21B. Drilling Contractor UNKNOWN
22. Approx. Date Work will start JUNE 25, 1984

APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK

1a. Type of Work b. Type of Well OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/> DRILL <input checked="" type="checkbox"/> DEEPEN <input type="checkbox"/> PLUG BACK <input type="checkbox"/> SINGLE ZONE <input checked="" type="checkbox"/> MULTIPLE ZONE <input type="checkbox"/>	2. Name of Operator GULF OIL CORPORATION	3. Address of Operator P.O. Box 670 HOBBS, NEW MEXICO	4. Location of Well UNIT LETTER L LOCATED 1980 FEET FROM THE SOUTH LINE AND 660 FEET FROM THE WEST LINE OF SEC. 28 TWP. 24S RGE. 38E NMPM
--	--	---	---

PROPOSED CASING AND CEMENT PROGRAM

SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	SACKS OF CEMENT	EST. TOP
12 1/4	8 5/8	24	1250	~ 550 ft ³	SURFACE
7 7/8	5 1/2	15.50	6900	~ 1200 ft ³	TIE-BACK

MUD PROGRAM: 0-1250 FW SPUD MUD 8.6-8.9 ppq 34vis 8.0 pH
1250-TD SATURATED BRINE 9.8-10.0 ppq 29vis 7.0 pH

BOP PROGRAM: SEE ATTACHED DRAWING FOR 3000 psi WORKING PRESSURE

APPROVAL VALID FOR 180 DAYS
PERMIT EXPIRES 12/13/84
UNLESS DRILLING UNDERWAY


IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODUCTIVE ZONE. GIVE BLOWOUT PREVENTER PROGRAM, IF ANY.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed E. C. Anderson Title AREA PROD MGR Date 6-11-84

(This space for State Use)

APPROVED BY Eddie W. Seay TITLE Oil & Gas Inspector DATE JUN 13 1984
CONDITIONS OF APPROVAL, IF ANY:



2000-3000 PSI WORKING PRESSURE
BOP HOOK-UP


SPECIFY WORKING PRESSURE

labeled, with control handles to indicate open and closed positions. A pressure reducer and regulator must be provided for operating the Hydril preventer. When requested, a second pressure reducer shall be available to limit operating fluid pressures to ram preventers. Gulf Legion No. 38 hydraulic oil, an equivalent or better, is to be used as the fluid to operate the hydraulic equipment.

The choke manifold, the choke flow line, the choke lines and the relief lines are to be supported by metal stands and adequately anchored. The choke flow line, relief lines and choke lines shall be constructed as straight as possible and without sharp bends. Easy and safe access shall be maintained to the choke manifold. All valves are to be selected for operation in the presence of oil, gas, and drilling fluids. The choke flow line valves and valves of the relief lines connected to the drilling spools and all ram type preventers must be equipped with stem extensions, universal joints if needed, and hand wheels which are to extend beyond the edge of the derrick substructure. All other valves shall be equipped with handles.

ADDITIONS - DELETIONS - CHANGES SPECIFY

NOTE: "When Requested" means at any time the Gulf Supervisor can, may, or will require the equipment to be installed during operations.



The blowout preventer assembly shall consist of one blind ram preventer and one pipe ram preventer, both hydraulically operated; a Hydril preventer; valves; chokes and connections, as illustrated. If a tapered drill string is used, a ram preventer shall be provided for each size of drill pipe. Casing and tubing rams to fit the preventers are to be available as needed. The ram preventers may be two singles or a double type. If correct in size, the flanged outlets of the ram preventer may be used for connecting to the 4-inch I.D. choke flow line and to the kill line. The substructure height shall be sufficient to install a rotating blowout preventer.

Minimum operating equipment for the preventers and hydraulically operated valves shall be as follows: (1) multiple pumps, driven by a continuous source of power, capable of fluid charging the total accumulator volume from the nitrogen precharge pressure to its rated pressure within 2 minutes. Also, the pumps are to be connected to the hydraulic operating system which is to be a closed system. (2) accumulators with a precharge of nitrogen of not less than 750 PSI and connected so as to receive the aforementioned fluid charge. With the charging pumps shut down, the pressurized fluid volume stored in the accumulators shall be sufficient to close all the pressure-operated devices simultaneously within 19 seconds; after closure, the remaining accumulator pressure shall be not less than 1000 PSI with the remaining accumulator fluid volume at least 50 percent of the original. When requested, either an additional source of power, remote and equivalent, is to be available to operate the above pumps; or there shall be additional pumps operated by separate power and equal in performance capabilities.

MEXICO OIL CONSERVATION COMMISSION
WELL LOCATION AND ACREAGE DEDICATION PLAT

Form C-102
 Supersedes C-128
 Effective 1-1-83

All distances must be from the outer boundaries of the Section.


Operator Gulf Oil Corp.			Lease W. A. Ramsey NCT-D		Well No. 3
Unit Letter L	Section 28	Township 24 South	Range 38 East	County Lea	
Actual Footage Location of Well: 1980 feet from the South line and 660 feet from the West line					
Ground Level Elev. 3213	Producing Formation Drinkard		Pool Subb Dollarhide, Drinkard		Dedicated Acreage: 40 Acres

1. Outline the acreage dedicated to the subject well by colored pencil or hachure marks on the plat below.
2. If more than one lease is dedicated to the well, outline each and identify the ownership thereof (both as to working interest and royalty).
3. If more than one lease of different ownership is dedicated to the well, have the interests of all owners been consolidated by communitization, unitization, force-pooling, etc?

☐ Yes ☐ No If answer is "yes," type of consolidation _____

If answer is "no," list the owners and tract descriptions which have actually been consolidated. (Use reverse side of this form if necessary.) _____

No allowable will be assigned to the well until all interests have been consolidated (by communitization, unitization, forced-pooling, or otherwise) or until a non-standard unit, eliminating such interests, has been approved by the Commission.



CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief.

L. C. Anderson

Name
R. C. ANDERSON

Position
AREA PROD MGR

Company
GULF OIL CORP

Date
6-11-84

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my knowledge and belief.

June 8, 1984

Date Surveyed

Registered Professional Engineer and/or Land Surveyor

John W. West

Certificate No. **JOHN W. WEST, 676**

RONALD J. EIDSON, 3239

