## State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103 Revised 5-27-2004

FILE IN TRIPLICATE OIL CONSERVA	ATION DIVISION
1/06 N. P 1 D II. II. ND 4 000 40	St. Francis Dr. WELL API NO. NM 87505 30-025-07526
DISTRICT II	5. Indicate Type of Lease
1301 W. Grand Ave, Artesia, NM 88210	STATE FEE
DISTRICT III	6. State Oil & Gas Lease No.
1000 Rio Brazos Rd, Aztec, NM 87410	
SUNDRY NOTICES AND REPORTS ON WE	
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (Form C-1	
1. Type of Well:  Oil Well  Gas Well  Other Injector	
2. Name of Operator 9. OGRID No. 157984 Occidental Permian Ltd.	
3. Address of Operator	10. Pool name or Wildcat HOBBS (G/SA)
1017 W. Stanolind Rd., HOBBS, NM 88240 505/397-8200  4. Well Location	
Unit Letter E: 1370 Feet From The NORTH 330 Feet From The WEST Line	
Section 32 Township 18-S	Range 37-E NMPM LEA County
11. Elevation (Show whether DF, RR 3630' GL	- · · · · · · · · · · · · · · · · · · ·
Pit or Below-grade Tank Application or Closure	
Pit Type Depth of Ground Water Distance from nearest fresh water well Distance from nearest surface water	
Pit Liner Thickness mil Below-Grade Tank: Volume bbls; Construction Material	
12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data  NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK PLUG AND ABANDON FEMPORARILY ABANDON CHANGE PLANS	REMEDIAL WORK  X  ALTERING CASING  COMMENCE DRILLING OPNS.  PLUG & ABANDONMENT
PULL OR ALTER CASING Multiple Completion	COMMENCE DRILLING OPNS PLUG & ABANDONMENT  CASING TEST AND CEMENT JOB
OTHER:	OTHER:
13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.	
1. RUPU. Wellhead has been replaced for CO2 service.	
2. Sqz perfs 4096 to 4100 and csg patch from 4088' to 4108' using 850 sx Prem + cmt w/3% CaCl.	
3. Perforate the following intervals: 4112-20 using 2 spf and 180 deg spiral ph.	
<ol> <li>Stimulate perfs 4112-4214 w/1890 g 15% NEFE HCL acid.</li> <li>RIH w/5" Guiberson UNI VI pc pkr, XL on/off tool w/1.875 ss "F" nipple. 130' 2-7/8" Duoline tbg. Pkr set @4024'.</li> </ol>	
6. Load csg w/160 bbl pkr fluid. Tst csg to 580 psi for 30 min and chart for the NMOCD.	
7. RDPU. Clean Location.	
Rig Up Date: 11/15/2004	
Rig Down Date: 12/06/2004	
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be	
constructed or closed according to NMOCD guidelines , a general permit	or an (attached) alternative OCD-approved
	plan
SIGNATURE Robert Filbert	TITLE Workover Completion Specialist DATE 12/27/2004
TYPE OR PRINT NAME Robert Gilbert E-mail address:	robert_gilbert@oxy.com TELEPHONE NO. 505/397-8206
For State Use Only	DEDDECENTATIVE II/STAFF NUNIVAYED
APPROVED BY	OC FIELD REPRESENTATIVE II/STAFF MAISTAN 1 3 2005
APPROVED BY CONDITIONS OF APPROVAL IFANY:	OC FIELD REPRESENTATIVE TO THE DATE DATE

