

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*
(See other in-
structions on
reverse side)

FOR APPROVED
OMB NO. 1004-0137

Expires: December 31, 1991

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a. TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRY ☐ OTHER ☐

b. TYPE OF COMPLETION:

NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RESVR ☐ OTHER ☐

RECEIVED

FARMINGTON NM

2. NAME OF OPERATOR

BURLINGTON RESOURCES OIL & GAS COMPANY

3. ADDRESS AND TELEPHONE NO.

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)

At surface 1945'FSL, 1440'FEL

At top prod. interval reported below

At total depth

5. LEASE DESIGNATION AND SERIAL NO.

NMSF-UBU/13B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

San Juan 30-6 Unit NMMN 78420B

8. FARM OR LEASE NAME, WELL NO.

San Juan 30-6 Unit #442S

9. API WELL NO.

30-039-27693

10. FIELD AND POOL, OR WILDCAT

Basin Fruitland Coal

11. SEC. T., R., M., OR BLOCK AND SURVEY OR AREA

Sec. 14, T-30-N, R-6-W

14. PERMIT NO.

DATE ISSUED

12. COUNTY OR PARISH

Rio Arriba

13. STATE

New Mexico

15. DATE SPUN

5/28/04

16. DATE T.O. REACHED

11/24/04

17. DATE COMPL. (Ready to prod.)

11/30/04

18. ELEVATIONS OF, RKB, RT, BR, ETC.)*

6209' GR, 6221' KB

19. ELEV. CASINGHEAD

20. TOTAL DEPTH, MD & TVD

3189'

21. PLUG, BACK T.O., MD & TVD

3189'

22. IF MULTIPLE COMPL., HOW MANY*

23. INTERVALS DRILLED BY

ROTARY TOOLS

CABLE TOOLS

0-3189'

24. PRODUCTION INTERVAL (S) OF THIS COMPLETION-TOP, BOTTOM, NAME (MD AND TVD)*

2835-3108' Fruitland Coal

25. WAS DIRECTIONAL SURVEY MADE

26. TYPE ELECTRIC AND OTHER LOGS RUN
GK-RHOB

27. WAS WELL CORED
No

CASING RECORD (Report all strings set in well)

CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
9 5/8"	32.3#	134'	12 1/4"	69 cu.ft.	
7"	20#	2808'	8 3/4"	778 cu.ft.	

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
5 1/2"	2778'	3189'	none		2 3/8"	3150'	
					(SN @ 3130')		

31. PERFORATION RECORD (Interval, size and number)

2835-2878', 2918-3003', 3065-3108'
Pre-perforated liner

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
2835-3108'	none

33. PRODUCTION
DATE FIRST PRODUCTION PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)

WELL STATUS (Producing or shut-in)

DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N FOR TEST PERIOD	OIL-BBL	GAS-MCF	WATER-BBL	GAS-OIL RATIO
11/30/03	1	2"			712 MCF/D Pitot Gauge		
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL-BBL	GAS-MCF	WATER-BBL	OIL GRAVITY-API (CORR.)	
SI 0	SI 83			712 MCF/D			

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

To be sold

TEST WITNESSED BY

35. LIST OF ATTACHMENTS

None

ACCEPTED FOR RECORD

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

DEC 21 2004

SIGNED Nancy Olthman TITLE Senior Staff Specialist

DATE 12/8/04

FARMINGTON FIELD OFFICE

*(See instructions and spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCD

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill-stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):

38. GEOLOGIC MARKERS

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	TOP	
					MEAS. DEPTH	TRUE VERT. DEPTH
Ojo Alamo	2161'	2344'	White, cr-gr ss.	Ojo Alamo	2161'	
Kirtland	2344'	2646'	Gry sh interbedded w/tight, gry, fine-gr ss.	Kirtland	2344'	
Fruitland	2646'	3108'	med gry, tight, fine gr ss.	Fruitland	2646'	
Pictured Cliffs	3108'	3189'	Bn-Gry, fine grn, tight ss.	Pic.Cliffs.	3108'	