

Submit To Appropriate District Office State Lease - 6 copies Fee Lease - 5 copies <u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 <u>District II</u> 1301 W. Grand Avenue, Artesia, NM 88210 <u>District III</u> 1000 Rio Brazos Rd., Aztec, NM 87410 <u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM 87505	State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505	Form C-105 Revised June 10, 2003 WELL API NO. 30-025-36913 5. Indicate Type of Lease STATE ☒ FEE ☐ State Oil & Gas Lease No. B-1167-48
--	---	--

WELL COMPLETION OR RECOMPLETION REPORT AND LOG					
1a. Type of Well: OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER _____ b. Type of Completion: NEW ☒ WORK ☐ DEEPEN ☐ PLUG ☐ DIFF. WELL OVER BACK RESVR. ☐ OTHER			7. Lease Name or Unit Agreement Name North Monument G/SA Unit 1431		
2. Name of Operator Amerada Hess Corporation			8. Well No. 337		
3. Address of Operator P.O. Box 840 Seminole, TX 79360			9. Pool name or Wildcat Eunice Monument; Grayburg-San Andres		
4. Well Location Unit Letter <u>L</u> : <u>2630</u> Feet From The <u>South</u> Line and <u>150</u> Feet From The <u>West</u> Line Section <u>36</u> Township <u>19S</u> Range <u>36E</u> NMPM <u>Lea</u> County					
10. Date Spudded 10/30/2004	11. Date T.D. Reached 11/5/2004	12. Date Compl. (Ready to Prod.) 12/9/2004	13. Elevations (DF& RKB, RT, GR, etc.) 3594' GR		14. Elev. Casinghead
15. Total Depth 3944'	16. Plug Back T.D.	17. If Multiple Compl. How Many Zones?	18. Intervals Drilled By	Rotary Tools	Cable Tools
19. Producing Interval(s), of this completion - Top, Bottom, Name Eunice Monument; Grayburg San Andres 3823'-3930'					20. Was Directional Survey Made No
21. Type Electric and Other Logs Run CBL/Platform Express Three-detector LithoDensity/High Resolution Laterolog Array GR					22. Was Well Cored
23. CASING RECORD (Report all strings set in well)					
CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8 5/8"	24#	432'	11"	400 sx 'C'	2122' 2524'
5 1/2"	15.5#	3944'	7 7/8"	850 sx 'C'	
24. LINER RECORD			25. TUBING RECORD		
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE
					2 7/8"
26. Perforation record (interval, size, and number) 3823'-3845', 3850'-3854', 3868'-3908', 3910'-3916', 3922-3930', Eunice Monument G/SA				27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC. DEPTH INTERVAL AMOUNT AND KIND MATERIAL USED 3823'-3930' Acidized w/6000 gals 15% NMGSAU blend	
28. PRODUCTION					
Date First Production 12/9/2004		Production Method (Flowing, gas lift, pumping - Size and type pump) Pumping 2 1/2" X 2" RWBC 20' pump A-1373			Well Status (Prod. or Shut-in) Producing
Date of Test 12/31/2004	Hours Tested 24	Choke Size	Prod'n For Test Period	Oil - Bbl 36	Gas - MCF 3
Water - Bbl. 46		Gas - Oil Ratio 85			
Flow Tubing Press. 40	Casing Pressure 40	Calculated 24-Hour Rate	Oil - Bbl. 36	Gas - MCF 3	Water - Bbl. 46
Oil Gravity - API - (Corr.) 32					
29. Disposition of Gas (Sold, used for fuel, vented, etc.) Sold					Test Witnessed By
30. List Attachments C103, C104, C102, Logs					
31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief					
Signature <i>Carol J. Moore</i>		Printed Name Carol J. Moore		Title Senior Advisor/Regulatory	Date 1/6/2005
E-mail Address cmoore@hess.com					

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy 1030'	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Salt 1130'	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates 2545'	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers	T. Devonian	T. Menefee	T. Madison
T. Queen	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg 3570'	T. Montoya	T. Mancos	T. McCracken
T. San Andres 3980'	T. Simpson	T. Gallup	T. Ignacio Otzte
T. Glorieta	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T.
T. Blinbry	T. Gr. Wash	T. Morrison	T.
T. Tubb	T. Delaware Sand	T. Todilto	T.
T. Drinkard	T. Bone Springs	T. Entrada	T.
T. Abo	T.	T. Wingate	T.
T. Wolfcamp	T.	T. Chinle	T.
T. Penn	T.	T. Permian	T.
T. Cisco (Bough C)	T.	T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....
No. 2, from.....to.....
No. 3, from.....to.....
No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology
0'	1030'	1030'	Red Beds
1030'	1130'	100'	Anhydrite
1130'	2545'	1415'	Salt
2545'	3980'	1435'	Dolomite, Anhydrite, & Sand