New Mexico Oil Construction Division, District I 1625 N. French Drive Hobbs, NM 38240

Form 3160-5

(April 2004)	DEPARTMENT OF THE	E INTERIOR			FORM APPROVED OMB No. 1004-0137 Expires: March 31, 2007	
	BUREAU OF LAND MAN			5. Lease Seria		
SUNDRY NOTICES AND REPORTS ON WELLS			NM-60777			
Do not use	this form for proposals well. Use Form 3160 - 3 (to drill or to re-e	nter an	6. If Indian	, Allottee or Tribe Name	
availdoned	well. Ose Form 3160-3 ((APD) for such pro	posais.			
SUBMIT IN TRIPLICATE- Other instructions on reverse side.				7. If Unit or	CA/Agreement, Name and/or No.	
1. Type of Well X Oil Well	Gas Well Other			8. Well Nar	ne and No	
2. Name of Operator	COC OPER	A TO THE		MINIS	"1" FEDERAL #	4
COG OPERATING LLC 3a Address 5.50 W. TEXAS AVENUE 3b. Phone No. (include area code)			9. APJ Well No. 30-025-36956		6	
TE 1300 SMIDEAND ONTX 79701 432-683-7443			10. Field and	d Pool, or Exploratory Area		
4. Location of Well (Footage, S	ec., T., R., M., or Survey Description)				MESA DELAWARE	
310' FNL & 330	O' FWL, Section	1, T-21S,	R-32E	11. County	or Parish, State	
				LEA	COUNTY, NM	
	APPROPRIATE BOX(ES) TO	O INDICATE NATUR	E OF NOTICE,	REPORT, OR	OTHER DATA	<u></u>
TYPE OF SUBMISSION		TYP	PE OF ACTION			
Notice of Intent	Acidize Alter Casing	Deepen	Production (S	tart/Resume)	Water Shut-Off	
Subsequent Report	Casing Repair	Fracture Treat New Construction	Reclamation		Well Integrity Other	
	Change Plans	Plug and Abandon	Recomplete Temporarily	handon		
Final Abandonment Notice	Convert to Injection	Plug Back	Water Disposa			
Attach the Bond under white following completion of the	upleted Operation (clearly state all perti- directionally or recomplete horizontal ich the work will be performed or prove e involved operations. If the operation . Final Abandonment Notices shall be	tinent details, including estir lly, give subsurface location vide the Bond No. on file w	ns and measured and to with BLM/BIA. Requiletion or recompletion	rue vertical depth ired subsequent r i in a new interva	ns of all pertinent markers and zone eports shall be filed within 30 days I. a Form 3160-4 shall be filed once	3.
Attach the Bond under whi following completion of the testing has been completed	apleted Operation (clearly state all perti- directionally or recomplete horizontal ich the work will be performed or prov- e involved operations. If the operation . Final Abandonment Notices shall be eady for final inspection.)	tinent details, including estir lly, give subsurface location vide the Bond No. on file wan results in a multiple comple e filed only after all requirer	ns and measured and to with BLM/BIA. Requiletion or recompletion	rue vertical depth ired subsequent r i in a new interva	ns of all pertinent markers and zone eports shall be filed within 30 days I. a Form 3160-4 shall be filed once	3.
Attach the Bond under whi following completion of the testing has been completed determined that the site is recommended.	apleted Operation (clearly state all pertidirectionally or recomplete horizontal ich the work will be performed or prove involved operations. If the operation. Final Abandonment Notices shall be eady for final inspection.) Drilled 10-5/8" hole to	tinent details, including estir lly, give subsurface location vide the Bond No. on file wan results in a multiple comple e filed only after all requirer	ns and measured and to with BLM/BIA. Requiletion or recompletion ments, including recla	rue vertical depth ired subsequent r i in a new interva mation, have bee	ns of all pertinent markers and zones eports shall be filed within 30 days il, a Form 3160-4 shall be filed once in completed, and the operator has	3.
Attach the Bond under whi following completion of the testing has been completed determined that the site is re	upleted Operation (clearly state all pertidirectionally or recomplete horizontal ich the work will be performed or prove involved operations. If the operation is Final Abandonment Notices shall be eady for final inspection.) Drilled 10-5/8" hole to Ran 121 jts of 8-5/8" 3	tinent details, including estirally, give subsurface location vide the Bond No. on file was results in a multiple comple e filed only after all requirer 5378'.	ns and measured and to with BLM/BIA. Requiletion or recompletion ments, including reclain	rue vertical depth ired subsequent r i in a new interva mation, have bee	ns of all pertinent markers and zone: eports shall be filed within 30 days I, a Form 3160-4 shall be filed once in completed, and the operator has with: 1st Lead:	3.
Attach the Bond under whi following completion of the testing has been completed determined that the site is recommended.	upleted Operation (clearly state all pertidirectionally or recomplete horizontal ich the work will be performed or prove involved operations. If the operation. Final Abandonment Notices shall be early for final inspection.) Drilled 10-5/8" hole to Ran 121 jts of 8-5/8" 3 200 sx H + 10% A-10	tinent details, including estir lly, give subsurface location vide the Bond No. on file wan results in a multiple comple e filed only after all requirer 5378'.	ns and measured and to with BLM/BIA. Requisition or recompletion ments, including reclaims. et @ 5378'. CCM1. 14.2#	rue vertical depthired subsequent rein a new intervalmation, have been	so of all pertinent markers and zone eports shall be filed within 30 days it, a Form 3160-4 shall be filed once in completed, and the operator has with: 1st Lead:	
Attach the Bond under whi following completion of the testing has been completed determined that the site is recommended.	pleted Operation (clearly state all pertidirectionally or recomplete horizontal ich the work will be performed or prove involved operations. If the operation. Final Abandonment Notices shall be eady for final inspection.) Drilled 10-5/8" hole to Ran 121 jts of 8-5/8" 3 200 sx H + 10% A-10 50 / 50 C + 10% GE, CI C, 1% CaCl2. Plug	tinent details, including estir lly, give subsurface location vide the Bond No. on file wan results in a multiple comple e filed only after all requirer 5378'. 32# J-55 casing so + 1/4# CF, 10# LC 5% salt, 1/4# CF, 1 g down @ 3:43 PM	et @ 5378'. CCM1. 14.2#, No. MST 1/6/05.	rue vertical depthired subsequent rein a new intervalmation, have been	ns of all pertinent markers and zone: eports shall be filed within 30 days I, a Form 3160-4 shall be filed once in completed, and the operator has with: 1st Lead:	
Attach the Bond under whi following completion of the testing has been completed determined that the site is recommended to the strain of the	pleted Operation (clearly state all pertidirectionally or recomplete horizontal ich the work will be performed or prove involved operations. If the operation. Final Abandonment Notices shall be eady for final inspection.) Drilled 10-5/8" hole to Ran 121 jts of 8-5/8" 3 200 sx H + 10% A-10 50 / 50 C + 10% GE, CI C, 1% CaCl2. Plug temperature survey ar	tinent details, including estir lly, give subsurface location vide the Bond No. on file wan results in a multiple comple e filed only after all requirer 5378'. 32# J-55 casing so + ½# CF, 10# LC 5% salt, ¼# CF, 1 g down @ 3:43 PM and found TOC at 2	et @ 5378'. CCM1. 14.2#, Y5# LCM1. 1.8M MST 1/6/05.2887'.	rue vertical depthired subsequent rein a new intervalmation, have been	with: 1st Lead: 2nd Lead: 560 sx 45. Fail: 200 sx hours. Ran	DR RECO
Attach the Bond under whi following completion of the testing has been completed determined that the site is recommended.	pleted Operation (clearly state all pertidirectionally or recomplete horizontal ich the work will be performed or prove involved operations. If the operation. Final Abandonment Notices shall be eady for final inspection.) Drilled 10-5/8" hole to Ran 121 jts of 8-5/8" 3 200 sx H + 10% A-10 50 / 50 C + 10% GE, CI C, 1% CaCl2. Plug	tinent details, including estir lly, give subsurface location vide the Bond No. on file wan results in a multiple comple e filed only after all requirer 5378'. 32# J-55 casing so + ½# CF, 10# LC 5% salt, ¼# CF, 1 g down @ 3:43 PM and found TOC at 2	et @ 5378'. CCM1. 14.2#, Y5# LCM1. 1.8M MST 1/6/05.2887'.	rue vertical depthired subsequent rein a new intervalmation, have been	so of all pertinent markers and zone eports shall be filed within 30 days it, a Form 3160-4 shall be filed once in completed, and the operator has with: 1st Lead:	DR RECO
Attach the Bond under whi following completion of the testing has been completed determined that the site is recommended to the strain of the	pleted Operation (clearly state all pertidirectionally or recomplete horizontal ich the work will be performed or prove involved operations. If the operation. Final Abandonment Notices shall be eady for final inspection.) Drilled 10-5/8" hole to Ran 121 jts of 8-5/8" 3 200 sx H + 10% A-10 50 / 50 C + 10% GE, CI C, 1% CaCl2. Plug temperature survey ar	tinent details, including estir lly, give subsurface location vide the Bond No. on file wan results in a multiple comple e filed only after all requirer 5378'. 32# J-55 casing so + ½# CF, 10# LC 5% salt, ¼# CF, 1 g down @ 3:43 PM and found TOC at 2	et @ 5378'. CCM1. 14.2#, Y5# LCM1. 1.8M MST 1/6/05.2887'.	rue vertical depthired subsequent rein a new intervalmation, have been	with: 1st Lead: 2nd Lead: 560 sx JAN 2 4	DR RECO
Attach the Bond under whi following completion of the testing has been completed determined that the site is recommend to the site is recommended to the site is recommended.	pleted Operation (clearly state all pertidirectionally or recomplete horizontal ich the work will be performed or prove involved operations. If the operation. Final Abandonment Notices shall be eady for final inspection.) Drilled 10-5/8" hole to Ran 121 jts of 8-5/8" 3 200 sx H + 10% A-10 50 / 50 C + 10% GE, CI C, 1% CaCl2. Plug temperature survey ar NU BOP's and test all	tinent details, including estir lly, give subsurface location vide the Bond No. on file wan results in a multiple comple e filed only after all requirer 5378'. 32# J-55 casing so + ½# CF, 10# LC 5% salt, ¼# CF, 1 g down @ 3:43 PM and found TOC at 2	et @ 5378'. CCM1. 14.2#, Y5# LCM1. 1.8M MST 1/6/05.2887'.	rue vertical depthired subsequent rein a new intervalmation, have been	with: 1st Lead: 2nd Lead: 560 sx 45. Fail: 200 sx hours. Ran	DR RECO
Attach the Bond under whi following completion of the testing has been completed determined that the site is recommend to the site is recommended.	pleted Operation (clearly state all pertidirectionally or recomplete horizontal ich the work will be performed or prove involved operations. If the operation. Final Abandonment Notices shall be eady for final inspection.) Drilled 10-5/8" hole to Ran 121 jts of 8-5/8" 3 200 sx H + 10% A-10 50 / 50 C + 10% GE, CI C, 1% CaCl2. Plug temperature survey ar NU BOP's and test all	tinent details, including estir lly, give subsurface location vide the Bond No. on file wan results in a multiple comple e filed only after all requirer 5378'. 32# J-55 casing so + ½# CF, 10# LC 5% salt, ¼# CF, 1 g down @ 3:43 PM and found TOC at 2	et @ 5378'. CCM1. 14.2#, \ 5# LCM1. 1.8 MMST 1/6/05.2887'.	rue vertical depthired subsequent ruin a new intervalmation, have been depthicated with the subsequent ruin a new intervalmation, have been depthicated with the subsequent ruin and ru	with: 1st Lead: 2nd Lead: 560 sx. 45. Tail: 200 sx: D F(hours. Ran	DR RECO
Attach the Bond under whi following completion of the testing has been completed determined that the site is round to the site is round	pleted Operation (clearly state all pertidirectionally or recomplete horizontal ich the work will be performed or prove involved operations. If the operation. Final Abandonment Notices shall be eady for final inspection.) Drilled 10-5/8" hole to Ran 121 jts of 8-5/8" 3 200 sx H + 10% A-10 50 / 50 C + 10% GE, CI C, 1% CaCl2. Plug temperature survey ar NU BOP's and test all	tinent details, including estir lly, give subsurface location vide the Bond No. on file wan results in a multiple comple e filed only after all requirer 5378'. 32# J-55 casing set + 1/4# CF, 10# LC 5% salt, 1/4# CF, 1 g down @ 3:43 PM and found TOC at 2 BOP equipment.	et @ 5378'. COM1. 14.2#, No. MST 1/6/05.2887'.	rue vertical depthired subsequent ruin a new intervalmation, have been depthicated with the subsequent ruin a new intervalmation, have been depthicated with the subsequent ruin and ru	with: 1st Lead: 2nd Lead: 560 sx 45. Tail: 200 sx: D F(hours. Ran JAN 2 A GARY GO PHIROLEUM An alyst	DR RECO
Attach the Brond under whi following completion of the testing has been completed determined that the site is respectively. O1/05/05 O1/06/05 O1/07/05 14. I hereby certify that the finame (Printed/Typed) PHYLLIS A.	pleted Operation (clearly state all pertidirectionally or recomplete horizontal ich the work will be performed or prove involved operations. If the operation. Final Abandonment Notices shall be eady for final inspection.) Drilled 10-5/8" hole to Ran 121 jts of 8-5/8" 3 200 sx H + 10% A-10 50 / 50 C + 10% GE, CI C, 1% CaCl2. Plug temperature survey ar NU BOP's and test all	inent details, including estir lly, give subsurface location vide the Bond No. on file wan results in a multiple comple e filed only after all requirer 5378'. 32# J-55 casing so + ½# CF, 10# LO 5% salt, ½# CF, 19 g down @ 3:43 PM and found TOC at 2 BOP equipment.	et @ 5378'. CCM1. 14.2#, \ 5# LCM1. 1.8 M MST 1/6/05.2887'.	rue vertical depthired subsequent rein a new intervalmation, have been depthication, depthication, have been depthication, depthic	with: 1st Lead: 2nd Lead: 560 sx 45. Tail: 200 sx: D F(hours. Ran JAN 2 A GARY GO PHIROLEUM An alyst	DR RECO
Attach the Bond under whi following completion of the testing has been completed determined that the site is round	pleted Operation (clearly state all pertidirectionally or recomplete horizontal ich the work will be performed or prove involved operations. If the operation. Final Abandonment Notices shall be eady for final inspection.) Drilled 10-5/8" hole to Ran 121 jts of 8-5/8" 3 200 sx H + 10% A-10 50 / 50 C + 10% GE, CI C, 1% CaCl2. Plug temperature survey ar NU BOP's and test all Toregoing is true and correct EDWARDS	tinent details, including estirally, give subsurface location vide the Bond No. on file wan results in a multiple comple filed only after all requirer 15378'. 32# J-55 casing so + ½# CF, 10# LC 5% salt, ½# CF, 10# LC 5% salt, ½# CF, 10# LC 15% s	et @ 5378'. COM1. 14.2#, No# LCM1. 1.8 MMST 1/6/05.2887'.	rue vertical depthired subsequent rein a new intervalmation, have been depthired 1.61. #, Yield 1.61. #, Yield 2. WOC 12	with: 1st Lead: 2nd Lead: 560 sx 45. Tail: 200 sx hours. Ran JAN 24 GARY GO PHIROLEUM An alyst	DR RECO
Attach the Bond under whi following completion of the testing has been completed determined that the site is respectively. O1/05/05 O1/06/05 O1/07/05 14. I hereby certify that the f Name (Printed/Typed) PHYLLIS A. Signature Approved by Conditions of approval, if any, a	pleted Operation (clearly state all pertidirectionally or recomplete horizontal ich the work will be performed or prove involved operations. If the operation. Final Abandonment Notices shall be eady for final inspection.) Drilled 10-5/8" hole to Ran 121 jts of 8-5/8" 3 200 sx H + 10% A-10 50 / 50 C + 10% GE, CI C, 1% CaCl2. Plug temperature survey ar NU BOP's and test all This space for	inent details, including estirally, give subsurface location vide the Bond No. on file was results in a multiple comple filed only after all requirer 5378'. 32# J-55 casing set + ½# CF, 10# LC 5% salt, ½# CF, 10# LC 5% salt, ½# CF, 10 BOP equipment. Title Date FEDERAL OR ST	et @ 5378'. CCM1. 14.2#, \ 5# LCM1. 1.8 M MST 1/6/05.2887'.	rue vertical depthired subsequent rein a new intervalmation, have been depthired 1.61. #, Yield 1.61. #, Yield 2. WOC 12	with: 1st Lead: 2nd Lead: 560 sx 45. Tail: 200 sx: D F(hours. Ran JAN 2 A GARY GO PHIROLEUM An alyst	DR RECO
Attach the Brod under whi following completion of the testing has been completed determined that the site is respectively. O1/05/05 O1/06/05 O1/07/05 14. I hereby certify that the finame (Printed/Typed) PHYLLIS A. Signature Approved by Conditions of approval, if any, a certify that the applicant holds less that the specific property is approved.	pleted Operation (clearly state all pertidirectionally or recomplete horizontal ich the work will be performed or prove involved operations. If the operation. Final Abandonment Notices shall be eady for final inspection.) Drilled 10-5/8" hole to Ran 121 jts of 8-5/8" 3 200 sx H + 10% A-10 50 / 50 C + 10% GE, CI C, 1% CaCl2. Plug temperature survey ar NU BOP's and test all Toregoing is true and correct EDWARDS	inent details, including estirally, give subsurface location vide the Bond No. on file wan results in a multiple comple in filed only after all requirer and the subsurface of the filed only after all requirer and the subsurface of the subsurface	et @ 5378'. COM1. 14.2#, No# LCM1. 1.8 MMST 1/6/05.2887'.	rue vertical depthired subsequent rein a new intervalmation, have been depthired 1.61. #, Yield 1.61. #, Yield 2. WOC 12	with: 1st Lead: 2nd Lead: 560 sx 45. Tail: 200 sx hours. Ran JAN 24 GARY GO PHIROLEUM An alyst	DR RECO

(Instructions on page 2)