L.	DEPARTMENT OF THE INTERIOR, NM 88240 BUREAU OF LAND MANAGEMENT, NM 88240			Expires: March 31, 2007 5. Lease Serial No. LC 030168A		
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.			6. If Indian, Allottee or Tribe Name			
abandoned w	ell. Use Form 3160-3 ((APD) for such pro	posais.	7.1511-10-0-0.04	Agreement, Name and/or No.	
	IPLICATE- Other inst	tructions on rever	se side.	7. If Unit of CAV	Agreement, Ivanic and of Ivo.	
I. Type of Well ☐ Gas Well ☐ Other					8. Weil Name and No. Eaves "A" #1	
2. Name of Operator Southwest Royalties, Inc.				9. API Well No. 30-025-12007		
a Address 6 Desta Drive, Ste 2100, Midl	3b. Phone No. (include 432/688-3267	3b. Phone No. (include area code) 432/688-3267		10. Field and Pool, or Exploratory Area Scarborough Yates 7-Rivers 11. County or Parish, State Lea County, NM		
Location of Well (Footage, Sec.)					
330' FSL & 2310' FEL Sec 19, T26S, R37E, Unit Let	, ,					
12. CHECK A	APPROPRIATE BOX(ES) TO	O INDICATE NATUR	LE OF NOTICE,	REPORT, OR O	THER DATA	
TYPE OF SUBMISSION		TY	PE OF ACTION			
Notice of Intent	Acidize	Deepen Fracture Treat	Production ((Start/Resume)	Water Shut-Off Well Integrity	
Subsequent Report	Casing Repair	New Construction	Recomplete]Other	
Final Abandonment Notice	Change Plans	Phug and Abandon Phug Back	Temporarily			
Attach the Bond under which following completion of the testing has been completed. determined that the site is rea MI & RU; NU 10" BOP Circ hole w/170 Bbls M POH w/tbg; ND WH; w 10-3/4" X 16" annulus a	inectionally or recomplete horizont h the work will be performed or pro- involved operations. If the operation Final Abandonment Notices shall ady for final inspection.) P; RIH w/tbg and tag CIBP @ LF, spot 55 sx from 2800' - 25 reld onto 8-5/8" esg; cut and p and 16 X 20" annulus -valved K 50 oc from 1650', 1550' W/	taily, give subsurface locati tovide the Bond No. on file ion results in a multiple com be filed only after all requir 2800'. S80'. and 1600' fo 8-5/8" csg. and plumbed to surface OC & tas: POH w/the.	with BLM/BIA. Req pletion or recompletis ements, including rec w/valve and risers	nuired subsequent repo on in a new interval, a lamation, have been c	nts shall be filed within 30 days Form 3160-4 shall be filed once completed, and the operator has	
If the proposal is to deepen d Attach the Bond under which following completion of the testing has been completed. determined that the site is rea MI & RU; NU 10" BOP Circ hole w/170 Bbls M POH w/tbg; ND WH; w 10-3/4" X 16" annulus a RIH w/tbg to 1650', spo Perforate 10-3/4" and 1 Leave cmt @ surface in	inectionally or recomplete horizont h the work will be performed or pro- involved operations. If the operation Final Abandonment Notices shall ady for final inspection.) *; RIH w/tbg and tag CIBP @ LF, spot 55 sx from 2800' - 25 reld onto 8-5/8" csg; cut and p and 16 X 20" annulus -valved is 50 sx from 1650' - 1550'. Wo 585'. RIH w/10-3/4" pkr and 6" csg @ 233'. Establish circ	taily, give subsurface locati rovide the Bond No. on file ion results in a multiple com be filed only after all requir 2800'. S80'. and 1600' fo 8-5/8" csg. and plumbed to surface OC & tag; POH w/tbg. d tbg; sqz perfs w/110 s; c out 10-3/4" X 16" csg a	with BLM/BIA. Req pletion or recompletion ements, including rec w/valve and risers & from 585' - 485';	s. WOC & tag;/POH	nts shall be filed within 30 days Form 3160-4 shall be filed once completed, and the operator has	
If the proposal is to deepen d Attach the Bond under which following completion of the testing has been completed. determined that the site is rea MI & RU; NU 10" BOP Circ hole w/170 Bbls M POH w/tbg; ND WH; w 10-3/4" X 16" annulus a RIH w/tbg to 1650', spo Perforate 10-3/4" csg @ Perforate 10-3/4" and I Leave cmt @ surface in MD MO WS. Cuf off V	inectionally or recomplete horizoni h the work will be performed or pro- involved operations. If the operation Final Abandonment Notices shall ady for final inspection.) *; RIH w/tbg and tag CIBP @ LF, spot 55 sx from 2800' - 25 reld onto 8-5/8" csg; cut and p and 16 X 20" annulus -valved tt 50 sx from 1650' - 1550'. W/ b) 585'. RIH w/10-3/4" pkr and 6" csg @ 233'. Establish circ side 10-3/4". VH, install dry hole marker an	taily, give subsurface locati rovide the Bond No. on file ion results in a multiple com be filed only after all requir 2800'. S80'. and 1600' fo 8-5/8" csg. and plumbed to surface OC & tag; POH w/tbg. d tbg; sqz perfs w/110 s; c out 10-3/4" X 16" csg a	with BLM/BIA. Req pletion or recompletion ements, including rec w/valve and risers & from 585' - 485';	s. WOC & tag;/POH	rts shall be filed within 30 days Form 3160-4 shall be filed once ompleted, and the operator has	
If the proposal is to deepen d Attach the Bond under which following completion of the testing has been completed. determined that the site is rea MI & RU; NU 10" BOP Circ hole w/170 Bbls M POH w/tbg; ND WH; w 10-3/4" X 16" annulus a RIH w/tbg to 1650', spo Perforate 10-3/4" and 1 Leave cmt @ surface in	inectionally or recomplete horizoni h the work will be performed or pro- involved operations. If the operation Final Abandonment Notices shall ady for final inspection.) *; RIH w/tbg and tag CIBP @ LF, spot 55 sx from 2800' - 25 reld onto 8-5/8" csg; cut and p and 16 X 20" annulus -valved t 50 sx from 1650' - 1550'. W/) 585'. RIH w/10-3/4" pkr and 6" csg @ 233'. Establish circ side 10-3/4". WH, install dry hole marker an oregoing is true and correct	taily, give subsurface locati rovide the Bond No. on file ion results in a multiple com be filed only after all requir 2 2800'. 580'. and 1600' fo 8-5/8" csg. and plumbed to surface OC & tag; POH w/tbg. d tbg; sqz perfs w/110 sz c out 10-3/4" X 16" csg a nd clean location.	with BLM/BIA. Req pletion or recompletion ements, including rec w/valve and risers & from 585' - 485';	s. WOC & tag;/POH	rts shall be filed within 30 days Form 3160-4 shall be filed once ompleted, and the operator has	
If the proposal is to deepen d Attach the Bond under which following completion of the testing has been completed. determined that the site is rea MI & RU; NU 10" BOP Circ hole w/170 Bbls M POH w/tbg; ND WH; w 10-3/4" X 16" annulus a RIH w/tbg to 1650', spo Perforate 10-3/4" csg @ Perforate 10-3/4" and I Leave cmt @ surface in MD MO WS. Cuf off V	inectionally or recomplete horizoni h the work will be performed or pro- involved operations. If the operation Final Abandonment Notices shall ady for final inspection.) *; RIH w/tbg and tag CIBP @ LF, spot 55 sx from 2800' - 25 reld onto 8-5/8" csg; cut and p and 16 X 20" annulus -valved t 50 sx from 1650' - 1550'. W/) 585'. RIH w/10-3/4" pkr and 6" csg @ 233'. Establish circ side 10-3/4". WH, install dry hole marker an oregoing is true and correct	taily, give subsurface location rovide the Bond No. on file ion results in a multiple com be filed only after all require 22800'. S80'. and plumbed to surface OC & tag; POH w/tbg. d tbg; sqz perfs w/110 sp c ut 10-3/4" X 16" csg a nd clean location.	with BLM/BIA. Req pletion or recompletio ements, including rec w/valve and risers to from 585' - 485'; nd 16" X 20" csg a	s. WOC & tag;/POH and 16" X 20"	rts shall be filed within 30 days Form 3160-4 shall be filed once ompleted, and the operator has	
If the proposal is to deepen d Attach the Bond under which following completion of the testing has been completed. determined that the site is rea MI & RU; NU 10" BOP Circ hole w/170 Bbls M POH w/tbg; ND WH; w 10-3/4" X 16" annulus : RIH w/tbg to 1650', spo Perforate 10-3/4" csg @ Perforate 10-3/4" and I Leave cmt @ surface in MD MO WS. Cuf off V 14. Ihereby certify that the f Name (Printed/Typed) Mark Gygax	irectionally or recomplete horizoni h the work will be performed or pro- involved operations. If the operation Final Abandonment Notices shall ady for final inspection.) P; RIH w/tbg and tag CIBP @ LF, spot 55 sx from 2800' - 25 reld onto 8-5/8" csg; cut and p and 16 X 20" annulus -valved t 50 sx from 1650' - 1550'. W(1) 585'. RIH w/10-3/4" pkr and 6" csg @ 233'. Establish circus iside 10-3/4". WH, install dry hole marker and oregoing is true and correct Magnetic Space FO	duly, give subsurface location rovide the Bond No. on file ion results in a multiple com be filed only after all require 2800'. S80'. and plumbed to surface OC & tag; POH w/tbg. d tbg; sqz perfs w/110 sz c out 10-3/4" X 16" csg a nd clean location. dmh Title Date DR FEDERAL OR	Area Engineer	s. WOC & tagy/POH and 16" X 20"	rts shall be filed within 30 days Form 3160-4 shall be filed once ompleted, and the operator has	
If the proposal is to deepen d Attach the Bond under which following completion of the testing has been completed. determined that the site is real MI & RU; NU 10" BOP Circ hole w/170 Bbls M POH w/tbg; ND WH; w 10-3/4" X 16" annulus a RIH w/tbg to 1650', spo Perforate 10-3/4" csg @ Perforate 10-3/4" csg @ Perforate 10-3/4" and T Leave cmt @ surface in MD MO WS. Cuf off V 14. Ihereby certify that the f Name (Printed/Typed) Mark Gygax	inectionally or recomplete horizoni h the work will be performed or pro- involved operations. If the operation Final Abandonment Notices shall ady for final inspection.) ?; RIH w/tbg and tag CIBP @ LF, spot 55 sx from 2800' - 25 veld onto 8-5/8" csg; cut and p and 16 X 20" annulus -valved t 50 sx from 1650' - 1550'. Wo 585'. RIH w/10-3/4" pkr and 6" csg @ 233'. Establish circ iside 10-3/4". WH, install dry hole marker an oregoing is true and correct	duly, give subsurface location rovide the Bond No. on file ion results in a multiple com be filed only after all require 2800'. S80'. and plumbed to surface OC & tag; POH w/tbg. d tbg; sqz perfs w/110 sz c out 10-3/4" X 16" csg a nd clean location. dmh Title Date DR FEDERAL OR	Area Engineer	s. WOC & tagy/POH and 16" X 20"	Here is shall be filed within 30 days form 3160-4 shall be filed once completed, and the operator has	
If the proposal is to deepen d Attach the Bond under which following completion of the testing has been completed. determined that the site is real MI & RU; NU 10" BOP Circ hole w/170 Bbls M POH w/tbg; ND WH; w 10-3/4" X 16" annulus : RIH w/tbg to 1650', spo Perforate 10-3/4" csg @ Perforate 10-3/4" csg @ Perforate 10-3/4" and I Leave cmt @ surface in MD MO WS. Cuf off V MD MO WS. Cuf off V Mark Gygax Signature MAM Approved by (ORIG. Conditions of approval, if any, certify that the applicant holds I	irectionally or recomplete horizont h the work will be performed or pro- involved operations. If the operation Final Abandonment Notices shall ady for final inspection.) P; RIH w/tbg and tag CIBP @ LF, spot 55 sx from 2800' - 25 veld onto 8-5/8" csg; cut and p and 16 X 20" annulus -valved t 50 sx from 1650' - 1550'. Wo 585'. RIH w/10-3/4" pkr and 6" csg @ 233'. Establish circ iside 10-3/4". WH, install dry hole marker and oregoing is true and correct THIS SPACE FO SGD.) DAWD R. G are attached. Approval of this no legal or equitable title to those rig nt to conduct operations thereon.	atily, give subsurface locati rovide the Bond No. on file ion results in a multiple com be filed only after all requir 2800'. 580'. and plumbed to surface 'OC & tag; POH w/tbg. d tbg; sqz perfs w/110 sz c out 10-3/4" X 16" csg a nd clean location. dmh Title Date DR FEDERAL OR LASS vice does not warrant or juts in the subject lease	Area Engineer 1-21-05 STATE OFFic Title Office	s. WOC & tag: POH and 16" X 20" CE USE	the JAN 3 1 2005	
If the proposal is to deepen d Attach the Bond under which following completion of the testing has been completed. determined that the site is real MI & RU; NU 10" BOP Circ hole w/170 Bbls M POH w/tbg; ND WH; w 10-3/4" X 16" annulus : RIH w/tbg to 1650', spo Perforate 10-3/4" csg @ Perforate 10-3/4" csg @ Perforate 10-3/4" and I Leave cmt @ surface in MD MO WS. Cuf off V MD MO WS. Cuf off V Mark Gygax Signature MAM Approved by (ORIG. Approved by (ORIG. Conditions of approval, if any, certify that the applicant holds I which would entitle the applicant	irectionally or recomplete horizont h the work will be performed or pro- involved operations. If the operation Final Abandonment Notices shall ady for final inspection.) P; RIH w/tbg and tag CIBP @ LF, spot 55 sx from 2800' - 25- reld onto 8-5/8" csg; cut and p and 16 X 20" annulus -valved t 50 sx from 1650' - 1550'. W() 585'. RIH w/10-3/4" pkr and 6" csg @ 233'. Establish circ iside 10-3/4". WH, install dry hole marker and oregoing is true and correct WHS SPACE FO SGD.) DAWD R. G are attached. Approval of this no legal or equitable title to those rig	atily, give subsurface location rovide the Bond No. on file ion results in a multiple com be filed only after all require 2800'. 580'. and plumbed to surface 'OC & tag; POH w/tbg. d tbg; sqz perfs w/110 sp cout 10-3/4" X 16" csg a nd clean location. dmh Title Date DR FEDERAL OR LASS vice does not warrant or gats in the subject lease e. it a crime for any person	Area Engineer 1-21-05 STATE OFFIC Title Office knowinely and will	s. WOC & tag: POH and 16" X 20" CE USE	the JAN 3 1 2005	
If the proposal is to deepen d Attach the Bond under which following completion of the testing has been completed. determined that the site is real MI & RU; NU 10" BOP Circ hole w/170 Bbls M POH w/tbg; ND WH; w 10-3/4" X 16" annulus : RIH w/tbg to 1650', spo Perforate 10-3/4" csg @ Perforate 10-3/4" csg @ Perforate 10-3/4" and I Leave cmt @ surface in MD MO WS. Cuf off V MD MO WS. Cuf off V Mark Gygax Signature MAM Approved by (ORIG. Approved by (ORIG. Approved by if any, certify that the applicant holds I which would entitle the applicant	irectionally or recomplete horizont h the work will be performed or pro- involved operations. If the operation Final Abandonment Notices shall ady for final inspection.) P; RIH w/tbg and tag CIBP @ LF, spot 55 sx from 2800' - 25 reld onto 8-5/8" csg; cut and p and 16 X 20" annulus -valved t 50 sx from 1650' - 1550'. Wo 585'. RIH w/10-3/4" pkr and 6" csg @ 233'. Establish circus iside 10-3/4". WH, install dry hole marker and oregoing is true and correct THIS SPACE FO SGD.) DAWD R. G are attached. Approval of this non- legal or equitable title to those rig in to conduct operations thereon. The 43 USC Section 1212 make	atily, give subsurface location rovide the Bond No. on file ion results in a multiple com be filed only after all require 2800'. 580'. and plumbed to surface 'OC & tag; POH w/tbg. d tbg; sqz perfs w/110 sp cout 10-3/4" X 16" csg a nd clean location. dmh Title Date DR FEDERAL OR LASS vice does not warrant or gats in the subject lease e. it a crime for any person	Area Engineer 1-21-05 STATE OFFIC Title Office knowinely and will	s. WOC & tag: POH and 16" X 20" CE USE	the JAN 3 1 2005	

Eaves A #1



12/86: TA'd w/ CIBP @ 2800'

7/28: Completed in Yates, 7 Rivers 2840'-3000' (OH)

> Eaves A #1 Currently

<u>Eaves A #1</u>



Proposed P&A