	RTMEN, OF THE INTERI	(Other Instanting	E Form approv Budget Bure 5. LEASE DESIGNATION	AND SERIAL NO.	
	GEOLOGICAL SURVEY	·····	6. IF INDIAN, ALLOTTE		
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals.)			د. دری مهر محمد است.	a we want	
······································		<u></u>	7. UNIT AGREEMENT N CST LATLAT	AME 11de	
OIL GAS OTH	ur Dual 111 and 11ate	r lujection	Drinkard		
NAME OF OPERATOR				ffde	
SKELLY UIL COR	разку		9. WELL NO.	Jait	
P. C. Box 1351	, Midlaud, Texas 79701		7		
	tion clearly and in accordance with any	-	10. FIELD AND POOL, (B WILDCAT	
At surface		U.S. GROLOUNAL SI	Dollarhide Ti		
16541 PS) and 1	1980" FEL Soc. 19-248-38	HOTES, HEW MEAK	11. SEC., T., R., M., OR SURVEY OR ARE.	BLK. AND A	
13379 CARLAND	LION PEL DEC. 17"440"JU	d	Sec. 19-24	5-38E	
PERMIT NO.	15. ELEVATIONS (Show whether DF,	, RT, GR, etc.)	12. COUNTY OB PARIS	H 13. STATE	
	3192° m		Lea	New Mexico	
Chec	k Appropriate Box To Indicate N	lature of Notice, Report, or	Other Data	الير ۲۰ ۲۰۰۰ - ۲۰۰۰ ۲۰۰۰ - ۲۰۰۰	
NOTICE OF	INTENTION TO :	SUBSE	EQUENT REPORT OF:		
TEST WATER SHUT-OFF	PULL OR ALTER CASING	WATEB SHUT-OFF	REPAIRING	WELL	
FRACTUBE TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING (CASING	
SHOOT OR ACIDIZE	ABANDON*	SHOOTING OR ACIDIZING	Ing and Convert	Tubb	
(Other)	CHANGE PLANS	(Other)	its of multiple completion	On Well	
work was done:			ween Planes - Time we	llowing	
				Llowing	
1. Moved is and	rigged up workover rig 9				
 Hoved in and Kan tubing and 	rigged up workover rig 9 d spear and pulled 5-1/2				
 hoved in and kan tubing an casing. 	d spear and pulled 5-1/2	" OD casing at 434,			
 Hoved in and Kan tubing an casing. kan 5-1/2" OB 	d spear and pulled 5-1/2 casing and set in colle	" OD casing at 434,			
 hoved in and kan tubing an casing. kan 5-1/2" OB 8ecovered all 	d spear and pulled 5-1/2 casing and set in colle of fight	" OD casing at 434,			
 Hoved in and Ran tubing an cesing. Kan 5-1/2" OD Secovered all Ran tubing an 6. Ran 2-3/8" OD 	d spear and pulled 5-1/2 casing and set in colle of fish. d tagged fill at 6730°, tubing internally coste	" OD casing at 434, Ir at 434". Id with tube kote TM	recovering col	Lapsed a the second se	
 Hoved in and Ran tubing and casing. Ran 5-1/2" OB Ran 5-1/2" OB Ran tubing an Ran tubing an Ran 2-3/8" OD with seal ass 	d spear and pulled 5-1/2 casing and set in colle of figh. d tagged fill at 6730°, tubing internally coste eachly, and set Baker pac	" OD casing at 434, Ir at 434". Id with tube kote TE Eker at 6600° for Dr	recovering col -75 plastic lin inkard sour inj	Lapsed Lapsed	
 Hoved in and Ran tubing an cosing. Ran 5-1/2" OB Becovered all Ran tubing an 6. Ran 2-3/8" OD with seal ass Loaded casing 	d spear and pulled 5-1/2 casing and set in colle of fish. d tagged fill at 6730 ⁴ , tubing internally coate embly, and set Baker pac annalus behind tubing w	" OD casing at 434, Ir at 434". Id with tube kote TR Iker at 6600" for Dr Aith inhibited Queen	recovering col -75 plastic lin inkard sour inj	Lapsed Lapsed	
 Hoved in and Ran tubing an cosing. Ran 5-1/2" OB Ran 5-1/2" OB Ran tubing an b. Ran tubing an b. Ran 2-3/8" OD with seal ass Loaded casing Queen perform 	d spear and pulled 5-1/2 casing and set in colle of fish. d tagged fill at 6730°, tubing internally coste eably, and set Saker pac annalus behind tubing w tions (3810°) to packer	" OD casing at 434, ar at 434". ed with tube kote TK eker at 6600° for Dr with inhibited Queen - setting depth.	-75 plastic lin inkard sout inj vater from bas	Lapséd La	
 Hoved in and Ran tubing an casing. Ran 5-1/2" OB Ran 5-1/2" OB Ran tubing an tubi	d spear and pulled 5-1/2 casing and set in colle of fish. d tagged fill at 6730°, tubing internally coste embly, and set Baker pac annalus behind tubing b tions (3810°) to packer d rods to pump Queen zon	" OD casing at 434', ar at 434'. ed with tube kote Th ker at 6600' for Dr with inhibited Queen - setting depth. w perforations 3754	-75 plastic lin inkard sout inj vater from bas	Lapséd La	
 Hoved in and Ran tubing and casing. Ran 5-1/2" OB Ran 5-1/2" OB Ran tubing and Ran tubing and Ran 2-3/8" OD with seal ass Loaded casing Queen perfora Ran tubing an this zone to Booked well t 	d spear and pulled 5-1/2 casing and set in colle of fish. d tagged fill at 6730 ⁴ , tubing internally coste embly, and set Baker pac annalus behind tubing w tions (3810 ⁴) to packer d rods to pump Queen zon operator, Atlantic-Richi to injection system and b	" OD casing at 434, in at 434". d with tube kote Th kar at 6600" for Dr with inhibited Queen - setting depth. me perforations 3754 field Company. megan injecting wate	-75 plastic lin inkard socc inj vater from bas -3810' and retu r on October 1.	Lapsed Lapsed States Ctions of English	
 Hoved in and Ran tubing an casing. Ran 5-1/2" OB Ran tubing an 5. Ran tubing an 5. Ran tubing an 5. Ran 2-3/8" OD with seal ass Loaded casing Queen perfora Ran tubing an this zone to Hooked well t into 5-1/2" O 	d spear and pulled 5-1/2 casing and set in colle of fish. d tagged fill at 6730°, tubing internally costs eachly, and set Sakar pac (annulus behind Eubing to tions (3810°) to packer ad rods to pump Queen zon operator, Atlantic-Richf to injection system and b D casing perforstions 66	" OD casing at 434, in at 434°. d with tube kote TE sker at 6600° for Dr with inhibited Queen - setting depth. we perforations 3754 field Company. segan injecting wate 570-6723° of the Tub	-75 plastic lin inkard some inj vater from bas -3810' and retu er on October 1. b-Drinkard Hese	Lapsed ing oction. of 1970, Tvolr.	
 hoved in and kan tubing an casing. kan 5-1/2" OB kan 5-1/2" OB kan tubing an 6. Ran 2-3/8" OD with seal ass Loaded casing Queen perfora Ran tubing an this zone to ilcoked well t into 5-1/2" O This is a 	d spear and pulled 5-1/2 casing and set in colle of fish. d tagged fill at 6730°, tubing internally coste embly, and set Baker pac (annulus behind tubing b tions (3010°) to packer d rods to pump Queen zon operator, Atlantic-Richi to injection system and b D casing perforstions 66 water injection well for	" OD casing at 434, in at 434°. d with tube kote TE sker at 6600° for Dr with inhibited Queen - setting depth. we perforations 3754 field Company. segan injecting wate 570-6723° of the Tub	-75 plastic lin inkard some inj vater from bas -3810' and retu er on October 1. b-Drinkard Hese	Lapséd ing oction. of ing 1970,	
 hoved in and kan tubing an casing. kan 5-1/2" OB kan 5-1/2" OB kan 2-3/8" OD with seal ass Loaded casing Queen perfora Ran tubing an this zons to Blooked well t into 5-1/2" O This is a operated 	d spear and pulled 5-1/2 casing and set in colle of fish. d tagged fill at 6730°, tubing internally coste embly, and set Baker pac (annalus behind tubing to tions (3810°) to packer d rods to pump Queen zon operator, Atlantic-Richi to injection system and b D casing perforstions 66 water injection well for by Skelly Oil Company.	" OD casing at 434, in at 434°. d with tube kote TE sker at 6600° for Dr with inhibited Queen - setting depth. we perforations 3754 field Company. segan injecting wate 570-6723° of the Tub	-75 plastic lin inkard socc inj vater from bas -3810' and retu er on October 1. b-Drinkard Rese	Lapséd ing oction. of ing 1970,	
 hoved in and kan tubing an casing. kan 5-1/2" OB kan 5-1/2" OB kan 2-3/8" OD with seal ass Loaded casing Queen perfora kan tubing an this zons to ilooked well t into 5-1/2" O This is a operated 	d spear and pulled 5-1/2 casing and set in colle of fish. d tagged fill at 6730°, tubing internally costs eachly, and set Baker pac danalus behind Eubing to tions (3810°) to packer d rods to pump Queen zon operator, Atlantic-Richf to injection system and b D casing perforstions 66 water injection well for by Skelly Oil Company.	" OD casing at 434, in at 434°. d with tube kote TE sker at 6600° for Dr with inhibited Queen - setting depth. we perforations 3754 field Company. segan injecting wate 570-6723° of the Tub	recovering col -75 plastic lin inkard some inj vater from bas -3810' and retu er on October 1; b-Drinkard Rese de Drinkard Uni	Lapséd Lapséd Lapséd Lapséd Lapséd Lapséd Lass Colorado Lass Lass Colorado Colorado Co	
 Hoved in and Kan tubing an casing. Kan 5-1/2" OB Kan 5-1/2" OB Kan 2-3/8" OD with seal ass Loaded casing Queen perfora Ran tubing an this sone to Blooked well t into 5-1/2" O This is a operated 	d spear and pulled 5-1/2 casing and set in colle of fish. d tagged fill at 6730° , tubing internally costs eachly, and set Saker pac annulus behind tubing to tions (3810°) to packer id rods to pump Queen zon operator, Atlantic-Richf to injection system and b D casing perforations 66 water injection well for by Skelly Oil Company. oing is true and correct $B_{\rm c} = 0.000$ TITLE bis	" OD casing at 434, ar at 434". ed with tube kote The eker at 6600° for Dr with inhibited Queen - setting depth. he perforations 3754 field Company. began injecting wate 570-6723° of the Tub or the West Dollarhi	-75 plastic lin inkard socc inj vater from bas -3810' and retu or on Occober 1. b-Drinkard Hese ide Driskard Uni	Lapséd Lapséd Lapséd Lapséd Lapséd Lapséd Lass Colorado Lass La	
 Hoved in and Ran tubing an casing. Ran 5-1/2" OB Ran 5-1/2" OB Ran tubing an tubing an tubing an tubing an tubing an tubing an this sone to Ran tubing an this sone to Booked well t into 5-1/2" O This is a operated Thereby certify that the foregonal states of the space for Federal or States APPROVED BY	d spear and pulled 5-1/2 casing and set in colle of fish. d tagged fill at 6730°, tubing internally coste embly, and set Baker pac annalus behind subing to tions (3810°) to packer d rods to pump Queen zon operator, Atlantic-Richi to injection system and b D casing perforstions 66 water injection well for by Skelly Oil Company. oing is true and correct B. A Site TITLE his the office use)	" OD casing at 434, in at 434°. ed with tube kote TE eker at 6600° for Dr with indubited Queen - setting depth. We perforations 3754 field Company. Segan injecting wate 570-5723° of the Tub or the West Dollarhi	-75 plastic lin inkard socc inj vater from bas -3810' and retu or on Occober 1. b-Drinkard Hese ide Driskard Uni	Lapséd Lapséd Lapséd Lapséd Lapséd Lapséd Lass Colorado Lass La	
 hoved in and kan tubing an casing. kan 5-1/2" OB kan 5-1/2" OB kan tubing an b. Ran tubing an b. Ran 2-3/8" OD with seal ass Loaded casing Queen perfora Ran tubing an this zone to ilooked well t into 5-1/2" O This is a operated I hereby certify that the foregoest of the space for Federal or State 	d spear and pulled 5-1/2 casing and set in colle of fish. d tagged fill at 6730°, tubing internally coste embly, and set Baker pac annalus behind subing to tions (3810°) to packer d rods to pump Queen zon operator, Atlantic-Richi to injection system and b D casing perforstions 66 water injection well for by Skelly Oil Company. oing is true and correct B. A Site TITLE his the office use)	" OD casing at 434, ar at 434". ed with tube kote The eker at 6600° for Dr with inhibited Queen - setting depth. he perforations 3754 field Company. began injecting wate 570-6723° of the Tub or the West Dollarhi	-75 plastic lin inkard sose inj vater from bas -3810' and retu bo-Drinkard Rese de Driskard Uni 	Lapséd Lapséd Lapséd Lapséd Lapséd Lass Ctions. Southand Ctions. Southand Ction	
 Hoved in and Ran tubing an casing. Ran 5-1/2" OB Ran 5-1/2" OB Ran tubing an b. Ran 2-3/8" OD with seal ass Ran 2-3/8" OD with seal ass Loaded casing Queen perfora Ran tubing an this zone to Blooked well t into 5-1/2" O This is a operated I bereby certify that the foregram operated 	d spear and pulled 5-1/2 casing and set in colle of fish. d tagged fill at 6730°, tubing internally coste embly, and set Baker pac annalus behind subing b tions (3810°) to packer d rods to pump Queen zon operator, Atlantic-Richf o injection system and b D casing perforstions 66 water injection well for by Skelly Oil Company. oing is true and correct E. A cast TITLE bis ite office use) . IF ANY:	" OD casing at 434, In at 434°. In at 434°	-75 plastic lin inkard some inj vater from bas -3810' and retu r on October 1, b-Drinkard Hese de Driekard Uni DATE OCT	Lapsed Lapsed Lapsed Lapsed Lapsed Lapsed Lass Collections Col	
 Hoved in and Kan tubing an casing. Kan 5-1/2" OB Kan 5-1/2" OB Kan 2-3/8" OD with seal ass Loaded casing Queen perfora Ran tubing an this zone to Blooked well t into 5-1/2" O This is a operated I bereby certify that the foregoestigned (SIGNED (SIGNED CONDITIONS OF APPROVAL) 	d spear and pulled 5-1/2 casing and set in colle of fish. d tagged fill at 6730°, tubing internally coste embly, and set Baker pac annalus behind subing to tions (3810°) to packer d rods to pump Queen zon operator, Atlantic-Richi to injection system and b D casing perforstions 66 water injection well for by Skelly Oil Company. oing is true and correct B. A Difference TITLE Inis the office use) TITLE Inis	" OD casing at 434, ar at 434". ed with tube kote Theker at 6600° for Dr with inhibited Queen - setting depth. he perforations 3754 field Company. began injecting wate 570-6723° of the Tub or the West Dollarhi est. Adm. Coordinator AGGIP C	-75 plastic lin inkard sose inj vater from bas -3810' and retu bo-Drinkard Rese de Driskard Uni 	Lapsed Lapsed	

a sa sa Nata Kata