

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. Oil Cons. Division
1625 N. French Dr.
Hobbs, NM 88240

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

CONFIDENTIAL

1. Type of Well
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator
Pogo Producing Company

3. Address and Telephone No.

P. O. Box 10340, Midland, TX 79702-7340 432-685-8100

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

840' FNL & 2310' FWL, Section 13, T22S, R32E

5. Lease Designation and Serial No.

NM-58940

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

WBR Federal #10

9. API Well No.

30-025-36064

10. Field and Pool, or Exploratory Area

Red Tank Bone Spring

11. County or Parish, State

Lea County, NM

12. **CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA**

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Drilg operations

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Intermediate Csg - Drld 11" hole to 4500'. TD reached @ 15:15 hrs 05/28/03. Ran 102 jts 8-5/8" 32# K-55, J-55 & S-80 LTC & STC csg. Cmt'd w/ 1200 sks 35:65 POZ "C" @ 12.4 ppg followed by 200 sks CI "C" + 1% CaCl2. Circ 150 sks to surface. Plug down @ 04:30 hrs 05/29/03. WOC 24 hrs. Make cut-off. Install WH. NU BOP's & test ok.

TD & Production Csg - Drld 7-7/8" hole to 10,050'. TD reached @ 09:30 hrs 06/09/03. Logged well w/ Schlumberger. Ran 230 jts 5-1/2" 17# J-55 & N-80 LT&C csg. Cmt'd 1st stage w/ 1375 sks CI "H" + additives @ 15.7 ppg. Circ 191 sks to surface. Cmt'd 2nd stage w/ 750 sks CI "C" + additives @ 14.09 ppg. Did not circ cmt to surface. CBL ran 06/21/03. TOC @ 2180'.

ACCEPTED FOR RECORD

JUL 15 2003

GARY GOURLEY
PETROLEUM ENGINEER

14. I hereby certify that the foregoing is true and correct

Signed

Cathy Lambert

Title Sr. Operation Tech

Date 07/07/03

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

Date

KZ