

**THE OIL CONSERVATION DIVISION MUST  
BE NOTIFIED 24 HOURS PRIOR TO THE  
BEGINNING OF PLUGGING OPERATIONS.**

# Vacuum SWD Well F-35

17 1/2" hole  
350 sx  
13 3/8" 48#  
H40 @ 330'

KB 3920  
GL 3907'

1986' FNL & 1982' FWL  
SEC 35- 17S 35E

API # 30-025-03034

TOC @ 1400'

11" hole  
400 sx

Casing filled with Unichem PKR FLD

8 5/8" 32.34#  
Csg @ 3253'

300 lbs on inter. 3-7-05

TOC @ 3705'

7 7/8" hole  
250 sx

CIBP @ 4800'  
5 1/2" 14# CSG @ 4885'

T/ Rustler 1716'

T/Yates 3070'

T/Queen 4010'

PBTD @ 5855'

T/Grayburg 4320'

5855-6350'  
150 sx

T/SanAndres 4630'

T/Glorieta 6435'

T/Clearfork 6580

7485-7600'  
50 sx

T/Abo Reef 9134'

PB 8845'  
150 sx

OH TD @ 9400'

# Vacuum SWD Well F-35

API # 30-025-03034  
KB 3920 GL 3907'  
1986' FNL & 1982' FWL  
SEC 35- 17S 35E

