

Submit 3 Copies To Appropriate District

Office

District I

1625 N. French Dr., Hobbs, NM 88240

District II

1301 W. Grand Ave., Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

87505

State of New Mexico

Energy, Minerals and Natural Resources

Form C-103

March 4, 2004

RECEIVED

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

Oil Conservation Division

1220 S. Saint Francis Dr. Santa Fe, NM 87505

WELL API NO.

30-025-06916

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

V.M.Henderson

8. Well Number

10

9. OGRID Number

10. Pool name or Wildcat

Paddock

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator

Chevron USA Inc

3. Address of Operator

15 Smith Rd, Midland, TX 79705

4. Well Location

Unit Letter D : 660 feet from the North line and 660 feet from the West line

Section 30 Township 21-S Range 37-E NMPM Lea County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

Pit or Below-grade Tank Application (For pit or below-grade tank closures, a form C-144 must be attached)

Pit Location: UL D Sect 30 Twp 21S Rng 37E Pit type Steel Depth to Groundwater 100 Distance from nearest fresh water well Over 1000'

Distance from nearest surface water 660 feet from the North line and 660 feet from the West line (Steel Tank)

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1. Notify OCD 24 hrs prior to MI and RU.

2. RU on Paddock (West) set 2 7/8 CIBP @ 5100, Spot 60sx Plug 5100-2700 (Paddock) WOC Tag.

3. RU on Grayburg (North) Set 2 7/8 CIBP @ 3610 Spot 25sx Plug 3610-2700 (Grayburg) WOC Tag.

4. RU on Paddock (East) Set 2 7/8 CIBP @ 5100 Spot 60sx Plug 5100-2700 (Paddock) WOC Tag.

5. Cut 2 7/8 CSGS @ 2700 L/D CSGS.

6. Displace Hole W/MLF 9.5 #Brine W/12.5 #Gel P/BBL.

7. Spot 100sx Plug 2700-2400 (Stub-Yates) WOC Tag

8. Spot 75sx Plug 1400-1200 (T-Salt) WOC Tag.

9. Spot 75sx Plug 375-200 (13 3/8 Shoe) WOC Tag.

10. 10sx Surf Install Dry Hole Marker

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐ a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE

TITLE

Consultant

DATE 3/8/05

Type or print name

Jimmy Bagley

E-mail address:

Telephone No. 432 561-8600

(This space for State use)

APPROVED BY

OCD FIELD REPRESENTATIVE II, STAFF MANAGER

TITLE

DATE

Conditions of approval, if any:

MAR 22 2005

THE OIL CONSERVATION DIVISION MUST
BE NOTIFIED 24 HOURS PRIOR TO
BEGINNING OF PLUGGING OPERAT

PLUGGING & ABANDONMENT WORKSHEET

(3 STRING CSNG)

OPERATOR CHEVRON USA INC.
LEASENAME V.M. HENDERSON

SECT 30 TWN 21-S RNG 37-E
FROM 1660 NSL 6600 EWL
TD: 6750 FORMATION @ TD Deintara
PBDT: FORMATION @ PBDT GRAYBUEG

	SIZE	SET @	TOC	TOC DETERMINED BY
SURFACE	13 3/8	329	SURF	CIRC
INTMED 1	45/8	2999	SURF	CIRC
INTMED 2				
PROD	27 1/8	6749-48	2700	T.S
	SIZE	TOP	BOT	TOC DETERMINED BY
LINER 1		5264		
LINER 2				
	CUT & PULL @		TOP - BOTTOM	
INTMED 1			PREDS	5146 - 5151
INTMED 2			OPENHOLE	3660 - 3775
PROD		2700		

* REQUIRED PLUGS DISTRICT I

KUTLER (ANYTD)	
YATES	
QUEEN	
GRAYBUEG	
SAN ANDRES	
CAPTAIN BERRY	
DELAWARE	
BELL CANYON	
CHESEY CANYON	
BRUNY CANYON	
BONE SPRING	
GEORGETA	
GLADEBAY	
TUBS	
OLDHEAD	
ARO	
WC	
PRIN	
STRAWN	
ARDEA	
MOBROW	
ARM	
DEVONIAN	

PLUG	TYPE	BACKS	DEPTH
PLUG	PLUG	COUNT	
EXAMPLES			
PLUG #1	OH	25 SXS	9850'
PLUG #2	SHOE	50 SXS	8700'-8800'
PLUG #3	CIRP/35'		5300'
PLUG #4	CIRP	25 SXS	5300'
PLUG #5	STUB	50 SXS	4600'-4700'
PLUG #6	RETNR SQZ	200 SXS	400
PLUG #7	SURF	10 SXS	0-10'
PLUG #8	PRODCK	60	5100
PLUG #9	GRAYBUEG	25	3610
PLUG #10	PRODCK	60	5100
PLUG #11	STUB	100	2700
PLUG #12	T-SALT	75	1400
PLUG #13	13 3/8 S	75	375
PLUG #14	SURF	10	10
PLUG #15			
PLUG #16			
PLUG #17			
PLUG #18			
PLUG #19			
PLUG #20			
PLUG #21			
PLUG #22			
PLUG #23			
PLUG #24			
PLUG #25			

13 3/8
@ 329
TOC SURF

45/8
@ 2999
TOC SURF

27 1/8 x 3
5264 @ 6749-48
TOC 2700

TD 6750

