New Mexico Oil Conservation Division, District 1 1625 N. French Drive Hobbs, NM 88240

Form 3160-5 UNITED STATES (September 2001) DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT			FORM APPROVED OMB No. 1004-0135 Expires January 31, 2004 5. Lease Scrial No.	
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.				NMNM 04229C 6. If Indian, Allouce or Tribe Name
SUBMIT IN TRIPLICATE - Other instructions on reverse side				7. If Unit or CA/Agreement, Name and/or No.
1. Type of Well A Oil Well Gas Well Other				Little Eddy Unit 8. Well Name and No.
2. Name of Operator Rubicon Oil & Gas, LLC				Little Eddy Unit #6
3a. Address 508 West Wall AveSte.500 3b. Phone No. (Include area code)				9. API Well No. 30-025-32629
Midland, Texas 7970; 432/687-5100 4. Location of Well (Footage, Sec., T., R., M., or Survey Description)				10. Field and Pool, or Exploratory Area
Unit H - 2000' FNL & 880' FEL				Hat Mesa Delaware 11. County or Parish, State
Section 5, T21S, R32E				Lea County, New Mexico
12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA				
TYPE OF SUBMISSION TYPE OF ACTION SOGO.				
	☐ Acidize	Deepen	Production (Start	() 4/ 1.7 \
Notice of Intent	Alter Casing	Fracture Treat	Reclamation	age Say Men michity
Subsequent Report		New Construction	Recomplete	Other
Final Abandonment Notice	_ *	Plug and Abandon Plug Back	Temporarily Ab	andon v
0&G, LLC propose 1. Run tubing i 2. Load casing 3. Set cement p a. 25 sx "C b. 25 sx "C 4. Cut off and 5. Set cement p a. 50 sx "C b. 50 sx "C c. 20 sx "C 6. Cut off 11-3 top of 11-3/	s to plug and aban n hole to check fo with 9.0# mud thro lugs, through tubi "from 4680' - 458 "from 3250' - 315 pull 5-1/2" casing lugs, through tubi "from 2600'-2400' "from 60' to surf /4" & 8-5/8" casin 4" casing. Instal ation and re-seed	idon this well or CIBP and ce ough tubing. Ing, in 5-1/2" O'. Tag O 2500' (TOC) Ing, in 8-5/8" (1/2 in & 1/2 Tag Tag Tace. Ing at 3' below Ing dry hole ma	as follows: ment plug se casing as f @ 2616' TS) casing as f out of 5-1/ ground levers	ollows: MAR 14 2005 ollows: GARY GOURLEY 2" stub ETROLEUM ENGINEER 1 and weld steel plate over
Darol K. Ramey		Title	Agent	-
Signature	11/1	P-1-		
THIS SPACE FOR PEDERAL OR STATE OFFICE USE				
THIS SERVE FOR VEDERAL OR STATE OFFICE USE				
Approved by Conditions of approval, if any, are certify that the applicant holds lega which would entitle the applicant to or	l or equitable title to those rights	does not warrant or in the subject lease Off		Date
Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.				

(Instructions on reverse)

Ŧ



Little Eddy Unit #6 Rubicon Oil+Gas, Lhe Wellbore Diagram Completion Data Proposed Plugging 20 sx Plug - 60' to Surface -1134", 42# H-40, Setat 1400 Contact W/ 185 sy. Circ. 50 sx Phy - 1450'-1350' -2 R-111-plus { -TOC 2616 (Temp. Sura) 50 sx Plag-2600'-2400'-2 5/2" csg Cut of @ 2500'+" 8 %, "32 # WC-50, Setat 3197' 25Ax Pluf-3250-3150'-Z 25 mx plug - 4/680-4580' 2 DVTool @5991" 7% hole CIBP @ 6750'+ W/35' Comt Cop Personatrons-6811 to 8310. 5/2", 15.5 # K-55 Set@ 8412' Cmtd W/ 1060 5x in 25toger TD-8412'

22-141 22-142 22-144

AMPAD