Submit I Copy To Appropriate District Office State of New Mexico	Form C-103
District I Energy, Minerals and Natural Resources	October 13, 2009
1625 N French Dr , Hobbs, NM 8824 HOBBS OCD	WELL API NO.
District II 1301 W. Grand Ave, Artesia, NM 88210 OIL CONSERVATION DIVISION	30-025-40001
District III JUN 17 2011 1220 South St. Francis Dr.	5. Indicate Type of Lease
1000 Rio Brazos Rd , Aztec, NM 87410	STATE FEE
District IV 1220 S St Francis Dr, Santa Fe, NM	6. State Oil & Gas Lease No.
87505	VB-853
SUNDRY NOTICES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A	Zapata BQZ State Com
DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH	8. Well Number
PROPOSALS) 1. Type of Well: Oil Well Gas Well Other	1H
2. Name of Operator	9. OGRID Number
Yates Petroleum Corporation	025575
3. Address of Operator	10. Pool name or Wildcat
105 South Fourth Street, Artesia, NM 88210	Wildcat; Bone Spring
4. Well Location	, 1 2
Surface N : 330 feet from the South line and	2180 feet from the West line
BHL C 330 feet from the North Line and	1980 feet from the West line
	
Section 2 Township 26S Range 32E	NMPM Lea County
11. Elevation (Show whether DR, RKB, RT, GR, e	tc.)
3256'GR	The state of the s
12. Check Appropriate Box to Indicate Nature of Notice	e, Report or Other Data
	•
NOTICE OF INTENTION TO A SECOND AND A SECOND	JBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL W	
TEMPORARILY ABANDON CHANGE PLANS COMMENCE I	PAND A P
PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMI	ENT JOB
DOWNHOLE COMMINGLE "	ه الله الله الله الله الله الله الله ال
	and the second of the second o
OTHER: OTHER Surfa	
OTHER: OTHER: OTHER Surfa 13. Describe proposed or completed operations. (Clearly state all pertinent details,	and give pertinent dates, including estimated date
OTHER: OTHER Surfa OTHER Surfa OTHER Surfa Of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple 0	and give pertinent dates, including estimated date
OTHER: OTHER: OTHER Surfa 13. Describe proposed or completed operations. (Clearly state all pertinent details,	and give pertinent dates, including estimated date
OTHER: OTHER Surfactions. (Clearly state all pertinent details, of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple of proposed completion or recompletion.	and give pertinent dates, including estimated date Completions: Attach wellbore diagram of
OTHER: OTHER Surface 13. Describe proposed or completed operations. (Clearly state all pertinent details, of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple of proposed completion or recompletion. 5/30/11 – Set 40' of 20" conductor and cemented to surface with 50 sx redi-mix. Notified	and give pertinent dates, including estimated date Completions: Attach wellbore diagram of
OTHER: OTHER Surface 13. Describe proposed or completed operations. (Clearly state all pertinent details, of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple of proposed completion or recompletion. 5/30/11 – Set 40' of 20" conductor and cemented to surface with 50 sx redi-mix. Notified 6/7/11 – Resumed drilling at 4:30 PM.	and give pertinent dates, including estimated date Completions: Attach wellbore diagram of ed E.L. Gonzales NMOCD-Hobbs of operations.
OTHER: OTHER Surfa 13. Describe proposed or completed operations. (Clearly state all pertinent details, of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple oproposed completion or recompletion. 5/30/11 – Set 40° of 20" conductor and cemented to surface with 50 sx redi-mix. Notified 6/7/11 – Resumed drilling at 4:30 PM. 6/9/11 – TD 17-1/2" hole to 765°. Set 13-3/8" 48# J-55 ST&C casing at 765°. Cemente	and give pertinent dates, including estimated date Completions: Attach wellbore diagram of ed E.L. Gonzales NMOCD-Hobbs of operations. d with 430 sx Class "C" + 0.2% D046 + 0.125%
OTHER: OTHER Surfa 13. Describe proposed or completed operations. (Clearly state all pertinent details, of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple oproposed completion or recompletion. 5/30/11 – Set 40' of 20" conductor and cemented to surface with 50 sx redi-mix. Notified 6/7/11 – Resumed drilling at 4:30 PM. 6/9/11 – TD 17-1/2" hole to 765'. Set 13-3/8" 48# J-55 ST&C casing at 765'. Cemente D130 + 2% S001 + 4% D020 (yld 1.97, wt 12.9). Tailed in with 180 sx Class "C" + 0.15	and give pertinent dates, including estimated date Completions: Attach wellbore diagram of ed E.L. Gonzales NMOCD-Hobbs of operations. d with 430 sx Class "C" + 0.2% D046 + 0.125% 25#/sx D130 (yld 1.33, wt 14.8). Circulated 175
OTHER: OTHER Surfa 13. Describe proposed or completed operations. (Clearly state all pertinent details, of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple oproposed completion or recompletion. 5/30/11 – Set 40° of 20" conductor and cemented to surface with 50 sx redi-mix. Notified 6/7/11 – Resumed drilling at 4:30 PM. 6/9/11 – TD 17-1/2" hole to 765°. Set 13-3/8" 48# J-55 ST&C casing at 765°. Cemente	and give pertinent dates, including estimated date Completions: Attach wellbore diagram of ed E.L. Gonzales NMOCD-Hobbs of operations. d with 430 sx Class "C" + 0.2% D046 + 0.125% 25#/sx D130 (yld 1.33, wt 14.8). Circulated 175
OTHER: OTHER Surfa 13. Describe proposed or completed operations. (Clearly state all pertinent details, of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple oproposed completion or recompletion. 5/30/11 – Set 40' of 20" conductor and cemented to surface with 50 sx redi-mix. Notified 6/7/11 – Resumed drilling at 4:30 PM. 6/9/11 – TD 17-1/2" hole to 765'. Set 13-3/8" 48# J-55 ST&C casing at 765'. Cemente D130 + 2% S001 + 4% D020 (yld 1.97, wt 12.9). Tailed in with 180 sx Class "C" + 0.15	and give pertinent dates, including estimated date Completions: Attach wellbore diagram of ed E.L. Gonzales NMOCD-Hobbs of operations. d with 430 sx Class "C" + 0.2% D046 + 0.125% 25#/sx D130 (yld 1.33, wt 14.8). Circulated 175
OTHER: OTHER Surfa 13. Describe proposed or completed operations. (Clearly state all pertinent details, of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple oproposed completion or recompletion. 5/30/11 – Set 40' of 20" conductor and cemented to surface with 50 sx redi-mix. Notified 6/7/11 – Resumed drilling at 4:30 PM. 6/9/11 – TD 17-1/2" hole to 765'. Set 13-3/8" 48# J-55 ST&C casing at 765'. Cemente D130 + 2% S001 + 4% D020 (yld 1.97, wt 12.9). Tailed in with 180 sx Class "C" + 0.15	and give pertinent dates, including estimated date Completions: Attach wellbore diagram of ed E.L. Gonzales NMOCD-Hobbs of operations. d with 430 sx Class "C" + 0.2% D046 + 0.125% 25#/sx D130 (yld 1.33, wt 14.8). Circulated 175
OTHER: OTHER Surfa 13. Describe proposed or completed operations. (Clearly state all pertinent details, of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple oproposed completion or recompletion. 5/30/11 – Set 40' of 20" conductor and cemented to surface with 50 sx redi-mix. Notified 6/7/11 – Resumed drilling at 4:30 PM. 6/9/11 – TD 17-1/2" hole to 765'. Set 13-3/8" 48# J-55 ST&C casing at 765'. Cemente D130 + 2% S001 + 4% D020 (yld 1.97, wt 12.9). Tailed in with 180 sx Class "C" + 0.15	and give pertinent dates, including estimated date Completions: Attach wellbore diagram of ed E.L. Gonzales NMOCD-Hobbs of operations. d with 430 sx Class "C" + 0.2% D046 + 0.125% 25#/sx D130 (yld 1.33, wt 14.8). Circulated 175
OTHER: OTHER Surfa 13. Describe proposed or completed operations. (Clearly state all pertinent details, of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple oproposed completion or recompletion. 5/30/11 – Set 40' of 20" conductor and cemented to surface with 50 sx redi-mix. Notified 6/7/11 – Resumed drilling at 4:30 PM. 6/9/11 – TD 17-1/2" hole to 765'. Set 13-3/8" 48# J-55 ST&C casing at 765'. Cemente D130 + 2% S001 + 4% D020 (yld 1.97, wt 12.9). Tailed in with 180 sx Class "C" + 0.15	and give pertinent dates, including estimated date Completions: Attach wellbore diagram of ed E.L. Gonzales NMOCD-Hobbs of operations. d with 430 sx Class "C" + 0.2% D046 + 0.125% 25#/sx D130 (yld 1.33, wt 14.8). Circulated 175
OTHER: OTHER Surfa 13. Describe proposed or completed operations. (Clearly state all pertinent details, of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple oproposed completion or recompletion. 5/30/11 – Set 40' of 20" conductor and cemented to surface with 50 sx redi-mix. Notified 6/7/11 – Resumed drilling at 4:30 PM. 6/9/11 – TD 17-1/2" hole to 765'. Set 13-3/8" 48# J-55 ST&C casing at 765'. Cemente D130 + 2% S001 + 4% D020 (yld 1.97, wt 12.9). Tailed in with 180 sx Class "C" + 0.15	and give pertinent dates, including estimated date Completions: Attach wellbore diagram of ed E.L. Gonzales NMOCD-Hobbs of operations. d with 430 sx Class "C" + 0.2% D046 + 0.125% 25#/sx D130 (yld 1.33, wt 14.8). Circulated 175
OTHER: OTHER Surfa 13. Describe proposed or completed operations. (Clearly state all pertinent details, of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple oproposed completion or recompletion. 5/30/11 – Set 40' of 20" conductor and cemented to surface with 50 sx redi-mix. Notified 6/7/11 – Resumed drilling at 4:30 PM. 6/9/11 – TD 17-1/2" hole to 765'. Set 13-3/8" 48# J-55 ST&C casing at 765'. Cemente D130 + 2% S001 + 4% D020 (yld 1.97, wt 12.9). Tailed in with 180 sx Class "C" + 0.15	and give pertinent dates, including estimated date Completions: Attach wellbore diagram of ed E.L. Gonzales NMOCD-Hobbs of operations. d with 430 sx Class "C" + 0.2% D046 + 0.125% 25#/sx D130 (yld 1.33, wt 14.8). Circulated 175
OTHER: OTHER: Surfa 13. Describe proposed or completed operations. (Clearly state all pertinent details, of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple oproposed completion or recompletion. 5/30/11 – Set 40° of 20" conductor and cemented to surface with 50 sx redi-mix. Notified 6/7/11 – Resumed drilling at 4:30 PM. 6/9/11 – TD 17-1/2" hole to 765°. Set 13-3/8" 48# J-55 ST&C casing at 765°. Cemente D130 + 2% S001 + 4% D020 (yld 1.97, wt 12.9). Tailed in with 180 sx Class "C" + 0.15 sx to pit. Tested casing to 600 psi. WOC 26 hrs 25 min. Reduced hole to 12-1/4" and resumed to the start of the sta	and give pertinent dates, including estimated date Completions: Attach wellbore diagram of ed E.L. Gonzales NMOCD-Hobbs of operations. d with 430 sx Class "C" + 0.2% D046 + 0.125% 25#/sx D130 (yld 1.33, wt 14.8). Circulated 175
OTHER: OTHER Surfa 13. Describe proposed or completed operations. (Clearly state all pertinent details, of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple oproposed completion or recompletion. 5/30/11 – Set 40' of 20" conductor and cemented to surface with 50 sx redi-mix. Notified 6/7/11 – Resumed drilling at 4:30 PM. 6/9/11 – TD 17-1/2" hole to 765'. Set 13-3/8" 48# J-55 ST&C casing at 765'. Cemente D130 + 2% S001 + 4% D020 (yld 1.97, wt 12.9). Tailed in with 180 sx Class "C" + 0.15	and give pertinent dates, including estimated date Completions: Attach wellbore diagram of ed E.L. Gonzales NMOCD-Hobbs of operations. d with 430 sx Class "C" + 0.2% D046 + 0.125% 25#/sx D130 (yld 1.33, wt 14.8). Circulated 175
OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple oproposed completion or recompletion. 5/30/11 – Set 40' of 20" conductor and cemented to surface with 50 sx redi-mix. Notified 6/7/11 – Resumed drilling at 4:30 PM. 6/9/11 – TD 17-1/2" hole to 765'. Set 13-3/8" 48# J-55 ST&C casing at 765'. Cemente D130 + 2% S001 + 4% D020 (yld 1.97, wt 12.9). Tailed in with 180 sx Class "C" + 0.11 sx to pit. Tested casing to 600 psi. WOC 26 hrs 25 min. Reduced hole to 12-1/4" and reduced hole to 12-1/4" and reduced hole to 12-1/4".	and give pertinent dates, including estimated date Completions: Attach wellbore diagram of ed E.L. Gonzales NMOCD-Hobbs of operations. d with 430 sx Class "C" + 0.2% D046 + 0.125% 25#/sx D130 (yld 1.33, wt 14.8). Circulated 175
OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple oproposed completion or recompletion. 5/30/11 – Set 40' of 20" conductor and cemented to surface with 50 sx redi-mix. Notified 6/7/11 – Resumed drilling at 4:30 PM. 6/9/11 – TD 17-1/2" hole to 765'. Set 13-3/8" 48# J-55 ST&C casing at 765'. Cemente D130 + 2% S001 + 4% D020 (yld 1.97, wt 12.9). Tailed in with 180 sx Class "C" + 0.11 sx to pit. Tested casing to 600 psi. WOC 26 hrs 25 min. Reduced hole to 12-1/4" and reduced hole to 12-1/4" and reduced hole to 12-1/4".	and give pertinent dates, including estimated date Completions: Attach wellbore diagram of ed E.L. Gonzales NMOCD-Hobbs of operations. d with 430 sx Class "C" + 0.2% D046 + 0.125% 25#/sx D130 (yld 1.33, wt 14.8). Circulated 175
OTHER: Surfa 13. Describe proposed or completed operations. (Clearly state all pertinent details, of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple oproposed completion or recompletion. 5/30/11 – Set 40' of 20" conductor and cemented to surface with 50 sx redi-mix. Notified 6/7/11 – Resumed drilling at 4:30 PM. 6/9/11 – TD 17-1/2" hole to 765'. Set 13-3/8" 48# J-55 ST&C casing at 765'. Cemente D130 + 2% S001 + 4% D020 (yld 1.97, wt 12.9). Tailed in with 180 sx Class "C" + 0.15 sx to pit. Tested casing to 600 psi. WOC 26 hrs 25 min. Reduced hole to 12-1/4" and results and results are results. Spud Date: 1/31/11 Rig Release Date:	and give pertinent dates, including estimated date Completions: Attach wellbore diagram of ad E.L. Gonzales NMOCD-Hobbs of operations. d with 430 sx Class "C" + 0.2% D046 + 0.125% 25#/sx D130 (yld 1.33, wt 14.8). Circulated 175 esumed drilling.
OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple oproposed completion or recompletion. 5/30/11 – Set 40' of 20" conductor and cemented to surface with 50 sx redi-mix. Notified 6/7/11 – Resumed drilling at 4:30 PM. 6/9/11 – TD 17-1/2" hole to 765'. Set 13-3/8" 48# J-55 ST&C casing at 765'. Cemente D130 + 2% S001 + 4% D020 (yld 1.97, wt 12.9). Tailed in with 180 sx Class "C" + 0.11 sx to pit. Tested casing to 600 psi. WOC 26 hrs 25 min. Reduced hole to 12-1/4" and reduced hole to 12-1/4" and reduced hole to 12-1/4".	and give pertinent dates, including estimated date Completions: Attach wellbore diagram of ad E.L. Gonzales NMOCD-Hobbs of operations. d with 430 sx Class "C" + 0.2% D046 + 0.125% 25#/sx D130 (yld 1.33, wt 14.8). Circulated 175 esumed drilling.
OTHER: OTHER Surfa 13. Describe proposed or completed operations. (Clearly state all pertinent details, of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple of proposed completion or recompletion. 5/30/11 – Set 40' of 20" conductor and cemented to surface with 50 sx redi-mix. Notified 6/7/11 – Resumed drilling at 4:30 PM. 6/9/11 – TD 17-1/2" hole to 765'. Set 13-3/8" 48# J-55 ST&C casing at 765'. Cemente D130 + 2% S001 + 4% D020 (yld 1.97, wt 12.9). Tailed in with 180 sx Class "C" + 0.1 sx to pit. Tested casing to 600 psi. WOC 26 hrs 25 min. Reduced hole to 12-1/4" and results of the state of the best of my knowledge of the best of the best of my knowledge of the best o	and give pertinent dates, including estimated date Completions: Attach wellbore diagram of ad E.L. Gonzales NMOCD-Hobbs of operations. d with 430 sx Class "C" + 0.2% D046 + 0.125% 25#/sx D130 (yld 1.33, wt 14.8). Circulated 175 esumed drilling.
OTHER: OTHER Surfa 13. Describe proposed or completed operations. (Clearly state all pertinent details, of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple of proposed completion or recompletion. 5/30/11 – Set 40' of 20" conductor and cemented to surface with 50 sx redi-mix. Notified 6/7/11 – Resumed drilling at 4:30 PM. 6/9/11 – TD 17-1/2" hole to 765'. Set 13-3/8" 48# J-55 ST&C casing at 765'. Cemente D130 + 2% S001 + 4% D020 (yld 1.97, wt 12.9). Tailed in with 180 sx Class "C" + 0.1 sx to pit. Tested casing to 600 psi. WOC 26 hrs 25 min. Reduced hole to 12-1/4" and results of the state of the best of my knowledge of the best of the best of my knowledge of the best o	and give pertinent dates, including estimated date Completions: Attach wellbore diagram of ad E.L. Gonzales NMOCD-Hobbs of operations. d with 430 sx Class "C" + 0.2% D046 + 0.125% 25#/sx D130 (yld 1.33, wt 14.8). Circulated 175 esumed drilling.
OTHER: OTHER Surface 13. Describe proposed or completed operations. (Clearly state all pertinent details, of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple of proposed completion or recompletion. 5/30/11 – Set 40' of 20" conductor and cemented to surface with 50 sx redi-mix. Notifice 6/7/11 – Resumed drilling at 4:30 PM. 6/9/11 – TD 17-1/2" hole to 765'. Set 13-3/8" 48# J-55 ST&C casing at 765'. Cemente D130 + 2% S001 + 4% D020 (yld 1.97, wt 12.9). Tailed in with 180 sx Class "C" + 0.1 sx to pit. Tested casing to 600 psi. WOC 26 hrs 25 min. Reduced hole to 12-1/4" and resumed to the best of my knowless true and complete to the best of my knowless true. I hereby certify that the information above is true and complete to the best of my knowless true. TITLERegulatory Compliant.	and give pertinent dates, including estimated date Completions: Attach wellbore diagram of ad E.L. Gonzales NMOCD-Hobbs of operations. d with 430 sx Class "C" + 0.2% D046 + 0.125% 25#/sx D130 (yld 1.33, wt 14.8). Circulated 175 esumed drilling. dge and belief. ce Supervisor DATE June 15, 2011
OTHER: OTHER Surface 13. Describe proposed or completed operations. (Clearly state all pertinent details, of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple of proposed completion or recompletion. 5/30/11 – Set 40' of 20" conductor and cemented to surface with 50 sx redi-mix. Notified 6/7/11 – Resumed drilling at 4:30 PM. 6/9/11 – TD 17-1/2" hole to 765'. Set 13-3/8" 48# J-55 ST&C casing at 765'. Cemente D130 + 2% S001 + 4% D020 (yld 1.97, wt 12.9). Tailed in with 180 sx Class "C" + 0.1 sx to pit. Tested casing to 600 psi. WOC 26 hrs 25 min. Reduced hole to 12-1/4" and results of the state of the set of my knowledge of the state of the set of my knowledge of the state of the set of my knowledge of the state of the set of my knowledge of the state of the set of my knowledge of the state of the set of my knowledge of the state of the set of my knowledge of the state of the set of my knowledge of the state of the set of my knowledge of the state of the set of my knowledge of the state of the set of my knowledge of the state of the set of my knowledge of the state of the set of my knowledge of the state of the set of my knowledge of the state of the set of my knowledge of the set of the set of my knowledge of the set of the	and give pertinent dates, including estimated date Completions: Attach wellbore diagram of ad E.L. Gonzales NMOCD-Hobbs of operations. d with 430 sx Class "C" + 0.2% D046 + 0.125% 25#/sx D130 (yld 1.33, wt 14.8). Circulated 175 esumed drilling. dge and belief. ce Supervisor DATE
OTHER: OTHER Surface 13. Describe proposed or completed operations. (Clearly state all pertinent details, of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple of proposed completion or recompletion. 5/30/11 – Set 40' of 20" conductor and cemented to surface with 50 sx redi-mix. Notifice 6/7/11 – Resumed drilling at 4:30 PM. 6/9/11 – TD 17-1/2" hole to 765'. Set 13-3/8" 48# J-55 ST&C casing at 765'. Cemente D130 + 2% S001 + 4% D020 (yld 1.97, wt 12.9). Tailed in with 180 sx Class "C" + 0.1 sx to pit. Tested casing to 600 psi. WOC 26 hrs 25 min. Reduced hole to 12-1/4" and resumed to the best of my knowless true and complete to the best of my knowless true. I hereby certify that the information above is true and complete to the best of my knowless true. TITLERegulatory Compliant.	and give pertinent dates, including estimated date Completions: Attach wellbore diagram of ad E.L. Gonzales NMOCD-Hobbs of operations. d with 430 sx Class "C" + 0.2% D046 + 0.125% 25#/sx D130 (yld 1.33, wt 14.8). Circulated 175 esumed drilling. dge and belief. ce Supervisor DATE June 15, 2011 eum.com PHONE: 575-748-4168
OTHER: OTHER Surface 13. Describe proposed or completed operations. (Clearly state all pertinent details, of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple of proposed completion or recompletion. 5/30/11 – Set 40' of 20" conductor and cemented to surface with 50 sx redi-mix. Notified 6/7/11 – Resumed drilling at 4:30 PM. 6/9/11 – TD 17-1/2" hole to 765'. Set 13-3/8" 48# J-55 ST&C casing at 765'. Cemente D130 + 2% S001 + 4% D020 (yld 1.97, wt 12.9). Tailed in with 180 sx Class "C" + 0.1 sx to pit. Tested casing to 600 psi. WOC 26 hrs 25 min. Reduced hole to 12-1/4" and results of the state of the set of my knowledge of the state of the set of my knowledge of the state of the set of my knowledge of the state of the set of my knowledge of the state of the set of my knowledge of the state of the set of my knowledge of the state of the set of my knowledge of the state of the set of my knowledge of the state of the set of my knowledge of the state of the set of my knowledge of the state of the set of my knowledge of the state of the set of my knowledge of the state of the set of my knowledge of the state of the set of my knowledge of the state of the set of my knowledge of the set of the set of my knowledge of the set of the	and give pertinent dates, including estimated date Completions: Attach wellbore diagram of ad E.L. Gonzales NMOCD-Hobbs of operations. d with 430 sx Class "C" + 0.2% D046 + 0.125% 25#/sx D130 (yld 1.33, wt 14.8). Circulated 175 esumed drilling. dge and belief. ce Supervisor DATE June 15, 2011
OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple oproposed completion or recompletion. 5/30/11 – Set 40' of 20" conductor and cemented to surface with 50 sx redi-mix. Notifice 6/7/11 – Resumed drilling at 4:30 PM. 6/9/11 – TD 17-1/2" hole to 765'. Set 13-3/8" 48# J-55 ST&C casing at 765'. Cemente D130 + 2% S001 + 4% D020 (yld 1.97, wt 12.9). Tailed in with 180 sx Class "C" + 0.1 sx to pit. Tested casing to 600 psi. WOC 26 hrs 25 min. Reduced hole to 12-1/4" and resumed from the information above is true and complete to the best of my knowledge SIGNATURE Type or print name Tina Huerta E-mail address: tinah@yatespetrolefor State Use Only	and give pertinent dates, including estimated date Completions: Attach wellbore diagram of ad E.L. Gonzales NMOCD-Hobbs of operations. d with 430 sx Class "C" + 0.2% D046 + 0.125% 25#/sx D130 (yld 1.33, wt 14.8). Circulated 175 esumed drilling. dge and belief. ce Supervisor DATE June 15, 2011 eum.com PHONE: 575-748-4168
OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple oproposed completion or recompletion. 5/30/11 – Set 40' of 20" conductor and cemented to surface with 50 sx redi-mix. Notifie 6/7/11 – Resumed drilling at 4:30 PM. 6/9/11 – TD 17-1/2" hole to 765'. Set 13-3/8" 48# J-55 ST&C casing at 765'. Cemente D130 + 2% S001 + 4% D020 (yld 1.97, wt 12.9). Tailed in with 180 sx Class "C" + 0.1 sx to pit. Tested casing to 600 psi. WOC 26 hrs 25 min. Reduced hole to 12-1/4" and results of the set of my knowless of the set of the set of my knowless of the set of the set of my knowless of the set of the set of my knowless of the set of the set of my knowless of the set of the set of my knowless of the set of the set of my knowless of the set of the set of my knowless of the set of the set of the set of my knowless of the set of the set of my knowless of the set of the set of the set of my knowless of the set of the set of the set of my knowless of the set of the set of the set of my knowless of the set of the set of my knowless of the set of the set of my knowless of the set of the set of my knowless of the set of the set of my knowless of the set of the set of my knowless of the set of the set of my knowless of the set of my knowless of the set of my knowless of the set of the se	and give pertinent dates, including estimated date Completions: Attach wellbore diagram of ad E.L. Gonzales NMOCD-Hobbs of operations. d with 430 sx Class "C" + 0.2% D046 + 0.125% 25#/sx D130 (yld 1.33, wt 14.8). Circulated 175 esumed drilling. dge and belief. ce Supervisor DATE June 15, 2011 eum.com PHONE: 575-748-4168