

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

JUL 07 2011

FORM APPROVED
OMB No 1004-0137
Expires March 31, 2007

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.**SUBMIT IN TRIPLICATE- Other instructions on reverse side.**1. Type of Well
☒ Oil Well ☐ Gas Well ☐ Other2. Name of Operator **ConocoPhillips Company Attn: Donna Williams**3a Address
3300 N. "A" St, Bldg 6 Midland, TX 797053b Phone No (include area code)
432-688-6913

4 Location of Well (Footage, Sec., T., R., M., or Survey Description)

**1980' FSL, 660' FEL
Sec 26, T-20-S, R-37-E, Unit "I"**

5. Lease Serial No.

LC 031696A

6 If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or No

8 Well Name and No.

SEMU #147

9. API Well No

30-025-34978

10 Field and Pool, or Exploratory Area

North Hardy Tubb-Drinkard

11 County or Parish, State

Lea County, New Mexico

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

☒ Notice of Intent☐ Subsequent Report☐ Final Abandonment Notice☐ Acidize☐ Alter Casing☐ Casing Repair☐ Change Plans☐ Convert to Injection☐ Deepen☐ Fracture Treat☐ New Construction☒ Plug and Abandon☐ Plug Back☐ Production (Start/Resume)☐ Reclamation☐ Recomplete☐ Temporarily Abandon☐ Water Disposal☐ Water Shut-Off☐ Well Integrity☐ Other

13 Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleate horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleation in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

1. MIRU, ND WH, NU BOP, POOH & LD Rods & Tbg.

2. RIH WL - Set 5 1/2" CIBP @ 6,396'. RIH Tbg to 6,396' - Circ hole w/ MLF. Cap BP w/ 25sx cmt.

3. Spot 25sx cmt @ 5,883' - 5,683'

4. Spot 25sx cmt @ 5,266' - 5,066'

5. Spot 25sx cmt @ 4,163' - 3,940' - WOC-TAG

6. Spot 35sx cmt @ 3,754' - 3,446' - WOC-TAG

7. Spot 50sx cmt @ 2,938' - 2,493' - WOC-TAG

8. Spot 30sx cmt @ 1,570' - 1,350' - WOC-TAG

9. Perf @ 60' - Circ 30sx cmt to surface

10. Fill wellbore. RDMO

**RECLAMATION PROCEDURE
ATTACHED****SEE ATTACHED FOR
CONDITIONS OF APPROVAL**14. I hereby certify that the foregoing is true and correct
Name (Printed/Typed)**Greg Bryant**Title **P&A Tech**

Signature

Date

04/11/2011**THIS SPACE FOR FEDERAL OR STATE OFFICE USE**

Approved by

Title

Date

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

WELLBORE SKETCH
ConocoPhillips Company -- Lower 48 - Mid-Continent BU / Permian Operations

Date Apr. 4, 2011

RKB @ 3521'
 DF @ 3520'
 GL @ 3510'

Subarea Hobbs
 Lease & Well No SEMU No. 147
 Legal Description 1980' FSL & 660' FEL, Sec 26, T20S, R37E, UL "I"
 County Lea State New Mexico
 Field North Hardy Tubb-Drnkard
 Spud 5/20/00 Rig Released 6/1/00
 API Number 30-025-34978
 Status: _____
 Lse Serial No. LC 031696(A)

Stimulation History:

Interval	Date	Type	Gals	Lbs. Sand	Max Press	ISIP	Max Rate	Down
	6/17/00	Run CBL, TOC @ 200'						
	6/19/00	Perforate Abo w/ 2 SPF @ 7166-7234; total 107 holes						
7166-7234	6/20/00	20% NEFE HCl	4,000		5000	3500	5.0	5-1/2"
	6/22/00	Set 5-1/2" CIBP @ 7130' w/ 35' cmt (3 sx)						
	6/23/00	Perforate San Andres w/ 2 SPF @ 3986-4000, 4044-4050, 4068-4076 and 4096-4106						
3986-4106	6/24/00	15% NEFE HCl	3,000	120 BS	2000	1200		
	12/5/00	Squeeze San Andres 3986-4106 w/ 65x						
	12/7/00	Perforate Tubb w/ 2 SPF @ 6496-6657						
6496-6657	12/11/00	15% NEFE HCl	4,000	300 BS	3250	2300	6.5	
6496-6657	12/12/00	Spectra G	56,000	158,260	6670	2800	35.0	
	8/27/02	RIH w/ new pump						
6496-6657	8/30/07	Xylene	500					
		15% HCl	2,000				2.5	

12-1/4" Hole

TOC 5-1/2" Csg @ 200' (CBL)

8-5/8" 24# J-55 @ 1520'

Cmt'd w/ 723 sx, circ 131 sx

TOC @ Surface

Top Salt @ 1400'

Base Salt @ 2650'

San Andres

3986-4000 4044-4050 }

4068-4076 4096-4106 } Sqz'd w/ 65 sx
 DV Tool @ 4113'

Tubb

6496-6505 6510-6512

6516-6528 6552-6560

6566-6575 6578-6584

6588-6592 6600-6604

6621-6628 6638-6651

6654-6657

EOT @ 6661'

CIBP @ 7130' w/ 3 sx cmt; TOC @ 7095'

7166-7192 7202-7208

7214-7234

7-7/8" Hole

5-1/2" 17# J-55 @ 7400'

Stage 1 Cmt. 565 sx, circ 40 bbls

Stage 2 Cmt. 1060 sx, circ 121 sx

TOC @ 200' (CBL)

PBTD @ 7095'
 TD @ 7400'

Formation Tops:

Tansil	2543'		
Yates	2682'	Gloneta	5266'
7 Rivers	2938'	Blinbry Mkr	5883'
Queen	3496'	Tubb Mkr	6398'
Penrose	3620'	Drnkard	6718'
Grayburg	3754'	Abo	7000'
San Andres	3990'		

WELLBORE SKETCH
ConocoPhillips Company -- Lower 48 - Mid-Continent BU / Permian Operations

Date, Apr. 4, 2011

RKB @ 3521'
 DF @ 3520'
 GL @ 3510'

12-1/4" Hole
 P&S 30sx cmt @ 60'-surface
 TOC 5-1/2" Csg @ 200' (CBL)

Spot 30sx cmt @ 1570'-1350' - TAG
 8-5/8" 24# J-55 @ 1520'
 Cmt'd w/ 723 sx, circ 131 sx
 TOC @ Surface
 Top Salt @ 1400'

Spot 50sx cmt @ 2938'-2493' - TAG
 Base Salt @ 2550'

Spot 35sx cmt @ 3754'-3448' - TAG

San Andres
 3986-4000 4044-4050 }
 4088-4076 4096-4106 } Sqz'd w/ 65 sx
 DV Tool @ 4113'
 Spot 25sx cmt @ 4163'-3940' - TAG

Spot 25sx cmt @ 5266'-5066'

Spot 25sx cmt @ 5883'-5683'

Cap BP w/ 25sx cmt @ 6396'-6196'
 CIBP @ 6396'
Tubb
 6496-6505 6510-6512
 6516-6528 6552-6560
 6566-6575 6578-6584
 6588-6592 6600-6604
 6621-6628 6638-6651
 6654-6657
 EOT @ 6661'

CIBP @ 7130' w/ 3 sx cmt, TOC @ 7095'
 7166-7192 7202-7208
 7214-7234

7-7/8" Hole
 5-1/2" 17# J-55 @ 7400'
 Stage 1 Cmt 565 sx, circ 40 bbls
 Stage 2 Cmt 1060 sx, circ 121 sx
 TOC @ 200' (CBL)

PBTD @ 7095'
 TD @ 7400'

Subarea : Hobbs
 Lease & Well No. SEMU No. 147
 Legal Description 1980' FSL & 660' FEL, Sec 26, T20S, R37E, UL "I"
 County Lea State New Mexico
 Field North Hardy Tubb-Drnkard
 Spud 5/20/00 Rig Released 6/1/00
 API Number 30-025-34978
 Status Lse Serial No. LC 031696(A)

Stimulation History:

Interval	Date	Type	Gals	Lbs. Sand	Max Press	ISIP	Max Rate	Max Down
	6/17/00	Run CBL, TOC @ 200'						
	6/19/00	Perforate Abo w/ 2 SPF @ 7166-7234; total 107 holes						
7166-7234	6/20/00	20% NEFE HCl	4,000		5000	3500	5.0	5-1/2"
	6/22/00	Set 5-1/2" CIBP @ 7130' w/ 35' cmt (3 sx)						
	6/23/00	Perforate San Andres w/ 2 SPF @ 3986-4000, 4044-4050, 4088-4076 and 4096-4106						
3986-4106	6/24/00	15% NEFE HCl	3,000	120 BS	2000	1200		
	12/5/00	Squeeze San Andres 3986-4106 w/ 65x						
	12/7/00	Perforate Tubb w/ 2 SPF @ 6496-6657						
6496-6657	12/11/00	15% NEFE HCl	4,000	300 BS	3250	2300	6.5	
6496-6657	12/12/00	Spectra G	56,000	158,260	6670	2800	35.0	
	8/27/02	RIH w/ new pump						
6496-6657	8/30/07	Xylene	500					
		15% HCl	2,000				2.5	

Formation Tops:

Tansil	2543'		
Yates	2682'	Glorieta	5266'
7 Rivers	2938'	Blinberry Mkr	5883'
Queen	3496'	Tubb Mkr	6398'
Penrose	3620'	Drnkard	6718'
Grayburg	3754'	Abo	7000'
San Andres	3990'		

Well Header

Doc. No.	00LA0112A		API No	3002534978		00	S2	APD Type	APD		Received Date	03/02/2000					
Well Name	SEMUR BURGER		Number	147				Proprietary			Exp. Date						
Customer No.			Change Effective Date			District			HOBBS INSPECTION OFFICE								
Name	CONOCO INCORPORATED					Case Number	Type	Lse Type	Case Name								
City	MIDLAND		State	TX		Lease	NMLC031696A		311111	P	SEMUR BURGER						
Phone	915 686.5424		Ext			Agrmt	NMNM71041L		318230	SE MONUMENT - TB-D							
Contact						Reservation						Well Type	OIL	Exp/Dev	DEV		
Phone						Allottee						Status	POW	Eff	12/18/2000		
Bond						Fields/Pools	NORTH HARDY					MMS Office Code	HO				
						Formations	TUBB-DRINKARD					Res Area	NM081				
												SME	BLM				
Depths	Meas	Proposed True	Meas	Actual True		State	Meridian	Survey	Rectangular Survey		NAD83						
Surface			7400	7400		NM	NMP										
Entry Pt																	
Exit Pt																	
Kick Off Pt																	
Bottom																	
Location Type	LEA	Twp	20S	Range	37E	Sec	26	Aliquot	NESE	NS-foot	1980FSL	EW-foot	660FEL	Latitude	Longitude	Lot	Tract
Surface																	
Entry Pt																	
Exit Pt																	
Kick Off Pt																	
Bottom																	

BC 111125

BUREAU OF LAND MANAGEMENT
Carlsbad Field Office
620 East Greene Street
Carlsbad, New Mexico 88220
575-234-5972

**Permanent Abandonment of Federal Wells
Conditions of Approval**

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within ninety (90) days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90th day provide this office, prior to the 90th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

2. Notification: Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.

3. Blowout Preventers: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.

4. Mud Requirement: Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of brine water. Minimum nine (9) pounds per gallon.

5. Cement Requirement: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. **Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.**

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. Dry Hole Marker: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). **The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10th day, the BLM is to be contacted with justification to receive an extension for completing the cut off.**

The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement, unless otherwise noted in COA (requirements will be attached). The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).

7. Subsequent Plugging Reporting: Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.**

8. Trash: All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation procedure.

J. Amos 3/6/11



United States Department of the Interior

BUREAU OF LAND MANAGEMENT

Carlsbad Field Office
620 E. Greene St.
Carlsbad, New Mexico 88220-6292
www.blm.gov/nm



In Reply Refer To: 1310

Reclamation Objectives and Procedures

Reclamation Objective: Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its pre-disturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any and all contaminants, scrap/trash, equipment, pipelines and powerlines. Strip and remove caliche, contour the location to blend with the surrounding landscape, re-distribute the native soils, provide erosion control as needed, rip and seed as specified in the original APD COA. This will apply to well pads, facilities, and access roads. Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

1. The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of Operations must include adequate measures for stabilization and reclamation of disturbed lands. Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD process as per Onshore Oil and Gas Order No. 1.
2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months of well abandonment.
3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.
4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation

equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.

5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos
Supervisory Environmental Protection Specialist
575-234-5909, 575-361-2648 (Cell)

Cody Layton
Natural Resource Specialist
575-234-5959

Terry Gregston
Environmental Protection Specialist
575-234-5958

Trishia Bad Bear
Natural Resource Specialist
575-393-3612

Bobby Ballard
Environmental Protection Specialist
575-234-2230

Todd Suter
Surface Protection Specialist
575-234-5987

Randy Rust
Environmental Protection Specialist
575-234-5943

Doug Hoag
Civil Engineering Technician
575-234-5979

Linda Denniston
Environmental Protection Specialist
575-234-5974

Jennifer Van Curen
Environmental Protection Specialist
575-234-5905

Justin Frye
Environmental Protection Specialist
575-234-5922