New Mexico Oil Conservation Division, District I						
	Image: Work and the second states Image: Work and the second states Image: Work and the second states Image: Work and the second states Image: Work and the second states Image: Work and the second states Image: Work and the second states Image: Work and the second states Image: Work and the second states Image: Work and the second states Image: Work and the second states Image: Work and the second states Image: Work and the second states Image: Work and the second states Image: Work and the second states Image: Work and the second states Image: Work and the second states Image: Work and the second states Image: Work and the second states Image: Work and the second states Image: Work and the second states Image: Work and the second states Image: Work and the second states Image: Work and the second states Image: Work and the second states Image: Work and the second states Image: Work and the second states Image: Work and the second states Image: Work and the second states Image: Work and the second states Image: Work and the second states Image: Work and the second states Image: Work and the second states Image: Work and the second states Image: Work and the second states Image: Work and the second states Image: Work and the sec				e FC ON	DRM APPROVED MB No. 1004-0137 res: March 31, 2007
BOREAU OF LAND MANAGEMENT HOBBS OCD					5. Lease Serial No. NM 23018	
SUNDRY NOTICES AND REPORTS ON WELLS RECOVER use this form for proposals to drill or to re-shier and 2011 abandoned well. Use Form 3160-3 (APD) for such proposals.				6. If Indian, Allottee or	Tribe Name	
SUBMIT IN TRIPLICATE – Other instructions on page RECEIVED					7. If Unit of CA/Agreement, Name and/or No.	
Oil Well 🔽 Gas V	Vell Other	/			8. Well Name and No. Federal "J" No.1	
2. Name of Operator H. L. Brown Operating, L.L.C.	/				9. API Well No. 30-041-20505	
3a. Address P. O. Box 2237		Bb. Phone No	. (include area cod	le)	10. Field and Pool or Ex	
Midland, TX 79702 432 4. Location of Well (Footage, Sec., T.,R.,M., or Survey Description) 1650' FN & EL Sec 10 1650' FN & EL Sec 10			5216		Bluitt San Andres (Gas)	
1650' FN & EL Sec 10 T-8-S, R-37-E			Roosevelt County, NM			
12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA						
TYPE OF SUBMISSION TYPE OF ACTION						······································
Notice of Intent	Acidize		en ture Treat		iction (Start/Resume)	Water Shut-Off
Subsequent Report	Casing Repair		Construction	=	mation mplete	Well Integrity
	Change Plans		and Abandon		orarily Abandon	
Final Abandonment Notice	Convert to Injection	Plug			Disposal	
determined that the site is ready for final inspection.) 6-09-11: After consultantion with BLM offices in Roswell and Hobbs, approval has been granted to pump 150sxs cement below packer set @ 1885' and displace cement down to leave top of plug at 2000'. Bottom of cement plug will be below 4-1/2" casing stub at 2464! The original plugging procedure will then resume to set a test cement plug across 12-3/4" shoe from set to set Tage ± 381' Set 205X. Surface Plug Will Monument.						
APPROVED FOR 3_MONTH PERIOD						
ENDING SEP 0 9 2011						
14. I hereby certify that the foregoing is true	e and correct.				······	
Name (Printed/Typed) Carlton Wheeler			Title Operations Manager			
Signature Cartton Wheeles Date 06/09/2011						
	THIS SPACE FO	DR FEDE	RAL OR STA	TE OFFI	CE USE	
Approved by /S/DAVI	A I I I I I A	ROLEUM		JUN 1 6 2011		
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations therein.						
Title 18 U.S.C. Section 1001 and Title 43.U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fiotitious or fraudulent statements or representations as to any matter within its jurisdiction.						
(Instructions on page 2) SEE ATTACHED FOR						
COPY CONDITIONS OF APPROVAL JUL 1 8 2011						

BUREAU OF LAND MANAGEMENT Roswell Field Office 2909 West Second Street Roswell, New Mexico 88201 (575) 627-0272

Permanent Abandonment of Federal Wells Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon. If you are unable to plug the well by the 90th day provide the BLM Roswell Field Office, prior to the 90th day, with the reason for not meeting the deadline and a date when the BLM Roswell Field Office can expect the well to be plugged. Failure to do so will result in enforcement action.

2. <u>Notification:</u> Contact the BLM Roswell Field Office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, during office hours call (575) 627-0205 or after office hours call (575) 420-2832. Engineer on call during office hours phone (575) 627-0275 or phone (after hours) call (575) 626-5749.

3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The minimum BOP requirement is a 2M system for a well not deeper than 9090 feet; a 3M system for a well not deeper than 13636 feet; and a 5M system for a well not deeper than 22727 feet.

4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at a rate of 25 sacks (50 pounds each) of gel per 100 barrels of water. Minimum nine (9) pounds per gallon.

5. <u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. In lieu of a cement plug in cased hole, a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 50 feet of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either class "C" for up to 7500 feet of depth, mixed at 14.8 lbs./gal with 6.3 gallons of fresh water per sack or class "H" for deeper than 7500 feet plugs, mixed at 16.4 lbs./gal with 4.3 gallons of fresh water per sack.

6. <u>Monument:</u> Upon abandonment of the well, all casing shall be cut-off at the base of the cellar or 3-feet below final restored ground level (whichever is deeper). The well bore shall then be covered with a metal plate at least ¼ inch thick and welded in place. The following information shall be permanently inscribed on the dry hole marker: Well name and number, the name of the operator, the lease serial number, the surveyed location (the quarter-quarter section, township and range or other authorized survey designation acceptable to the authorized officer; such as metes and bounds).

7. <u>Subsequent Plugging Reporting:</u> Within 30 days after plugging work is completed, file one original and five copies of the Subsequent Report of Abandonment, Form 3160-5 to the BLM Roswell Field Office. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. <u>Show date well was plugged.</u>

Following the submittal and approval of the Subsequent Report of Abandonment, a Notice of Intent for Final Abandonment with the proposed surface restoration procedure must be submitted for approval.