Submit 3 Copies To Appropriate District Office	Diate of Item Mexico	Form C-103 June 19, 2008
<u>District I</u> 1625 N French Dr , Hobbs, NM 88240	Energy, Minerals and Natural Reso	
District II	SOCO OIL CONSERVATION DIVIS	ION 30-025-39954 /
District III	1220 South St. Francis Dr.	5. Indicate Type of Lease STATE FEE
1 000 Rio Brazos Rd., Aztec, NM 8741 0 District IV	97 2011 Santa Fe, NM 87505	6. State Oil & Gas Lease No.
1220 S St Francis Dr., Santa Fe, NM		V-8232
87505 SUNDRY NOT	TICES REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROP DIFFERENT RESERVOIR, USE "APPLI	TO DRILL OR TO DEEPEN OR PLUG BACK CATION FOR PERMIT" (FORM C-101) FOR SUCH	TO A Paint State
PROPOSALS.) 1. Type of Well: Oil Well	Gas Well Other	8. Well Number 1
2. Name of Operator	das weir 📋 Other	9. OGRID Number
Mack	Energy Corporation	013837
3. Address of Operator	50.4	10. Pool Name or Wildcat
4. Well Location	60 Artesia, NM· 88210	Wildcat; Bone Springs
Unit Letter E	1650 feet from the North lir	e and 990 feet from the West line
Section 1		35E NMPM County Lea
	11. Elevation (Show whether DR, RKB, R	TWIN IVI County
Salar Salar	3889' GR	
12 Check	Appropriate Box to Indicate Nature of	Notice Report or Other Data
	***	•
	NTENTION TO: Clade and Nate	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK TEMPORARILY ABANDON	<u> </u>	DIALWORK ☐ ALTERING CASING ☐ ENCE DRILLING OPNS.☐ P AND A ☐
PULL OR ALTER CASING	_ 	G/CEMENT JOB
DOWNHOLE COMMINGLE	_	
OTHER:	· □ OTHER	:
13. Describe proposed or com		letails, and give pertinent dates, including estimated date
of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.		
Mack Energy Corporation proposes to Plug and Abandoned as follows:		
Mack Energy Corporation proposes to Flug and Abandoned as follows.		
1. Notify OCD 24 hours prior to starting plugging operations.		
2. Set CIBP @ 7700' w/35' cement cap.		
3, Set 25sx plug from 5709-5966'(cover Bone Spring)		
4. Set 50sx plug from 4790-5220'(cover Grayburg/SA). 5. Set 25sx plug from 2980-3236'(cover BOS).		
	(cover TOS and surface casing shoe). WO	C and tag.
7. TIH w/tubing to 65' circ cemen		
8. Install Dry Hole Marker.		•
	•	servation Division Must be notified
	24 nours pri	or to the beginning of plugging operations.
Spud Date: 2/27/20	Rig Release Date:	3/22/2011
2/2//20		3/22/2011
I h analas a saife al ad al a información		
nereby certify that the information	above is true slid complete to the best of my	knowledge and belief.
()	CIM	
SIGNATURE Jeny W.	TITLE Production Cler	DATE 7/6/11
Type or print name Jerry W. Sherr	ell E-mail address: ierrvs@	@mackenergycorp.com PHONE: (575)748-1288
For State Use Only		111ONE. (5/5)/10 1200
5/-		ENGZ DATE 7-18-2011
APPROVED BY Conditions of Approval (it any):	TILLE STOPP	MGZ DATE 7-18-2011

Mack Energy Corporation Paint State #1 30-025-39954

