	State of New Mexico	Form C-103
Office <u>District I</u> – (575) 393-6161	Energy, Minerals and Natural Resources	October 13, 2009
1625 N French Dr , Hobbs, NM 88240	AAA	WELL API NO.
District II - (575) 748-1283 <b>HOBB</b> 811 S First St , Artesia, NM 88210	S OCC CONSERVATION DIVISION	30-025-28659
District III. (505) 224 6179	2 2011 1220 South St. Francis Dr.	5. Indicate Type of Lease STATE FEE
1000 Rio Brazos Rd , Aztec, NM 87419UL 2 District IV – (505) 476-3460	2 2011 Santa Fe, NM 87505	6. State Oil & Gas Lease No.
1220 S St Francis Dr , Santa Fe, NM		V-732-2
87505		
	REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
	S TO DRILL OR TO DEEPEN OR PLUG BACK TO A ON FOR PERMIT" (FORM Ç-101) FOR SUCH	NM DL State
PROPOSALS)	_	8. Well Number #6
	s Well  Other	/
2. Name of Operator		9. OGRID Number
ENDURANCE RESOURCES, LLC  3. Address of Operator		270329 10. Pool name or Wildcat
PO BOX 1466 ARTESIA, NM 88211		Cruz Delaware
		Cruz Delaware
4. Well Location	co c c d court	
	feet from theSOUTH line and	
Section 18	Township 23S Range 33E	
	1. Elevation (Show whether DR, RKB, RT, GR,	, etc.)
		Alexander of the second
12 01 1 4		
12. Check App	propriate Box to Indicate Nature of Not	ice, Report or Other Data
NOTICE OF INTE	NTION TO:	SUBSEQUENT REPORT OF:
	LUG AND ABANDON   REMEDIAL V	
		E DRILLING OPNS. P AND A
	IULTIPLE COMPL	
DOWNHOLE COMMINGLE	_	_
		·
OTHER:	OTHER:	
		s, and give pertinent dates, including estimated date
proposed completion or recomp	SEE RULE 19.15.7.14 NMAC. For Multiple	E Completions: Attach wellbore diagram of
proposed completion of recomp	netion.	
6/27/2011 MOVE IN RIG UP AND IN	STALL BOP.	
6/28/2011 UNSET ANCHOR, TALLEY		
		SP AND SET AT 5090'. CIRCULATE HOLE
WITH BRINE AND MUD. TEST CAS		BP AND SET AT 5090'. CIRCULATE HOLE C CEMENT ON TOP OF CIBP. DID NOT TAG
WITH BRINE AND MUD. TEST CAS AS PER OCD.	SINGHELD 350 PSI. SPOT 25 SX CALSS	C CEMENT ON TOP OF CIBP. DID NOT TAG
WITH BRINE AND MUD. TEST CAS AS PER OCD. 6/29/2011 POH TO 3098' AND SPOT	SINGHELD 350 PSI. SPOT 25 SX CALSS 25 SX CLASS C CEMENT. WOC AND TAC	C CEMENT ON TOP OF CIBP. DID NOT TAG  GGED AT 2883'. POH TO 1310' AND SPOT 25
WITH BRINE AND MUD. TEST CAS AS PER OCD. 6/29/2011 POH TO 3098' AND SPOT	SINGHELD 350 PSI. SPOT 25 SX CALSS 25 SX CLASS C CEMENT. WOC AND TAC	C CEMENT ON TOP OF CIBP. DID NOT TAG
WITH BRINE AND MUD. TEST CAS AS PER OCD. 6/29/2011 POH TO 3098' AND SPOT	SINGHELD 350 PSI. SPOT 25 SX CALSS 25 SX CLASS C CEMENT. WOC AND TAC	C CEMENT ON TOP OF CIBP. DID NOT TAG  GGED AT 2883'. POH TO 1310' AND SPOT 25
WITH BRINE AND MUD. TEST CAS AS PER OCD. 6/29/2011 POH TO 3098' AND SPOT SX CLASS C CEMENT. DID NOT TA	SINGHELD 350 PSI. SPOT 25 SX CALSS 25 SX CLASS C CEMENT. WOC AND TAC	GGED AT 2883'. POH TO 1310' AND SPOT 25 ULATED CLASS C CEMENT TO SURFACE.  RS. Approved for plugging of well bore only.
WITH BRINE AND MUD. TEST CAS AS PER OCD. 6/29/2011 POH TO 3098' AND SPOT SX CLASS C CEMENT. DID NOT TA	SINGHELD 350 PSI. SPOT 25 SX CALSS 25 SX CLASS C CEMENT. WOC AND TAC AG AS PER OCD. POH TO 758' AND CIRCU	GGED AT 2883'. POH TO 1310' AND SPOT 25 ULATED CLASS C CEMENT TO SURFACE.  RS. Approved for plugging of well bore only. Liability under bond is retained pending receipt
WITH BRINE AND MUD. TEST CAS AS PER OCD. 6/29/2011 POH TO 3098' AND SPOT SX CLASS C CEMENT. DID NOT TA	SINGHELD 350 PSI. SPOT 25 SX CALSS 25 SX CLASS C CEMENT. WOC AND TAC AG AS PER OCD. POH TO 758' AND CIRCU	GGED AT 2883'. POH TO 1310' AND SPOT 25 ULATED CLASS C CEMENT TO SURFACE.  RS. Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging)
WITH BRINE AND MUD. TEST CAS AS PER OCD. 6/29/2011 POH TO 3098' AND SPOT SX CLASS C CEMENT. DID NOT TA	SINGHELD 350 PSI. SPOT 25 SX CALSS 25 SX CLASS C CEMENT. WOC AND TAC AG AS PER OCD. POH TO 758' AND CIRCU	GGED AT 2883'. POH TO 1310' AND SPOT 25 ULATED CLASS C CEMENT TO SURFACE.  RS. Approved for plugging of well bore only. Liability under bond is retained pending receipt
WITH BRINE AND MUD. TEST CAS AS PER OCD.  6/29/2011 POH TO 3098' AND SPOT SX CLASS C CEMENT. DID NOT TA	SINGHELD 350 PSI. SPOT 25 SX CALSS  25 SX CLASS C CEMENT. WOC AND TAC  AG AS PER OCD. POH TO 758' AND CIRCU  ISTALL MARKER, AND CUT OFF ANCHO	GGED AT 2883'. POH TO 1310' AND SPOT 25 ULATED CLASS C CEMENT TO SURFACE.  RS. Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.cmnrd.state.nm.us/ocd.
WITH BRINE AND MUD. TEST CAS AS PER OCD.  6/29/2011 POH TO 3098' AND SPOT SX CLASS C CEMENT. DID NOT TA	SINGHELD 350 PSI. SPOT 25 SX CALSS 25 SX CLASS C CEMENT. WOC AND TAC AG AS PER OCD. POH TO 758' AND CIRCU	GGED AT 2883'. POH TO 1310' AND SPOT 25 ULATED CLASS C CEMENT TO SURFACE.  RS. Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.cmnrd.state.nm.us/ocd.
WITH BRINE AND MUD. TEST CAS AS PER OCD.  6/29/2011 POH TO 3098' AND SPOT SX CLASS C CEMENT. DID NOT TA	SINGHELD 350 PSI. SPOT 25 SX CALSS  25 SX CLASS C CEMENT. WOC AND TAC  AG AS PER OCD. POH TO 758' AND CIRCU  ISTALL MARKER, AND CUT OFF ANCHO	GGED AT 2883'. POH TO 1310' AND SPOT 25 ULATED CLASS C CEMENT TO SURFACE.  RS. Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.cmnrd.state.nm.us/ocd.
WITH BRINE AND MUD. TEST CAS AS PER OCD.  6/29/2011 POH TO 3098' AND SPOT SX CLASS C CEMENT. DID NOT TA  7/11/2011 CUT OFF WELL HEAD, IN	SINGHELD 350 PSI. SPOT 25 SX CALSS 25 SX CLASS C CEMENT. WOC AND TACK AG AS PER OCD. POH TO 758' AND CIRCU STALL MARKER, AND CUT OFF ANCHO  EVE is true and complete to the best of my know	GGED AT 2883'. POH TO 1310' AND SPOT 25 ULATED CLASS C CEMENT TO SURFACE.  RS. Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.cmnrd.state.nm.us/ocd.  ledge and belief.
WITH BRINE AND MUD. TEST CAS AS PER OCD.  6/29/2011 POH TO 3098' AND SPOT SX CLASS C CEMENT. DID NOT TA	SINGHELD 350 PSI. SPOT 25 SX CALSS  25 SX CLASS C CEMENT. WOC AND TACK  AG AS PER OCD. POH TO 758' AND CIRCU  ISTALL MARKER, AND CUT OFF ANCHO  We is true and complete to the best of my known  TITLE  FEUCOL, ST	GGED AT 2883'. POH TO 1310' AND SPOT 25 ULATED CLASS C CEMENT TO SURFACE.  RS. Approved for plugging of well hore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.cmnrd.state.nm.us/ocd.  DATE 7/18/1/
WITH BRINE AND MUD. TEST CAS AS PER OCD.  6/29/2011 POH TO 3098' AND SPOT SX CLASS C CEMENT. DID NOT TA 7/11/2011 CUT OFF WELL HEAD, IN SIGNATURE	SINGHELD 350 PSI. SPOT 25 SX CALSS  25 SX CLASS C CEMENT. WOC AND TACK  AG AS PER OCD. POH TO 758' AND CIRCU  ISTALL MARKER, AND CUT OFF ANCHO  We is true and complete to the best of my known  TITLE  FEUCOL, ST	GGED AT 2883'. POH TO 1310' AND SPOT 25 ULATED CLASS C CEMENT TO SURFACE.  RS. Approved for plugging of well hore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.cmnrd.state.nm.us/ocd.  DATE 7/18/1/
WITH BRINE AND MUD. TEST CAS AS PER OCD.  6/29/2011 POH TO 3098' AND SPOT SX CLASS C CEMENT. DID NOT TA  7/11/2011 CUT OFF WELL HEAD, IN	SINGHELD 350 PSI. SPOT 25 SX CALSS  25 SX CLASS C CEMENT. WOC AND TACK  AG AS PER OCD. POH TO 758' AND CIRCU  ISTALL MARKER, AND CUT OFF ANCHO  We is true and complete to the best of my known  TITLE  FEUCOL, ST	GGED AT 2883'. POH TO 1310' AND SPOT 25 ULATED CLASS C CEMENT TO SURFACE.  RS. Approved for plugging of well hore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.cmnrd.state.nm.us/ocd.  DATE 7/18/1/
WITH BRINE AND MUD. TEST CAS AS PER OCD.  6/29/2011 POH TO 3098' AND SPOT SX CLASS C CEMENT. DID NOT TA 7/11/2011 CUT OFF WELL HEAD, IN SIGNATURE  Type or print name Randau	SINGHELD 350 PSI. SPOT 25 SX CALSS  25 SX CLASS C CEMENT. WOC AND TACK  AG AS PER OCD. POH TO 758' AND CIRCU  ISTALL MARKER, AND CUT OFF ANCHO  We is true and complete to the best of my known  TITLE  FEUCOL, ST	GGED AT 2883'. POH TO 1310' AND SPOT 25 ULATED CLASS C CEMENT TO SURFACE.  RS. Approved for plugging of well hore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.cmnrd.state.nm.us/ocd.  DATE 7/S/N  DATE 7/S/N  DATE 7/S/N  DATE 7/S/N
WITH BRINE AND MUD. TEST CAS AS PER OCD.  6/29/2011 POH TO 3098' AND SPOT SX CLASS C CEMENT. DID NOT TA 7/11/2011 CUT OFF WELL HEAD, IN SIGNATURE  Type or print name Randau	SINGHELD 350 PSI. SPOT 25 SX CALSS  25 SX CLASS C CEMENT. WOC AND TACK  AG AS PER OCD. POH TO 758' AND CIRCU  ISTALL MARKER, AND CUT OFF ANCHO  We is true and complete to the best of my known  TITLE  FEUCOL, ST	GGED AT 2883'. POH TO 1310' AND SPOT 25 ULATED CLASS C CEMENT TO SURFACE.  RS. Approved for plugging of well hore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.cmnrd.state.nm.us/ocd.  DATE 7/18/1/